



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power [W] - range:</b>	30-53
<b>Luminous flux of the luminaire [lm] - range:</b>	1890 - 6100
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour temperature [K] - range:</b>	2700 - 6500
<b>Frequency [Hz]:</b>	50 - 60
<b>SDCM:</b>	3
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Electrical protection class:</b>	I
<b>Diffuser material:</b>	PMMA; PS
<b>Diffuser type:</b>	OPAL
<b>Colour of the body:</b>	black; white
<b>Dimensions (H/W/T/S) [mm]:</b>	ø602/32; ø602/68; ø900/32; ø900/68; ø1200/32
<b>Mounting version:</b>	surface; suspended
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

### Solanto – Light That Defines Space. Elegance in the Form of a Ring.

Solanto is an LED fixture that combines minimalist design with functionality, creating a striking focal point in any arrangement. Its timeless ring shape emphasizes the prestige of prestigious interiors such as lobbies, reception areas, galleries, and sales areas, and also blends perfectly into apartments and modern homes.

#### Why choose Solanto?

- Freedom of arrangement – available in suspended or surface-mounted versions, it allows for adaptation to the character of the space.
- Customizable colors – powder-coated steel body in white, black, or a color individually selected for the project.
- Harmonious light – the opal thermoformed diffuser provides soft, even light distribution, emphasizing the decorative character of the fixture.
- Flexible Multi-LED technology – four flux and power settings in one fixture, simplifying design and reducing the number of indexes.
- Complete mounting system – the pendant version includes a central box and all accessories, ready for installation.

#### Benefits for designers:

- Flexible design – a single design language across various mounting options.
- Freedom to create lighting arrangements – lamps of different sizes can be suspended at different heights.
- Visual lightness – the delicate rings do not dominate the interior, but are its decoration.

**Solanto – more than just lighting. It is a design element.**

## APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

# SOLANTO

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### SOLANTO surface

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
30/38/45/53	4000	2820/3570/4200/4980	white		ø602/68	surface	<a href="#">&gt;&gt; 463006</a>
30/38/45/53	3000	2550/3200/3800/4500	white		ø602/68	surface	<a href="#">&gt;&gt; 463013</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø602/68	surface	<a href="#">&gt;&gt; 463129</a>
30/38/45/53	3000	1890/2400/2800/3330	black		ø602/68	surface	<a href="#">&gt;&gt; 463136</a>
30/38/45/53	3000	1890/2400/2800/3330	black		ø900/68	surface	<a href="#">&gt;&gt; 463372</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø900/68	surface	<a href="#">&gt;&gt; 463365</a>
30/38/45/53	3000	2550/3200/3800/4500	white		ø900/68	surface	<a href="#">&gt;&gt; 463259</a>
30/38/45/53	4000	2820/3570/4200/4980	white		ø900/68	surface	<a href="#">&gt;&gt; 463242</a>
38	4000	2590	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463143</a>
38	3000	2400	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463150</a>
38	3000	3230	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463037</a>
38	4000	3570	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463020</a>
38	4000	2590	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463389</a>
38	4000	3570	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463266</a>
38	3000	3230	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463273</a>
38	3000	2400	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463396</a>
53	4000	3600	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463167</a>
53	4000	4980	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463044</a>
53	3000	4500	white	yes	ø602/68	surface	<a href="#">&gt;&gt; 463051</a>
53	3000	3340	black	yes	ø602/68	surface	<a href="#">&gt;&gt; 463174</a>
53	4000	4980	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463280</a>
53	3000	4500	white	yes	ø900/68	surface	<a href="#">&gt;&gt; 463297</a>
53	4000	3600	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463402</a>
53	3000	3340	black	yes	ø900/68	surface	<a href="#">&gt;&gt; 463419</a>

### SOLANTO suspended

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
30/38/45/53	4000	2820/3570/4200/4980	white		ø602/32	suspended	<a href="#">&gt;&gt; 463068</a>
30/38/45/53	3000	2550/3200/3800/4500	white		ø602/32	suspended	<a href="#">&gt;&gt; 463075</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø602/32	suspended	<a href="#">&gt;&gt; 463181</a>
30/38/45/53	3000	1890/2400/2800/3330	black		ø602/32	suspended	<a href="#">&gt;&gt; 463198</a>
30/38/45/53	3000	1890/2400/2800/3330	black		ø900/32	suspended	<a href="#">&gt;&gt; 463433</a>
30/38/45/53	4000	2040/2600/3000/3600	black		ø900/32	suspended	<a href="#">&gt;&gt; 463426</a>

# SOLANTO

## GENERAL CARD

Rated power [W] - range	Colour temperature [K]	Luminous flux of the luminaire [lm] - range	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Mounting version	Index
30/38/45/53	3000	2550/3200/3800/4500	white		ø900/32	suspended	<a href="#">&gt;&gt; 463310</a>
30/38/45/53	4000	2820/3570/4200/4980	white		ø900/32	suspended	<a href="#">&gt;&gt; 463303</a>
38	4000	3570	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463082</a>
38	3000	3230	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463099</a>
38	4000	2590	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463204</a>
38	3000	2400	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463211</a>
38	4000	3570	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463327</a>
38	3000	3230	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463334</a>
38	4000	2590	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463440</a>
38	3000	2400	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463457</a>
53	3000	3340	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463235</a>
53	4000	3600	black	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463228</a>
53	3000	4500	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463112</a>
53	4000	4980	white	yes	ø602/32	suspended	<a href="#">&gt;&gt; 463105</a>
53	3000	4500	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463358</a>
53	3000	3340	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463471</a>
53	4000	3600	black	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463464</a>
53	4000	4980	white	yes	ø900/32	suspended	<a href="#">&gt;&gt; 463341</a>
62	3000	3900	black	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467974</a>
62	3000	3900	black		ø1200/32	suspended	<a href="#">&gt;&gt; 467936</a>
62	4000	4300	black	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467967</a>
62	4000	4300	black		ø1200/32	suspended	<a href="#">&gt;&gt; 467929</a>
62	3000	5060	white	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467998</a>
62	3000	5060	white		ø1200/32	suspended	<a href="#">&gt;&gt; 467950</a>
62	4000	5620	white	yes	ø1200/32	suspended	<a href="#">&gt;&gt; 467981</a>
62	4000	5620	white		ø1200/32	suspended	<a href="#">&gt;&gt; 467943</a>
68		4300	black		ø1200/32	suspended	<a href="#">&gt;&gt; 467370</a>

Card creation date: 18 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 217/2023; 218/2023; 34/2022