# PLASTER LITE FUTURE LED

GENERAL CARD





### **TECHNICAL PARAMETERS**

Ingress protection: IP54 Impact resistance: IK07 Rated power of the luminaire [W]\*: 49.00 6100 Luminous flux [lm]\*: Colour temperature [K]: 4000 **Energy efficiency class:** D **Electrical protection class:** 80 Color rendering index (Ra) >: 50 - 60 Frequency [Hz]: 45/120 Beam angle [°]: Diffuser material: PC

Diffuser type:transparentMaterial of the body:PC + aluminiumWorking temperature [°C]:from -20 to +35Dimensions (H/W/T/S) [mm]:490/592/70;

Warranty [years]: 5

## **CHARACTERISTICS**

Modern and efficient luminaire It provides even and solid illumination of the working surface so that all surface irregularities are immediately visible. Powerful LEDs and lenses ensure that the beam is focused along the wall surface which highlights irregularities and minor surface defects already during the job and eliminates the need for touch-ups after the job is completed. Body made of aluminum and rubber, highly resistant to impacts and water splashes. The diffuser is made of transparent polycarbonate PC. A quick-mounting stand is available as an additional accessory so that the position of the luminaire can be adapted to the work at hand.

#### **APPLICATION**

Detection of defects and unevenness in the surface to be treated already at the working stage. Puttying work, plastering work, painting work, construction site, an inspection of completed work.



# **PLASTER LITE FUTURE LED**

**GENERAL CARD** 

#### **AVAILABLE VERSIONS**



Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Beam angle [°]	Material of the body	Dimensions (H/W/T/S) [mm]	Index
49	6100	4000	45/120	PC + aluminium	490/592/70	>> 359217

Card creation date: 06 July 2021





This product is a subject to electric and electronic waste equipment regulations (WEEE).