UV-C STERILON FLOW 72W

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	72.00
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Exchangeable source:	yes
Material of the body:	powder coated carbon steel
Colour of the body:	white-silver
Dimensions (H/W/T/S) [mm]:	724/160/160;
Ingress protection:	IP20
Mounting version:	detached
Version:	dual-purpose
Flow air disinfection function:	yes
Max volume of the disinfected room [m3]:	75.00
Warranty [years]:	2
Direct surface disinfection function:	yes

CHARACTERISTICS

UV-C STERILON FLOW 72W luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is available as dual-function products.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 72W

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Air flow [m3 / h]	Working time counter	Protection against opening	HEPA filter holder	Index
72	9000	UNI-SCHUKO	3	I	160			yes	>> 246456
72	9000	UNI-SCHUKO	3	I	160	yes	yes	yes	>> 240546
72	9000	UNI-SCHUKO	3	I	160	yes		yes	>> 240522
72	9000	UNI-SCHUKO	3	I	160		yes	yes	>> 240416

UV-C STERILON FLOW 72W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
243677	HEPA H10 filter - set of 5 only for the Flow model
243639	UV-C protective glasses
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
243646	Set of guide wheels Sterilon Flow 72W matt white
240485	Wall bracket STERILON FLOW 72W



HEPA H10 filter - set of 5 only for the Flow model (243677)



UV-C protective glasses (243639)



Set of guide wheels Sterilon Flow 72W matt white (243646)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 324/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl