UV-C STERILON AIR LIGHT 144W

GENERAL CARD





TECHNICAL PARAMETERS

Nominal power [W]: 144.00

Supply voltage [V]: 220 - 240

Electrical protection class:

Material of the body: powder coated carbon

steel

Colour of the body: white / endcap gray

Dimensions (H/W/T/S) [mm]: 600/148/148;

Ingress protection: IP20

investment version to be connected to the

electrical installation; wall

version with a cord for the

socket 120.00

Max volume of the disinfected room

[m3]:

Mounting version:

Warranty [years]: 2

CHARACTERISTICS

UV-C STERILON AIR LIGHT flow luminaires are intended for wall mounting. Luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. Luminaires are available with a 3-meter power cord and without a cord (the so-called investment version).

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.



UV-C STERILON AIR LIGHT 144W

GENERAL CARD

AVAILABLE VERSIONS



Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Air flow [m3 / h]	Working time counter	Net weight [kg]	Index
144	9000	UNI- SCHUKO	3	I	220 - 240	160	yes	4.900	>> 240638
144	9000			I	220 - 240	160	yes	4.900	>> 240577



UV-C STERILON AIR LIGHT 144W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Card creation date: 08 November 2023





This product is a subject to electric and electronic waste equipment regulations (WEEE).