UV-C STERILON FLOW 72W MONO

GENERAL CARD

TECHNICAL PARAMETERS

Nominal power [W]:	72.00
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	powder coated carbon steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	724/160/160;
Ingress protection:	IP20
Mounting version:	detached
Version:	single-function
Max volume of the disinfected room [m3]:	60.00
Warranty [years]:	2

CHARACTERISTICS

UV-C STERILON FLOW 72W MONO luminaire emitting ultraviolet (UV-C) light is one of the most effective devices capable of removing viruses, bacteria, fungi from the environment or destroying the DNA or RNA of any exposed microorganisms.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 72W MONO

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Nominal power [W]	Service life of the UV-C radiation source [h]	Version	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Air flow [m3 / h]	Working time counter	HEPA filter holder	Index
72	9000	single-function	UNI-SCHUKO	3	I	220 - 240	110		yes	>> 246449
72	9000	single-function	UNI-SCHUKO	3	I	220 - 240	110	yes	yes	>> 240515

LENA LIGHTING

UV-C STERILON FLOW 72W MONO

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240478	Wall bracket STERILON FLOW MONO
243653	Set of guide wheels Sterilon Flow 72W gloss white
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Set of guide wheels Sterilon Flow 72W
gloss white (243653)

This product is a subject to electric andelectronic waste equipment regulations (WEEE).   CE   Certificate CE - Nr: 339/2023