UV-C STERILON AIR 144W/Z1

GENERAL CARD





TECHNICAL PARAMETERS

Nominal power [W]: 144.00

Supply voltage [V]: 220 - 240

Electrical protection class:

Material of the body: carbon steel

Colour of the body: white / endcap gray

Dimensions (H/W/T/S) [mm]: 1082/471/471;

Ingress protection: IP20

Mounting version: version on a mobile stand

150.00

329/2023

Max volume of the disinfected room

[m3]:

CE certificate:

5].

CHARACTERISTICS

STERILON AIR Z1 UV-C flow luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. Thanks to the movable base fitted as standard, the luminaire is easy to move. Selected versions are equipped with a 3-meter power cord and a switch. The luminaire is equipped with ECO mode, which makes its operation quieter.

APPLICATION


Luminaires are recommended for use in service-providing facilities (hair and beauty salons), healthcare facilities, hotels, restaurants, public administration, educational and care facilities, gyms.



UV-C STERILON AIR 144W/Z1

GENERAL CARD

AVAILABLE VERSIONS



Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Air flow in ECO mode [m3 / h]	Air flow [m3 / h]	ECO mode	Working time counter	Index
144	9000	UNI- SCHUKO	3	I	220 - 240	110	220	yes	yes	>> 244261



UV-C STERILON AIR 144W/Z1

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

