UV-C STERILON HEPA

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]: 216.00

Supply voltage [V]: 220 - 240

Electrical protection class:

Material of the body: powder coated carbon

steel

Colour of the body: black and gold; white-

silver

Dimensions (H/W/T/S) [mm]: 724/260/260;

Ingress protection: IP20

Mounting version: detached

Max volume of the disinfected room

[m3]:

300.00

Warranty [years]: 2

CHARACTERISTICS

UV-C STERILON HEPA flow luminaires emitting ultraviolet (UV-C) light are one of the most effective (99.9%) devices capable of safely removing viruses, bacteria, and mold from the environment in the presence of people and animals.

Air-flow adjustment (noise level): 25% fan power = ~70 m3/h (~38dB) 50% fan power = ~90 m3/h (~44dB) 75% fan power = ~110 m3/h (~48dB) 100% fan power = ~200 m3/h (~51,5dB)

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.



UV-C STERILON HEPA

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Service life of the UV-C radiation source [h]	Colour of the body	Plug type	Cable length [m]	Air flow [m3 / h]	ECO mode adjustment	Working time counter	HEPA filter holder	Net weight [kg]	ECO mode	Index
216	9000	white-silver	UNI- SCHUKO	3	200	yes	yes	yes	15.720	yes	>> 245985
216	9000	black and gold	UNI- SCHUKO	3	200	yes	yes	yes	14.590	yes	>> 245992



UV-C STERILON HEPA

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244315	HEPA H13 + CARBON filter

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

