### **UV-C STERILON AIR LIGHT 72W/Z4**

**GENERAL CARD** 





### **TECHNICAL PARAMETERS**

Nominal power [W]: 288.00

**Supply voltage [V]:** 220 - 240

Electrical protection class:

Material of the body: powder coated carbon

steel

440.00

Colour of the body: white / endcap gray

Dimensions (H/W/T/S) [mm]: 1082/471/471;

Ingress protection: IP20

Mounting version: version on a mobile stand

Max volume of the disinfected room

[m3]:

Warranty [years]: 2

### **CHARACTERISTICS**

**STERILON AIR LIGHT Z4 UV-C** flow luminaires in the form of a set of disinfection luminaires integrated with a stand with wheels. Luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. The luminaires are equipped with a 3-meter power cord and an on-off switch.

### APPLICATION

Luminaires are recommended for use in large service-providing facilities (hair and beauty salons), healthcare facilities, hotels, restaurants, public administration, educational and care facilities, gyms.



# **UV-C STERILON AIR LIGHT 72W/Z4**

GENERAL CARD

#### **AVAILABLE VERSIONS**



Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Air flow [m3 / h]	Working time counter	Index
288	9000	UNI- SCHUKO	3	I	220 - 240	440	yes	>> 244308



## **UV-C STERILON AIR LIGHT 72W/Z4**

GENERAL CARD

#### **ACCESSORIES AVAILABLE**

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

