

CROP FUTURE LED

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	4.00
Luminous flux [lm]*:	400
Colour temperature [K]:	6500
Diffuser material:	ABS
Diffuser type:	transparent
Dimensions (H/W/T/S) [mm]:	255/58/45;

CHARACTERISTICS

The manual LED luminaire is a proposal for people working in a car workshop, mobile service center, garage, or on a construction site. Professionals and DIY enthusiasts alike will benefit from the functionality of the LED hand-held luminaire - everyone for whom good lighting is important during work or hobby. The luminaire is characterized by high durability, a strong light beam, and a long working time, which allows you to focus on the task. At the same time, the emitted light is pleasant to the eyes, and the energy-saving LED technology itself.

- Light source: 4 W COB LED + 4 W SMD LED (above)
- Lighting time: 400 lm - 3,5 h, 120 lm - 10 h
- Protection class III
- The set includes a 1.5 m microUSB cable
- Ingress protection class: IP54
- Dimensions: 255x58x45 mm
- Weight: 110 g
- Battery Li-ion 3,7V 2600 mAh
- Charging time: 3 h
- Magnet on the bottom of the lamp

APPLICATION

It is used as a working luminaire for lighting workplaces, workshops, or garages.

CROP FUTURE LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser material	Diffuser type	Dimensions (H/W/T/S) [mm]	Index
4	6500	400	ABS	transparent	255/58/45	>> 608599

Card creation date: 13 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 278/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl