

CLIMA EVO UV

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	1.00
Diffuser colour:	transparent
Material of the body:	aluminium
Colour of the body:	black
Battery:	18650 lithium battery 2000Mah
Dimensions (H/W/T/S) [mm]:	37/31/182;
Electrical protection class:	III

CHARACTERISTICS

Special set for checking for leaks in the A/C system. Professional tools for every car workshop and mobile service that professionally deals with air conditioning. Thanks to the use of appropriate UV wavelengths and special protective goggles the leak location is clearly visible.

- Power: 1 W
- Light source: UV LED
- Burning time 3h
- Charging time: 3,5h
- Aluminium body
- Functions: 100% on/off • ZOOM
- Complete with:
 - black wristband
 - 2000 mAh lithium battery
 - UV glasses
- Weight: 0.143 kg
- Non-removable luminaire

APPLICATION

It is used as a working fixture to test for leaks in the air conditioning system.

CLIMA EVO UV

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Material of the body	Colour of the body	Diffuser colour	Dimensions (H/W/T/S) [mm]	Battery capacity [mAh]	Plug type	Index
1	aluminium	black	transparent	37/31/182	2000	Charging cable with pin C	>> 608575

Card creation date: 28 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 293/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl