

PELICAN EVO LED

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED
Rated power of the luminaire [W]*:	2.00
Colour temperature [K]:	6500
Material of the body:	ABS + PC
Colour of the body:	grey
Diffuser colour:	transparent
Dimensions (H/W/T/S) [mm]:	252 /55/41;

CHARACTERISTICS

The manual LED luminaire is a proposal for people working in a car workshop, mobile service center, garage, or on a construction site. Professionals and DIY enthusiasts alike will benefit from the functionality of the LED hand-held luminaire - everyone for whom good lighting is important during work or hobby. The luminaire is characterized by high durability, a strong light beam, and a long working time, which allows you to focus on the task. At the same time, the emitted light is pleasant to the eyes, and the energy-saving LED technology itself.

APPLICATION

It is used as a working luminaire for lighting workplaces, workshops, or garages.

PELICAN EVO LED

GENERAL CARD

AVAILABLE VERSIONS

 Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Battery	Battery capacity [mAh]	Diffuser colour	Material of the body	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
2	6500	Li-ion 3.7V 4400 mAh Li-ion (2x 18650)	4400	transparent	ABS + PC	grey	252 /55/41	>> 608582

Card creation date: 06 August 2021
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 280/2023