

ARTO 2 LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Rated power of the luminaire [W]*:	21.00 - 53.00
Luminous flux [lm]*:	2070 - 5270
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
SDCM:	3
Material of the body:	powder coated steel
Diffuser material:	PS
Diffuser type:	OPAL
Mounting version:	recessed mounted in modular ceiling possible; surface mounted
Dimensions (H/W/T/S) [mm]:	592/592/45;
Warranty [years]:	5

CHARACTERISTICS

Surface-mounted modular ceiling luminaire with integrated energy-efficient LED panel made of white powder-coated steel. Opalized polystyrene diffuser ensures uniform light distribution. The central part of the luminaire is a louvre, which is a part of a modular ceiling. Thanks to it the luminaire perfectly fits into the interior decor.

APPLICATION

Multifunctional luminaire designed for surface mounting with the possibility of flush installation in modular ceilings in office, representative, or general utility rooms. It is also used as the main source of light. Luminaire is perfect for new applications as well as for replacing traditional fluorescent fixtures with energy-saving LED solutions.

ARTO 2 LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details


Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Motion sensor	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
21	3000	2070	yes		592/592/45	>> 021220
21	4000	2250			592/592/45	>> 021046
21	4000	2250	yes		592/592/45	>> 021176
21	3000	2070			592/592/45	>> 021114
26	3000	2600			592/592/45	>> 021107
26	3000	2600	yes		592/592/45	>> 021213
26	4000	2820			592/592/45	>> 021039
26	4000	2820	yes		592/592/45	>> 021169
31	3000	3100			592/592/45	>> 021091
31	3000	3100	yes		592/592/45	>> 021206
31	4000	3380			592/592/45	>> 021022
31	4000	3380	yes		592/592/45	>> 021152
37	3000	3600		yes	592/592/45	>> 021084
37	4000	3950	yes		592/592/45	>> 021145
37	4000	3950			592/592/45	>> 021008
37	4000	3950		yes	592/592/45	>> 021015
37	3000	3600	yes		592/592/45	>> 021190
37	3000	3600			592/592/45	>> 021077
53	3000	4850		yes	592/592/45	>> 021138
53	3000	4850			592/592/45	>> 021121
53	3000	4850	yes		592/592/45	>> 021237
53	4000	5270		yes	592/592/45	>> 021060
53	4000	5270			592/592/45	>> 021053
53	4000	5270	yes		592/592/45	>> 021183

ARTO 2 LED


GENERAL CARD

ACCESSORIES AVAILABLE


index	Name
998966	Frame steel white structure RAL9016 600x600 SM "well effect"
374845	Frame adapter KG 635x635 WHITE
998973	Frame steel white gloss RAL9016 600x600 SM "well effect"



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)



Frame adapter KG 635x635 WHITE (374845)



Frame steel white gloss RAL9016 600x600 SM "well effect" (998973)

Card creation date: 08 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 253/2023