

# ARTO 2 LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Rated power of the luminaire [W]*:</b>	21.00 - 53.00
<b>Luminous flux [lm]*:</b>	2070 - 5270
<b>Colour temperature [K]:</b>	3000; 4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Material of the body:</b>	powder coated steel
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	OPAL
<b>Mounting version:</b>	recessed mounted in modular ceiling possible; surface mounted
<b>Dimensions (H/W/T/S) [mm]:</b>	592/592/45;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

Surface-mounted modular ceiling luminaire with integrated energy-efficient LED panel made of white powder-coated steel. Opalized polystyrene diffuser ensures uniform light distribution. The central part of the luminaire is a louver, which is a part of a modular ceiling. Thanks to it the luminaire perfectly fits into the interior decor.

## APPLICATION

Multifunctional luminaire designed for surface mounting with the possibility of flush installation in modular ceilings in office, representative, or general utility rooms. It is also used as the main source of light. Luminaire is perfect for new applications as well as for replacing traditional fluorescent fixtures with energy-saving LED solutions.

# ARTO 2 LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details


Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Motion sensor	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
21	3000	2070	yes		592/592/45	<a href="#">&gt;&gt; 021220</a>
21	4000	2250			592/592/45	<a href="#">&gt;&gt; 021046</a>
21	4000	2250	yes		592/592/45	<a href="#">&gt;&gt; 021176</a>
21	3000	2070			592/592/45	<a href="#">&gt;&gt; 021114</a>
26	3000	2600			592/592/45	<a href="#">&gt;&gt; 021107</a>
26	3000	2600	yes		592/592/45	<a href="#">&gt;&gt; 021213</a>
26	4000	2820			592/592/45	<a href="#">&gt;&gt; 021039</a>
26	4000	2820	yes		592/592/45	<a href="#">&gt;&gt; 021169</a>
31	3000	3100			592/592/45	<a href="#">&gt;&gt; 021091</a>
31	3000	3100	yes		592/592/45	<a href="#">&gt;&gt; 021206</a>
31	4000	3380			592/592/45	<a href="#">&gt;&gt; 021022</a>
31	4000	3380	yes		592/592/45	<a href="#">&gt;&gt; 021152</a>
37	3000	3600		yes	592/592/45	<a href="#">&gt;&gt; 021084</a>
37	4000	3950	yes		592/592/45	<a href="#">&gt;&gt; 021145</a>
37	4000	3950			592/592/45	<a href="#">&gt;&gt; 021008</a>
37	4000	3950		yes	592/592/45	<a href="#">&gt;&gt; 021015</a>
37	3000	3600	yes		592/592/45	<a href="#">&gt;&gt; 021190</a>
37	3000	3600			592/592/45	<a href="#">&gt;&gt; 021077</a>
53	3000	4850		yes	592/592/45	<a href="#">&gt;&gt; 021138</a>
53	3000	4850			592/592/45	<a href="#">&gt;&gt; 021121</a>
53	3000	4850	yes		592/592/45	<a href="#">&gt;&gt; 021237</a>
53	4000	5270		yes	592/592/45	<a href="#">&gt;&gt; 021060</a>
53	4000	5270			592/592/45	<a href="#">&gt;&gt; 021053</a>
53	4000	5270	yes		592/592/45	<a href="#">&gt;&gt; 021183</a>

# ARTO 2 LED


GENERAL CARD

## ACCESSORIES AVAILABLE


index	Name
<a href="#">999543</a>	Plasterboard recessing kit 630x630 white (steel version)
<a href="#">998966</a>	Frame steel white structure RAL9016 600x600 SM "well effect"
<a href="#">998973</a>	Frame steel white gloss RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)



Frame steel white gloss RAL9016 600x600 SM "well effect" (998973)

Card creation date: 19 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 253/2023