



TECHNICAL PARAMETERS

Rated power [W] - range:	21-37; 32-55
Luminous flux of the luminaire [lm] - range:	2000 - 3800; 3100 - 5600
Electrical protection class:	I
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
SDCM:	≤ 3
Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	white
Dimensions (H/W/T/S) [mm]:	630/50; 970/80;
Ingress protection:	IP40
Mounting version:	suspended
Warranty [years]:	5

CHARACTERISTICS

Sizzano is a suspended ring-shaped LED luminaire, whose shape and final form are given by an impact-resistant diffuser made by rotomoulding. The design is complemented by an inner collar in black or any RAL color to match the character and color scheme of the room.

APPLICATION

The classic proportions of Sizzano will emphasize the prestigious character of any room without the effect of tactless domination. The length of the pendant can be adjusted to individual needs and the desired final effect. The complete adjustable suspension system with the central box is supplied with the luminaire.

Multi LED versions allow the selection of 4 luminaire power and flux settings, increasing the versatility and functionality of the luminaire and reducing the number of indexes to the minimum.

AVAILABLE VERSIONS



Click index >>, to see details

Sizzano 630/50mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
21-37	2100 - 3600	3000		630/50	>> 468063
21-37	2200 - 3800	4000		630/50	>> 468001
27	2600	3000	yes	630/50	>> 468070
27	2800	4000	yes	630/50	>> 468018
37	3600	3000	yes	630/50	>> 468087
37	3800	4000	yes	630/50	>> 468025

Sizzano 970/80mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
32-55	3000 - 5300	3000		970/80	>> 468094
32-55	3200 - 5600	4000		970/80	>> 468032
40	4000	3000	yes	970/80	>> 468100
40	4200	4000	yes	970/80	>> 468049
55	5300	3000	yes	970/80	>> 468117
55	5600	4000	yes	970/80	>> 468056

Card creation date: 24 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 216/2023