

CRANE COB LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W] - range:	5W COB - 1W SMD
Luminous flux of the luminaire [lm] - range:	620 - 120
Ingress protection:	IP44
Supply voltage [V]:	5
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	90.00
Electrical protection class:	III
Colour rendering index:	>80
Charging time [h:min]:	3.00
Battery life [h:min]:	3
Battery:	Li-Ion 3,7V
Dimensions (H/W/T/S) [mm]:	61/41.5/340;
Warranty [years]:	2

CHARACTERISTICS

- Light source: 5W COB LED + 1W SMD LED (top)
- Luminous flux: 5W COB - 620lm, 1W SMD - 120lm
- Torchlight function
- Strong magnet in base
- Protection class: III
- Retractable rotating hook in handle
- Charger in set: USB 100-240 AC/DC 5V1A + 1,5m micro
- Weight: 0,30 kg
- Li-Ion 3,7V 2200mAh battery
- Lamp covered with rubber
- Charging time: 3H
- Working time: 3H (high option), 5,5H (low option)
- Indicator of battery state
- Elastic joint +/- 120°

APPLICATION

CRANE COB LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W] - range	Luminous flux of the luminaire [lm] - range	Charging time [h:min]	Battery life [h:min]	Battery	Battery capacity [mAh]	Plug type	Dimensions (H/W/T/S) [mm]	Index
5W COB - 1W SMD	620 - 120	3.00	3	Li-Ion 3,7V	2600	UNI-SCHUKO	61/41.5/340	>> 334764

Card creation date: 31 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 282/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl