FUTURE BALL LED LV

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44; IP44/20; IP54/20
Impact resistance:	IK10
Nominal power [W]:	10.00; 20.00
Colour temperature [K]:	4000
Luminous flux [lm]*:	2000
Supply voltage [V]:	24; 24 - 48; 42 - 48
Frequency [Hz]:	50 - 60
Beam angle [°]:	120
Electrical protection class:	III
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	matt
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	244/237/236;
Warranty [years]:	5

CHARACTERISTICS

- Light source: highly efficient LED
- Power: 20W
- Maksymalny strumień świetlny: 2000lm
- Ingress protection class: IP 44/20
- Impact resistance class: IK10
- Even (spherical) light distribution
- Opal bowl made of PC
- Foldable hook
- Rubber cable H07RN-F 3x1,5mm (5m)
- Body: PP
- Protective bags

Version with emergency module:

- Power (48V): 10W
- Luminous flux (48V): 1100lm
- Luminous flux (operating on battery): 380lm
- Emergency mode: 3x60 min
- Battery NiMH 1300 mAh 14,4V
- Charging time: 3h
- The luminaire is equipped with a service power switch that allows switching power to 20 W (2000 lumens).

APPLICATION

FUTURE BALL LED LV

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Supply voltage [V]	Wire type	Cable length [m]	Sockets	Socket type	Plug type	Emergency lighting [h]	Ingress protection	Dimensions (H/W/T/S) [mm]	Index
10	4000	2000	24 - 48	H07RN-F 2x1.5mm	5					IP44/20	244/237/236	>> 619410
20	4000	2000	42 - 48	H07RN-F 2x1.5mm	5				3	IP54/20	244/237/236	>> 619465
20	4000	2000	24 - 48	H07RN-F 2x1.5mm	5					IP44/20	244/237/236	>> 619403
20	4000	2000	24	H07RN-F 2x1.5mm	5	0		CEE		IP44	244/237/236	>> 619328
20	4000	2000	24	H07RN-F 2x1.5mm	5	2	CEE	CEE		IP44	244/237/236	>> 619335
20	4000	2000	42 - 48	H07RN-F 2x1.5mm	5	0		CEE		IP44	244/237/236	>> 619083
20	4000	2000	42 - 48	H07RN-F 2x1.5mm	5	2	CEE	CEE		IP44	244/237/236	>> 619090

FUTURE BALL LED LV

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
016707	MAGNUM STAND - SMALL

Card creation date: 12 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 267/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl