PROFI SLIM LINE LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	28.00 - 126.00
Colour temperature [K]:	4000
Luminous flux [lm]*:	3500 - 15300
Supply voltage [V]:	220 - 240; 24
Luminous efficacy [lm/W]:	121.00; 125.00
Ingress protection:	IP65
Impact resistance:	IK10
Electrical protection class:	III
Color rendering index (Ra) >:	80
Diffuser material:	PC
Diffuser type:	transparent
Dimensions (H/W/T/S) [mm]:	ø20/1720; ø20/1160;
Working temperature [°C]:	from -20 to +35
Warranty [years]:	5

CHARACTERISTICS

PROFI SLIM LINE LED is an innovative luminaire that provides a strong luminous flux, incomparably higher than in traditional fluorescent lamps. The luminaire is characterized by a compact structure (its diameter is only 20mm), thanks to which it will effectively fit into the mounting location. Luminaires are offered in selected sets with a dedicated mounting system (mounting brackets or magnets) and integrated with an easy-to-connect wiring system, connectors, and power supply. Thanks to this, you can easily create a connection configuration, and the installation of the luminaire system is intuitively simple and fast. Standardly available in sets: 2, 4, and 6 pieces.

Optional:

- color temperature: 3000K, 5700K,
- any sets.

APPLICATION

The luminaire is especially recommended for lighting car lifts, workshops, machines, and industrial surfaces.

PROFI SLIM LINE LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

PROFI SLIM LINE LED 220 - 240V

Nominal power [W]	Luminous flux [lm]*	Supply voltage [V]	Version	Accessories included	Plug type	Dimensions (H/W/T/S) [mm]	Index
28	3500	220 - 240	set 2x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	>> 378805
42	5100	220 - 240	set 2x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	>> 378881
56	7000	220 - 240	set 4x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	>> 378898
84	10500	220 - 240	set 6x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	>> 378904
84	10200	220 - 240	set 4x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	>> 378812
126	15300	220 - 240	set 6x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	>> 378829

PROFI SLIM LINE LED 24V

Nominal power [W]	Luminous flux [lm]*	Supply voltage [V]	Version	Accessories included	Plug type	Dimensions (H/W/T/S) [mm]	Index
28	3500	24	2x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	>> 378928
42	5100	24	2x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	>> 378874
56	7000	24	4x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	>> 378935
84	10500	24	6x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	>> 378942
84	10200	24	4x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	>> 378799
126	15300	24	6x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	>> 378911

PROFI SLIM LINE LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
	PROFI SLIM LINE LED MAGNETIC HOLDER



PROFI SLIM LINE LED MAGNETIC HOLDER (378751)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 11/2018; 286/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl