

PROFI SLIM LINE LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	28.00 - 126.00
Colour temperature [K]:	4000
Luminous flux [lm]*:	3500 - 15300
Supply voltage [V]:	220 - 240; 24
Luminous efficacy [lm/W]:	121.00; 125.00
Ingress protection:	IP65
Impact resistance:	IK10
Electrical protection class:	III
Colour rendering index:	>80
Diffuser material:	PC
Diffuser type:	transparent
Dimensions (H/W/T/S) [mm]:	ø20/1720; ø20/1160;
Working temperature [°C]:	from -20 to +35
Warranty [years]:	5

CHARACTERISTICS

PROFI SLIM LINE LED is an innovative luminaire that provides a strong luminous flux, incomparably higher than in traditional fluorescent lamps. The luminaire is characterized by a compact structure (its diameter is only 20mm), thanks to which it will effectively fit into the mounting location. Luminaires are offered in selected sets with a dedicated mounting system (mounting brackets or magnets) and integrated with an easy-to-connect wiring system, connectors, and power supply. Thanks to this, you can easily create a connection configuration, and the installation of the luminaire system is intuitively simple and fast. Standardly available in sets: 2, 4, and 6 pieces.

Optional:

- color temperature: 3000K, 5700K,
- any sets.

APPLICATION

The luminaire is especially recommended for lighting car lifts, workshops, machines, and industrial surfaces.

PROFI SLIM LINE LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

PROFI SLIM LINE LED 220 - 240V

Nominal power [W]	Luminous flux [lm]*	Supply voltage [V]	Version	Accessories included	Plug type	Dimensions (H/W/T/S) [mm]	Index
28	3500	220 - 240	set 2x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	>> 378805
42	5100	220 - 240	set 2x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	>> 378881
56	7000	220 - 240	set 4x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	>> 378898
84	10500	220 - 240	set 6x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	>> 378904
84	10200	220 - 240	set 4x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	>> 378812
126	15300	220 - 240	set 6x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	>> 378829

PROFI SLIM LINE LED 24V

Nominal power [W]	Luminous flux [lm]*	Supply voltage [V]	Version	Accessories included	Plug type	Dimensions (H/W/T/S) [mm]	Index
28	3500	24	2x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	>> 378928
42	5100	24	2x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	>> 378874
56	7000	24	4x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	>> 378935
84	10500	24	6x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	>> 378942
84	10200	24	4x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	>> 378799
126	15300	24	6x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	>> 378911

PROFI SLIM LINE LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
	PROFI SLIM LINE LED MAGNETIC HOLDER



PROFI SLIM LINE LED MAGNETIC HOLDER (378751)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 11/2018; 286/2023