

# PROFI SLIM LINE LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Nominal power [W]:</b>	28.00 - 126.00
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	3500 - 15300
<b>Supply voltage [V]:</b>	220 - 240; 24
<b>Luminous efficacy [lm/W]:</b>	121.00; 125.00
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK10
<b>Electrical protection class:</b>	III
<b>Colour rendering index:</b>	>80
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	transparent
<b>Dimensions (H/W/T/S) [mm]:</b>	ø20/1720; ø20/1160;
<b>Working temperature [°C]:</b>	from -20 to +35
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

PROFI SLIM LINE LED is an innovative luminaire that provides a strong luminous flux, incomparably higher than in traditional fluorescent lamps. The luminaire is characterized by a compact structure (its diameter is only 20mm), thanks to which it will effectively fit into the mounting location. Luminaires are offered in selected sets with a dedicated mounting system (mounting brackets or magnets) and integrated with an easy-to-connect wiring system, connectors, and power supply. Thanks to this, you can easily create a connection configuration, and the installation of the luminaire system is intuitively simple and fast. Standardly available in sets: 2, 4, and 6 pieces.

Optional:

- color temperature: 3000K, 5700K,
- any sets.

## APPLICATION

The luminaire is especially recommended for lighting car lifts, workshops, machines, and industrial surfaces.

# PROFI SLIM LINE LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### PROFI SLIM LINE LED 220 - 240V

Nominal power [W]	Luminous flux [lm]*	Supply voltage [V]	Version	Accessories included	Plug type	Dimensions (H/W/T/S) [mm]	Index
28	3500	220 - 240	set 2x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	<a href="#">&gt;&gt; 378805</a>
42	5100	220 - 240	set 2x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	<a href="#">&gt;&gt; 378881</a>
56	7000	220 - 240	set 4x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	<a href="#">&gt;&gt; 378898</a>
84	10500	220 - 240	set 6x14W with power supply	mounting brackets	UNI-SCHUKO	ø20/1160	<a href="#">&gt;&gt; 378904</a>
84	10200	220 - 240	set 4x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	<a href="#">&gt;&gt; 378812</a>
126	15300	220 - 240	set 6x21W with power supply	mounting brackets	UNI-SCHUKO	ø20/1720	<a href="#">&gt;&gt; 378829</a>

### PROFI SLIM LINE LED 24V

Nominal power [W]	Luminous flux [lm]*	Supply voltage [V]	Version	Accessories included	Plug type	Dimensions (H/W/T/S) [mm]	Index
28	3500	24	2x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	<a href="#">&gt;&gt; 378928</a>
42	5100	24	2x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	<a href="#">&gt;&gt; 378874</a>
56	7000	24	4x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	<a href="#">&gt;&gt; 378935</a>
84	10500	24	6x14W KIT with CEE plug	mounting brackets	CEE	ø20/1160	<a href="#">&gt;&gt; 378942</a>
84	10200	24	4x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	<a href="#">&gt;&gt; 378799</a>
126	15300	24	6x21W KIT with CEE plug	mounting brackets	CEE	ø20/1720	<a href="#">&gt;&gt; 378911</a>

# PROFI SLIM LINE LED

GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
	PROFI SLIM LINE LED MAGNETIC HOLDER



PROFI SLIM LINE LED MAGNETIC  
HOLDER (378751)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 11/2018; 286/2023