

CYCLOP LED

GENERAL CARD



TECHNICAL PARAMETERS

Impact resistance:	IK09
Luminous flux [lm]*:	300
Supply voltage [V]:	3.7
Electrical protection class:	III
Colour rendering index:	>80
Diffuser type:	transparent
Dimensions (H/W/T/S) [mm]:	78/475/42;
Warranty [years]:	2

CHARACTERISTICS

- Light source: COB LED
- ACCU mode working types:
 - 300lm - 2,5h working time
 - 150lm - 4h working time
- Elastic top joint 60°
- Protection class: III
- The set includes a 1.5 m microUSB cable
- Dimensions: 260x75x75mm
- Weight: 110 g
- Li-Ion 3,7V 1500mAh battery
- Charging time: 3H
- Indicator of battery state
- Turning on the lamp by hand movement thanks to included sensor
- Non-skid belt
- Modern design and top quality

APPLICATION

CYCLOP LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Luminous flux [lm]*	Supply voltage [V]	Electrical protection class	Impact resistance	Dimensions (H/W/T/S) [mm]	Index
300	3.7	III	IK09	78/475/42	>> 334689

Card creation date: 31 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 287/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl