

# CYCLOP LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Impact resistance:</b>	IK07
<b>Luminous flux [lm]*:</b>	300
<b>Supply voltage [V]:</b>	3.7
<b>Electrical protection class:</b>	III
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Diffuser type:</b>	transparent
<b>Dimensions (H/W/T/S) [mm]:</b>	78/475/42;
<b>Warranty [years]:</b>	2

## CHARACTERISTICS

- Light source: COB LED
- ACCU mode working types:
  - 300lm - 2,5h working time
  - 100lm - 4h working time
- Elastic top joint 60°
- Protection class: III
- The set includes USB-C cable
- Dimensions: 260x75x75mm
- Weight: 110 g
- Li-Ion 3,7V 1500mAh battery
- Charging time: 3H
- Indicator of battery state
- Turning on the lamp by hand movement thanks to included sensor
- Non-skid belt
- Modern design and top quality

## APPLICATION

# CYCLOP LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Luminous flux [lm]*	Supply voltage [V]	Electrical protection class	Impact resistance	Dimensions (H/W/T/S) [mm]	Index
300	3.7	III	IK07	78/475/42	<a href="#">&gt;&gt; 334689</a>

Card creation date: 13 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 287/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl