

# TAURUS LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44; IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	40.00
<b>Colour temperature [K]:</b>	4000
<b>Supply voltage [V]:</b>	220 - 240; 24; 42
<b>Electrical protection class:</b>	I; II; III
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	MAT
<b>Dimensions (H/W/T/S) [mm]:</b>	373/312/125;

## CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm<sup>2</sup> (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm<sup>2</sup> (5m)

## APPLICATION

# TAURUS LED

## GENERAL CARD

### AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Ingress protection	Plug type	Socket type	Sockets	Switch	Electrical protection class	Supply voltage [V]	Dimensions (H/W/T/S) [mm]	Index
40	4000	IP44	CEE				III	24	373/312/125	<a href="#">&gt;&gt; 291937</a>
40	4000	IP44	CEE		0	yes	III	24	373/312/125	<a href="#">&gt;&gt; 291951</a>
40	4000	IP44	CEE	CEE (2-PIN)	2		III	24	373/312/125	<a href="#">&gt;&gt; 291944</a>
40	4000	IP44	CEE	CEE (2-PIN)	2	yes	III	24	373/312/125	<a href="#">&gt;&gt; 291968</a>
40	4000	IP44	CEE		0		III	42	373/312/125	<a href="#">&gt;&gt; 291890</a>
40	4000	IP44	CEE		0	yes	III	42	373/312/125	<a href="#">&gt;&gt; 291913</a>
40	4000	IP44	CEE	CEE (2-PIN)	2		III	42	373/312/125	<a href="#">&gt;&gt; 291906</a>
40	4000	IP44	CEE	CEE (2-PIN)	2	yes	III	42	373/312/125	<a href="#">&gt;&gt; 291920</a>
40	4000	IP44	DK		0		I	220 - 240	373/312/125	<a href="#">&gt;&gt; 291807</a>
40	4000	IP44	DK		0	yes	II	220 - 240	373/312/125	<a href="#">&gt;&gt; 291975</a>
40	4000	IP54	UNI-SCHUKO		0		II	220 - 240	373/312/125	<a href="#">&gt;&gt; 291791</a>
40	4000	IP54	UNI-SCHUKO		0	yes	II	220 - 240	373/312/125	<a href="#">&gt;&gt; 291845</a>
40	4000	IP44	DK	DK	2		I	220 - 240	373/312/125	<a href="#">&gt;&gt; 291821</a>
40	4000	IP44	DK	DK	2	yes	I	220 - 240	373/312/125	<a href="#">&gt;&gt; 291876</a>
40	4000	IP54	UNI-SCHUKO	PL-FR	2		I	220 - 240	373/312/125	<a href="#">&gt;&gt; 291814</a>
40	4000	IP54	UNI-SCHUKO	PL-FR	2	yes	I	220 - 240	373/312/125	<a href="#">&gt;&gt; 291869</a>
40	4000	IP54	UNI-SCHUKO	UNI-SCHUKO	2		I	220 - 240	373/312/125	<a href="#">&gt;&gt; 291838</a>
40	4000	IP54	UNI-SCHUKO	UNI-SCHUKO	2	yes	I	220 - 240	373/312/125	<a href="#">&gt;&gt; 291883</a>

Card creation date: 06 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 53/2016



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl