

TAURUS LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44; IP54
Impact resistance:	IK10
Nominal power [W]:	40.00
Colour temperature [K]:	4000
Supply voltage [V]:	220 - 240; 24; 42
Electrical protection class:	I; II; III
Material of the body:	PP
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	MAT
Dimensions (H/W/T/S) [mm]:	373/312/125;

CHARACTERISTICS

- Light source: highly efficient SMD LED
- Power: 40W
- Ingress protection class: IP54, IP44
- Impact-resistant casing and multi-positional arm
- Anti-glare diffuser made of frozen polycarbonate
- Wide lighting angle (120°)
- Rubber cable H07RN-F 2x1,0mm² (5m)
- Weight: 3,2kg - 3,4kg

Optionally available:

- Two sockets at the backside of the fitting
- Rubber cable H07RN-F 3x1,5mm² (5m)

APPLICATION

TAURUS LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Colour temperature [K]	Ingress protection	Plug type	Socket type	Sockets	Switch	Electrical protection class	Supply voltage [V]	Dimensions (H/W/T/S) [mm]	Index
40	4000	IP44	CEE				III	24	373/312/125	>> 291937
40	4000	IP44	CEE		0	yes	III	24	373/312/125	>> 291951
40	4000	IP44	CEE	CEE (2-PIN)	2		III	24	373/312/125	>> 291944
40	4000	IP44	CEE	CEE (2-PIN)	2	yes	III	24	373/312/125	>> 291968
40	4000	IP44	CEE		0		III	42	373/312/125	>> 291890
40	4000	IP44	CEE		0	yes	III	42	373/312/125	>> 291913
40	4000	IP44	CEE	CEE (2-PIN)	2		III	42	373/312/125	>> 291906
40	4000	IP44	CEE	CEE (2-PIN)	2	yes	III	42	373/312/125	>> 291920
40	4000	IP44	DK		0		I	220 - 240	373/312/125	>> 291807
40	4000	IP44	DK		0	yes	II	220 - 240	373/312/125	>> 291975
40	4000	IP54	UNI-SCHUKO		0		II	220 - 240	373/312/125	>> 291791
40	4000	IP54	UNI-SCHUKO		0	yes	II	220 - 240	373/312/125	>> 291845
40	4000	IP44	DK	DK	2		I	220 - 240	373/312/125	>> 291821
40	4000	IP44	DK	DK	2	yes	I	220 - 240	373/312/125	>> 291876
40	4000	IP54	UNI-SCHUKO	PL-FR	2		I	220 - 240	373/312/125	>> 291814
40	4000	IP54	UNI-SCHUKO	PL-FR	2	yes	I	220 - 240	373/312/125	>> 291869
40	4000	IP54	UNI-SCHUKO	UNI-SCHUKO	2		I	220 - 240	373/312/125	>> 291838
40	4000	IP54	UNI-SCHUKO	UNI-SCHUKO	2	yes	I	220 - 240	373/312/125	>> 291883

Card creation date: 06 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 53/2016



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl