

PROFI SMD LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	4.00
Luminous flux [lm]*:	450
Colour temperature [K]:	4000
Ingress protection:	IP54
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Colour rendering index:	>80
Material of the body:	gum
Dimensions (H/W/T/S) [mm]:	60/415;
Warranty [years]:	2

CHARACTERISTICS

- Power: 4W
- Luminous flux: 450lm
- 65% less power consumption (compared to Profi 11W)
- Light source: SMD LED
- Polycarbonate impact-resistant prismatic diffuser
- Handle and cap made of rubber
- High ingress protection class IP54
- Rotating hook
- Weight: 0,7 kg
- Rubber cable H05RN-F 2x1 mm² (5m)
- Spare parts available

APPLICATION

PROFI SMD LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	450	UNI-SCHUKO	60/415	>> 260834

PROFI SMD LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
111631	
886584	Magnetic rubber mount



Magnetic rubber mount (886584)

Card creation date: 28 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 258/2023; 259/2023; 42/2012