PROFI SMD LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	4.00
Luminous flux [lm]*:	450
Colour temperature [K]:	4000
Ingress protection:	IP54
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Color rendering index (Ra) >:	80
Material of the body:	gum
Dimensions (H/W/T/S) [mm]:	60/415;
Warranty [years]:	2

CHARACTERISTICS

- Power: 4W
- Luminous flux: 450lm
- 65% less power consumption (compared to Profi 11W)
- Light source: SMD LED
- Polycarbonate impact-resistant prismatic diffuser
- Handle and cap made of rubber
- High ingress protection class IP54
- Rotating hook
- Weight: 0,7 kg
- Rubber cable H05RN-F 2x1 mm2 (5m)
- Spare parts available

APPLICATION

PROFI SMD LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	450	UNI-SCHUKO	60/415	>> 260834

PROFI SMD LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
111631	
886584	Magnetic rubber mount



Magnetic rubber mount (886584)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 258/2023; 259/2023; 42/2012

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl