

EFFECT LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	4.00
Luminous flux [lm]*:	400
Colour temperature [K]:	4000
Ingress protection:	IP20
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Colour rendering index:	>80
Material of the body:	PP
Dimensions (H/W/T/S) [mm]:	390/50;
Warranty [years]:	2

CHARACTERISTICS

- Power: 4W
- Luminous flux: 400lm
- Light source: SMD LED
- Casing made of polypropylene
- Diffuser made of impact-resistant polycarbonate
- Rotating hook
- Weight: 0,5 kg
- Cable H05VV-F 2x0,75 mm² (5m)

APPLICATION

EFFECT LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	400	Universal	390/50	>> 270109

Card creation date: 03 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 277/2023; 90/2013



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl