

EFFECT LED

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|-----------|
| Nominal power [W]: | 4.00 |
| Luminous flux [lm]*: | 400 |
| Colour temperature [K]: | 4000 |
| Ingress protection: | IP20 |
| Supply voltage [V]: | 220 - 240 |
| Frequency [Hz]: | 50 - 60 |
| Electrical protection class: | II |
| Colour rendering index: | >80 |
| Material of the body: | PP |
| Dimensions (H/W/T/S) [mm]: | 390/50; |
| Warranty [years]: | 2 |

CHARACTERISTICS

- Power: 4W
- Luminous flux: 400lm
- Light source: SMD LED
- Casing made of polypropylene
- Diffuser made of impact-resistant polycarbonate
- Rotating hook
- Weight: 0,5 kg
- Cable H05VV-F 2x0,75 mm² (5m)

APPLICATION

EFFECT LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

| Nominal power [W] | Luminous flux [lm]* | Plug type | Dimensions (H/W/T/S) [mm] | Index |
|-------------------|---------------------|-----------|---------------------------|---------------------------------|
| 4 | 400 | Universal | 390/50 | >> 270109 |

Card creation date: 03 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 277/2023; 90/2013



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl