

# BARIS 52 LED P SM

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44/IP20
<b>Impact resistance:</b>	IK03
<b>Rated power of the luminaire [W]*:</b>	9.00 - 45.00
<b>Luminous flux [lm]*:</b>	1100 - 5775
<b>Colour temperature [K]:</b>	3000; 4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black; grey; white
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL; PRM
<b>Mounting version:</b>	recessed
<b>Dimensions (H/W/T/S) [mm]:</b>	593/69/60; 1193/69/60; 1793/69/60;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

A recessed luminaire with classic proportions and modern design, intended for installation in modular ceilings. The luminaire is available in three lengths: 595mm, 1195mm, 1795mm. The housing of the luminaire is made of an anodized aluminum profile in gray or an aluminum profile painted in white or black (other colors available on request). The optical system is in the form of a dedicated, flexible opal diffuser that evenly illuminates the luminaire, with a PRM prismatic diffuser. The luminaire is equipped with a complete mounting system enabling quick and easy installation in modular ceilings.

## APPLICATION

The luminaire is dedicated to indoor use. It is applied as the source of the main light and is conducive to office work requiring concentration of eyesight. Classic design, energy-saving LED modules, and the possibility of cooperation with external lighting control systems in the DALI standard dedicate the lamp to be used in modern office buildings of the A+ class, with particular consideration of representative rooms, conference halls, passageways.

# BARIS 52 LED P SM

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

BARIS 52 LED P SM 1193/69/60mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
18	3000	2225	OPAL	grey	yes	1193/69/60	<a href="#">&gt;&gt; 929083</a>
18	3000	2225	OPAL	white	yes	1193/69/60	<a href="#">&gt;&gt; 929120</a>
18	3000	2225	OPAL	black	yes	1193/69/60	<a href="#">&gt;&gt; 929168</a>
18	3000	2175	PRM	grey	yes	1193/69/60	<a href="#">&gt;&gt; 929090</a>
18	3000	2175	PRM	white	yes	1193/69/60	<a href="#">&gt;&gt; 929137</a>
18	3000	2175	PRM	black	yes	1193/69/60	<a href="#">&gt;&gt; 929175</a>
18	3000	2225	OPAL	grey		1193/69/60	<a href="#">&gt;&gt; 928963</a>
18	3000	2225	OPAL	white		1193/69/60	<a href="#">&gt;&gt; 929007</a>
18	3000	2225	OPAL	black		1193/69/60	<a href="#">&gt;&gt; 929045</a>
18	3000	2175	PRM	grey		1193/69/60	<a href="#">&gt;&gt; 928970</a>
18	3000	2175	PRM	white		1193/69/60	<a href="#">&gt;&gt; 929014</a>
18	3000	2175	PRM	black		1193/69/60	<a href="#">&gt;&gt; 929052</a>
18	4000	2325	OPAL	grey	yes	1193/69/60	<a href="#">&gt;&gt; 928369</a>
18	4000	2325	OPAL	white	yes	1193/69/60	<a href="#">&gt;&gt; 928406</a>
18	4000	2325	OPAL	black	yes	1193/69/60	<a href="#">&gt;&gt; 928444</a>
18	4000	2275	PRM	grey	yes	1193/69/60	<a href="#">&gt;&gt; 928376</a>
18	4000	2275	PRM	white	yes	1193/69/60	<a href="#">&gt;&gt; 928413</a>
18	4000	2275	PRM	black	yes	1193/69/60	<a href="#">&gt;&gt; 928451</a>
18	4000	2325	OPAL	grey		1193/69/60	<a href="#">&gt;&gt; 928246</a>
18	4000	2325	OPAL	white		1193/69/60	<a href="#">&gt;&gt; 928284</a>
18	4000	2325	OPAL	black		1193/69/60	<a href="#">&gt;&gt; 928321</a>
18	4000	2275	PRM	grey		1193/69/60	<a href="#">&gt;&gt; 928253</a>
18	4000	2275	PRM	white		1193/69/60	<a href="#">&gt;&gt; 928291</a>
18	4000	2275	PRM	black		1193/69/60	<a href="#">&gt;&gt; 928338</a>
30	3000	3675	OPAL	grey	yes	1193/69/60	<a href="#">&gt;&gt; 929106</a>
30	3000	3675	OPAL	white	yes	1193/69/60	<a href="#">&gt;&gt; 929144</a>
30	3000	3675	OPAL	black	yes	1193/69/60	<a href="#">&gt;&gt; 929182</a>
30	3000	3625	PRM	grey	yes	1193/69/60	<a href="#">&gt;&gt; 929113</a>
30	3000	3625	PRM	white	yes	1193/69/60	<a href="#">&gt;&gt; 929151</a>
30	3000	3625	PRM	black	yes	1193/69/60	<a href="#">&gt;&gt; 929199</a>
30	3000	3675	OPAL	grey		1193/69/60	<a href="#">&gt;&gt; 928987</a>
30	3000	3675	OPAL	white		1193/69/60	<a href="#">&gt;&gt; 929021</a>
30	3000	3675	OPAL	black		1193/69/60	<a href="#">&gt;&gt; 929069</a>

# BARIS 52 LED P SM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
30	3000	3625	PRM	grey		1193/69/60	<a href="#">&gt;&gt; 928994</a>
30	3000	3625	PRM	white		1193/69/60	<a href="#">&gt;&gt; 929038</a>
30	3000	3625	PRM	black		1193/69/60	<a href="#">&gt;&gt; 929076</a>
30	4000	3850	OPAL	grey	yes	1193/69/60	<a href="#">&gt;&gt; 928383</a>
30	4000	3850	OPAL	white	yes	1193/69/60	<a href="#">&gt;&gt; 928420</a>
30	4000	3850	OPAL	black	yes	1193/69/60	<a href="#">&gt;&gt; 928468</a>
30	4000	3775	PRM	grey	yes	1193/69/60	<a href="#">&gt;&gt; 928390</a>
30	4000	3775	PRM	white	yes	1193/69/60	<a href="#">&gt;&gt; 928437</a>
30	4000	3775	PRM	black	yes	1193/69/60	<a href="#">&gt;&gt; 928475</a>
30	4000	3850	OPAL	grey		1193/69/60	<a href="#">&gt;&gt; 928260</a>
30	4000	3850	OPAL	white		1193/69/60	<a href="#">&gt;&gt; 928307</a>
30	4000	3850	OPAL	black		1193/69/60	<a href="#">&gt;&gt; 928345</a>
30	4000	3775	PRM	grey		1193/69/60	<a href="#">&gt;&gt; 928277</a>
30	4000	3775	PRM	white		1193/69/60	<a href="#">&gt;&gt; 928314</a>
30	4000	3775	PRM	black		1193/69/60	<a href="#">&gt;&gt; 928352</a>

## BARIS 52 LED P SM 1793/69/60mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
26	3000	3200	OPAL	grey	yes	1793/69/60	<a href="#">&gt;&gt; 929328</a>
26	3000	3200	OPAL	white	yes	1793/69/60	<a href="#">&gt;&gt; 929366</a>
26	3000	3200	OPAL	black	yes	1793/69/60	<a href="#">&gt;&gt; 929403</a>
26	3000	3125	PRM	grey	yes	1793/69/60	<a href="#">&gt;&gt; 929335</a>
26	3000	3125	PRM	white	yes	1793/69/60	<a href="#">&gt;&gt; 929373</a>
26	3000	3125	PRM	black	yes	1793/69/60	<a href="#">&gt;&gt; 929410</a>
26	3000	3200	OPAL	grey		1793/69/60	<a href="#">&gt;&gt; 929205</a>
26	3000	3200	OPAL	white		1793/69/60	<a href="#">&gt;&gt; 929243</a>
26	3000	3200	OPAL	black		1793/69/60	<a href="#">&gt;&gt; 929281</a>
26	3000	3125	PRM	grey		1793/69/60	<a href="#">&gt;&gt; 929212</a>
26	3000	3125	PRM	white		1793/69/60	<a href="#">&gt;&gt; 929250</a>
26	3000	3125	PRM	black		1793/69/60	<a href="#">&gt;&gt; 929298</a>
26	4000	3350	OPAL	grey	yes	1793/69/60	<a href="#">&gt;&gt; 928604</a>
26	4000	3350	OPAL	white	yes	1793/69/60	<a href="#">&gt;&gt; 928642</a>
26	4000	3350	OPAL	black	yes	1793/69/60	<a href="#">&gt;&gt; 928680</a>
26	4000	3275	PRM	grey	yes	1793/69/60	<a href="#">&gt;&gt; 928611</a>
26	4000	3275	PRM	white	yes	1793/69/60	<a href="#">&gt;&gt; 928659</a>
26	4000	3275	PRM	black	yes	1793/69/60	<a href="#">&gt;&gt; 928697</a>
26	4000	3350	OPAL	grey		1793/69/60	<a href="#">&gt;&gt; 928482</a>
26	4000	3350	OPAL	white		1793/69/60	<a href="#">&gt;&gt; 928529</a>

# BARIS 52 LED P SM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
26	4000	3350	OPAL	black		1793/69/60	<a href="#">&gt;&gt; 928567</a>
26	4000	3275	PRM	grey		1793/69/60	<a href="#">&gt;&gt; 928499</a>
26	4000	3275	PRM	white		1793/69/60	<a href="#">&gt;&gt; 928536</a>
26	4000	3275	PRM	black		1793/69/60	<a href="#">&gt;&gt; 928574</a>
45	3000	5525	OPAL	grey	yes	1793/69/60	<a href="#">&gt;&gt; 929342</a>
45	3000	5525	OPAL	white	yes	1793/69/60	<a href="#">&gt;&gt; 929380</a>
45	3000	5525	OPAL	black	yes	1793/69/60	<a href="#">&gt;&gt; 929427</a>
45	3000	5425	PRM	grey	yes	1793/69/60	<a href="#">&gt;&gt; 929359</a>
45	3000	5425	PRM	white	yes	1793/69/60	<a href="#">&gt;&gt; 929397</a>
45	3000	5425	PRM	black	yes	1793/69/60	<a href="#">&gt;&gt; 929434</a>
45	3000	5525	OPAL	grey		1793/69/60	<a href="#">&gt;&gt; 929229</a>
45	3000	5525	OPAL	white		1793/69/60	<a href="#">&gt;&gt; 929267</a>
45	3000	5525	OPAL	black		1793/69/60	<a href="#">&gt;&gt; 929304</a>
45	3000	5425	PRM	grey		1793/69/60	<a href="#">&gt;&gt; 929236</a>
45	3000	5425	PRM	white		1793/69/60	<a href="#">&gt;&gt; 929274</a>
45	3000	5425	PRM	black		1793/69/60	<a href="#">&gt;&gt; 929311</a>
45	4000	5775	OPAL	grey	yes	1793/69/60	<a href="#">&gt;&gt; 928628</a>
45	4000	5775	OPAL	white	yes	1793/69/60	<a href="#">&gt;&gt; 928666</a>
45	4000	5775	OPAL	black	yes	1793/69/60	<a href="#">&gt;&gt; 928703</a>
45	4000	5675	PRM	grey	yes	1793/69/60	<a href="#">&gt;&gt; 928635</a>
45	4000	5675	PRM	white	yes	1793/69/60	<a href="#">&gt;&gt; 928673</a>
45	4000	5675	PRM	black	yes	1793/69/60	<a href="#">&gt;&gt; 928710</a>
45	4000	5775	OPAL	grey		1793/69/60	<a href="#">&gt;&gt; 928505</a>
45	4000	5775	OPAL	white		1793/69/60	<a href="#">&gt;&gt; 928543</a>
45	4000	5775	OPAL	black		1793/69/60	<a href="#">&gt;&gt; 928581</a>
45	4000	5675	PRM	grey		1793/69/60	<a href="#">&gt;&gt; 928512</a>
45	4000	5675	PRM	white		1793/69/60	<a href="#">&gt;&gt; 928550</a>
45	4000	5675	PRM	black		1793/69/60	<a href="#">&gt;&gt; 928598</a>

## BARIS 52 LED P SM 593/69/60mm

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
9	3000	1125	OPAL	grey	yes	593/69/60	<a href="#">&gt;&gt; 928840</a>
9	3000	1125	OPAL	white	yes	593/69/60	<a href="#">&gt;&gt; 928888</a>
9	3000	1125	OPAL	black	yes	593/69/60	<a href="#">&gt;&gt; 928925</a>
9	3000	1100	PRM	grey	yes	593/69/60	<a href="#">&gt;&gt; 928857</a>
9	3000	1100	PRM	white	yes	593/69/60	<a href="#">&gt;&gt; 928895</a>
9	3000	1100	PRM	black	yes	593/69/60	<a href="#">&gt;&gt; 928932</a>
9	3000	1125	OPAL	grey		593/69/60	<a href="#">&gt;&gt; 928727</a>

# BARIS 52 LED P SM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
9	3000	1125	OPAL	white		593/69/60	<a href="#">&gt;&gt; 928765</a>
9	3000	1125	OPAL	black		593/69/60	<a href="#">&gt;&gt; 928802</a>
9	3000	1100	PRM	grey		593/69/60	<a href="#">&gt;&gt; 928734</a>
9	3000	1100	PRM	white		593/69/60	<a href="#">&gt;&gt; 928772</a>
9	3000	1100	PRM	black		593/69/60	<a href="#">&gt;&gt; 928819</a>
9	4000	1175	OPAL	grey	yes	593/69/60	<a href="#">&gt;&gt; 928123</a>
9	4000	1175	OPAL	white	yes	593/69/60	<a href="#">&gt;&gt; 928161</a>
9	4000	1175	OPAL	black	yes	593/69/60	<a href="#">&gt;&gt; 928208</a>
9	4000	1150	PRM	grey	yes	593/69/60	<a href="#">&gt;&gt; 928130</a>
9	4000	1150	PRM	white	yes	593/69/60	<a href="#">&gt;&gt; 928178</a>
9	4000	1150	PRM	black	yes	593/69/60	<a href="#">&gt;&gt; 928215</a>
9	4000	1175	OPAL	grey		593/69/60	<a href="#">&gt;&gt; 928000</a>
9	4000	1175	OPAL	white		593/69/60	<a href="#">&gt;&gt; 928048</a>
9	4000	1175	OPAL	black		593/69/60	<a href="#">&gt;&gt; 928086</a>
9	4000	1150	PRM	grey		593/69/60	<a href="#">&gt;&gt; 928017</a>
9	4000	1150	PRM	white		593/69/60	<a href="#">&gt;&gt; 928055</a>
9	4000	1150	PRM	black		593/69/60	<a href="#">&gt;&gt; 928093</a>
16	3000	1975	OPAL	grey	yes	593/69/60	<a href="#">&gt;&gt; 928864</a>
16	3000	1975	OPAL	white	yes	593/69/60	<a href="#">&gt;&gt; 928901</a>
16	3000	1975	OPAL	black	yes	593/69/60	<a href="#">&gt;&gt; 928949</a>
16	3000	1925	PRM	grey	yes	593/69/60	<a href="#">&gt;&gt; 928871</a>
16	3000	1925	PRM	white	yes	593/69/60	<a href="#">&gt;&gt; 928918</a>
16	3000	1925	PRM	black	yes	593/69/60	<a href="#">&gt;&gt; 928956</a>
16	3000	1975	OPAL	grey		593/69/60	<a href="#">&gt;&gt; 928741</a>
16	3000	1975	OPAL	white		593/69/60	<a href="#">&gt;&gt; 928789</a>
16	3000	1975	OPAL	black		593/69/60	<a href="#">&gt;&gt; 928826</a>
16	3000	1925	PRM	grey		593/69/60	<a href="#">&gt;&gt; 928758</a>
16	3000	1925	PRM	white		593/69/60	<a href="#">&gt;&gt; 928796</a>
16	3000	1925	PRM	black		593/69/60	<a href="#">&gt;&gt; 928833</a>
16	4000	2050	OPAL	grey	yes	593/69/60	<a href="#">&gt;&gt; 928147</a>
16	4000	2050	OPAL	white	yes	593/69/60	<a href="#">&gt;&gt; 928185</a>
16	4000	2050	OPAL	black	yes	593/69/60	<a href="#">&gt;&gt; 928222</a>
16	4000	2025	PRM	grey	yes	593/69/60	<a href="#">&gt;&gt; 928154</a>
16	4000	2025	PRM	white	yes	593/69/60	<a href="#">&gt;&gt; 928192</a>
16	4000	2025	PRM	black	yes	593/69/60	<a href="#">&gt;&gt; 928239</a>
16	4000	2050	OPAL	grey		593/69/60	<a href="#">&gt;&gt; 928024</a>
16	4000	2050	OPAL	white		593/69/60	<a href="#">&gt;&gt; 928062</a>
16	4000	2050	OPAL	black		593/69/60	<a href="#">&gt;&gt; 928109</a>

# BARIS 52 LED P SM

## GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
16	4000	2025	PRM	grey		593/69/60	<a href="#">&gt;&gt; 928031</a>
16	4000	2025	PRM	white		593/69/60	<a href="#">&gt;&gt; 928079</a>
16	4000	2025	PRM	black		593/69/60	<a href="#">&gt;&gt; 928116</a>

Card creation date: 02 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 245/2023; 38/2026



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

