INDUSTRY SLIM LED

GENERAL CARD



INDUSTRY SLIM LED

GENERAL CARD

TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK09
Nominal power [W]:	22.00 - 115.00
Luminous flux [lm]*:	2000 - 17500
Colour temperature [K]:	3000; 4000; 5000
Color rendering index (Ra) >:	80; 90
SDCM:	3
Material of the body:	aluminium
Colour of the body:	black; grey; silver
Diffuser material:	PC
Diffuser type:	OPAL; matrix led; transparent
Optics material:	PC
Optics:	105D; 120D; 46/117D; 46x117D; lens
Beam angle [°]:	30 - butterfly
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	621/50/75; 651/50/75; 1177/50/75 ; 590/50/75;
Warranty [years]:	5


CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

DETAILS



INDUSTRY SLIM LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

INDUSTRY SLIM LED 105°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
14	4000	2100	105	VW		transparent			silver	1177/50/75	>> 838125
14	4000	2100	105	VW	yes	transparent			silver	1177/50/75	>> 973802
14	4000	2100	105	VW		transparent		R2	silver	1177/50/75	>> 838125/2
14	4000	2100	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973802/2
18	4000	2700	105	VW		transparent			silver	1177/50/75	>> 838132
18	4000	2700	105	VW	yes	transparent			silver	1177/50/75	>> 973819
18	4000	2700	105	VW		transparent		R2	silver	1177/50/75	>> 838132/2
18	4000	2700	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973819/2
22	4000	3500	105	VW		matrix led			grey	590/50/75	>> 827570
22	4000	3500	105	VW	yes	matrix led			grey	590/50/75	>> 827587
22	4000	3500	105	VW		matrix led		R2	grey	590/50/75	>> 827570/2
22	4000	3500	105	VW	yes	matrix led		R2	grey	590/50/75	>> 827587/2
23	4000	2950	105	symmetric		OPAL			grey	621/50/75	>> 933004
23	4000	2950	105	symmetric	yes	OPAL			grey	621/50/75	>> 933011
23	4000	2950	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933035
23	4000	2950	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933028
23	5000	2950	105	symmetric		OPAL			grey	621/50/75	>> 933486
23	5000	2950	105	symmetric	yes	OPAL			grey	621/50/75	>> 933493
23	5000	2950	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933516
23	5000	2950	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933509
26	4000	4100	105	VW		transparent			silver	1177/50/75	>> 838149
26	4000	4100	105	VW	yes	transparent			silver	1177/50/75	>> 973826
26	4000	4100	105	VW		transparent		R2	silver	1177/50/75	>> 838149/2
26	4000	4100	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973826/2
27	4000	4150	105	VW		matrix led			grey	590/50/75	>> 827594
27	4000	4150	105	VW	yes	matrix led			grey	590/50/75	>> 827600
27	4000	4150	105	VW		matrix led		R2	grey	590/50/75	>> 827594/2
27	4000	4150	105	VW	yes	matrix led		R2	grey	590/50/75	>> 827600/2
28	4000	4200	105	symmetric		OPAL			grey	621/50/75	>> 934247
28	4000	4200	105	symmetric	yes	OPAL			grey	621/50/75	>> 934254
28	4000	4200	105	symmetric		OPAL	LS2		grey	651/50/75	>> 934278
28	4000	4200	105	symmetric		OPAL	LS2		grey	651/50/75	>> 934261
28	5000	4200	105	symmetric		OPAL			grey	621/50/75	>> 935008

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	5000	4200	105	symmetric	yes	OPAL			grey	621/50/75	>> 935015
28	5000	4200	105	symmetric		OPAL	LS2		grey	651/50/75	>> 935039
28	5000	4200	105	symmetric		OPAL	LS2		grey	651/50/75	>> 935022
30	3000	3900	105	symmetric		OPAL			black	1177/50/75	>> 945724
31	4000	5000	105	VW		transparent			silver	1177/50/75	>> 838156
31	4000	5000	105	VW	yes	transparent			silver	1177/50/75	>> 973833
31	4000	5000	105	VW		transparent		R2	silver	1177/50/75	>> 838156/2
31	4000	5000	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973833/2
33	4000	4450	105	symmetric		OPAL			grey	621/50/75	>> 933165
33	4000	4450	105	symmetric	yes	OPAL			grey	621/50/75	>> 933172
33	4000	4450	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933196
33	4000	4450	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933189
33	5000	4450	105	symmetric		OPAL			grey	621/50/75	>> 933646
33	5000	4450	105	symmetric	yes	OPAL			grey	621/50/75	>> 933653
33	5000	4450	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933677
33	5000	4450	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933660
33	4000	4900	105	VW		matrix led			grey	590/50/75	>> 827617
33	4000	4900	105	VW	yes	matrix led			grey	590/50/75	>> 827624
33	4000	4900	105	VW		matrix led		R2	grey	590/50/75	>> 827617/2
33	4000	4900	105	VW	yes	matrix led		R2	grey	590/50/75	>> 827624/2
37	4000	5500	105	VW		matrix led			grey	590/50/75	>> 827631
37	4000	5500	105	VW	yes	matrix led			grey	590/50/75	>> 827648
37	4000	5500	105	VW		matrix led		R2	grey	590/50/75	>> 827631/2
37	4000	5500	105	VW	yes	matrix led		R2	grey	590/50/75	>> 827648/2
40	4000	6400	105	VW		transparent			silver	1177/50/75	>> 838163
40	4000	6400	105	VW	yes	transparent			silver	1177/50/75	>> 973840
40	4000	6400	105	VW		transparent		R2	silver	1177/50/75	>> 838163/2
40	4000	6400	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973840/2
47	4000	7000	105	symmetric		OPAL			grey	621/50/75	>> 934445
47	4000	7000	105	symmetric	yes	OPAL			grey	621/50/75	>> 934452
47	4000	7000	105	symmetric		OPAL	LS2		grey	651/50/75	>> 934476
47	4000	7000	105	symmetric		OPAL	LS2		grey	651/50/75	>> 934469
47	5000	7000	105	symmetric		OPAL			grey	621/50/75	>> 935206
47	5000	7000	105	symmetric	yes	OPAL			grey	621/50/75	>> 935213
47	5000	7000	105	symmetric		OPAL	LS2		grey	651/50/75	>> 935237
47	5000	7000	105	symmetric		OPAL	LS2		grey	651/50/75	>> 935220
47	4000	8000	105	VW		transparent			silver	1177/50/75	>> 838170
47	4000	8000	105	VW	yes	transparent			silver	1177/50/75	>> 973857

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
47	4000	8000	105	VW		transparent		R2	silver	1177/50/75	>> 838170/2
47	4000	8000	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973857/2
55	4000	8400	105	symmetric		OPAL			grey	1177/50/75	>> 945281
55	4000	8400	105	symmetric	yes	OPAL			grey	1177/50/75	>> 945298
55	4000	8400	105	symmetric		OPAL	LS2,5		grey	1177/50/75	>> 945311
55	4000	8400	105	symmetric		OPAL	LS2		grey	1177/50/75	>> 945304
56	4000	7500	105	symmetric		OPAL			grey	621/50/75	>> 933325
56	4000	7500	105	symmetric	yes	OPAL			grey	621/50/75	>> 933332
56	4000	7500	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933356
56	4000	7500	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933349
56	5000	7500	105	symmetric		OPAL			grey	621/50/75	>> 933806
56	5000	7500	105	symmetric	yes	OPAL			grey	621/50/75	>> 933813
56	5000	7500	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933837
56	5000	7500	105	symmetric		OPAL	LS2		grey	651/50/75	>> 933820
57	4000	9500	105	VW		transparent			silver	1177/50/75	>> 838187
57	4000	9500	105	VW	yes	transparent			silver	1177/50/75	>> 973864
57	4000	9500	105	VW		transparent		R2	silver	1177/50/75	>> 838187/2
57	4000	9500	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973864/2
59	4000	8600	105	symmetric		OPAL			grey	621/50/75	>> 934643
59	4000	8600	105	symmetric	yes	OPAL			grey	621/50/75	>> 934650
59	4000	8600	105	symmetric		OPAL	LS2		grey	651/50/75	>> 934674
59	4000	8600	105	symmetric		OPAL	LS2		grey	651/50/75	>> 934667
59	5000	8600	105	symmetric		OPAL			grey	621/50/75	>> 935404
59	5000	8600	105	symmetric	yes	OPAL			grey	621/50/75	>> 935411
59	5000	8600	105	symmetric		OPAL	LS2		grey	651/50/75	>> 935435
59	5000	8600	105	symmetric		OPAL	LS2		grey	651/50/75	>> 935428
67	4000	10300	105	VW		transparent			silver	1177/50/75	>> 838194
67	4000	10300	105	VW	yes	transparent			silver	1177/50/75	>> 973871
67	4000	10300	105	VW		transparent		R2	silver	1177/50/75	>> 838194/2
67	4000	10300	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973871/2
71	4000	11800	105	VW		transparent			silver	1177/50/75	>> 838200
71	4000	11800	105	VW	yes	transparent			silver	1177/50/75	>> 973888
71	4000	11800	105	VW		transparent		R2	silver	1177/50/75	>> 838200/2
71	4000	11800	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973888/2
80	4000	13300	105	VW		transparent			silver	1177/50/75	>> 838217
80	4000	13300	105	VW	yes	transparent			silver	1177/50/75	>> 973895
80	4000	13300	105	VW		transparent		R2	silver	1177/50/75	>> 838217/2
80	4000	13300	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973895/2

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
81	4000	12100	105	symmetric		OPAL			grey	1177/50/75	>> 944765
81	4000	12100	105	symmetric	yes	OPAL			grey	1177/50/75	>> 944772
81	4000	12100	105	symmetric		OPAL	LS2,5		grey	1177/50/75	>> 944796
81	4000	12100	105	symmetric		OPAL	LS2		grey	1177/50/75	>> 944789
84	4000	12300	105	symmetric		OPAL			grey	1177/50/75	>> 944444
84	4000	12300	105	symmetric	yes	OPAL			grey	1177/50/75	>> 944451
84	4000	12300	105	symmetric		OPAL	LS2,5		grey	1177/50/75	>> 944475
84	4000	12300	105	symmetric		OPAL	LS2		grey	1177/50/75	>> 944468
91	4000	14900	105	VW		transparent			silver	1177/50/75	>> 838224
91	4000	14900	105	VW	yes	transparent			silver	1177/50/75	>> 973901
91	4000	14900	105	VW		transparent		R2	silver	1177/50/75	>> 838224/2
91	4000	14900	105	VW	yes	transparent		R2	silver	1177/50/75	>> 973901/2
94	4000	14100	105	symmetric		OPAL			grey	1177/50/75	>> 944604
94	4000	14100	105	symmetric	yes	OPAL			grey	1177/50/75	>> 944611
94	4000	14100	105	symmetric		OPAL	LS2,5		grey	1177/50/75	>> 944635
94	4000	14100	105	symmetric		OPAL	LS2		grey	1177/50/75	>> 944628
117	4000	16200	105	symmetric		OPAL			grey	1177/50/75	>> 944284
117	4000	16200	105	symmetric	yes	OPAL			grey	1177/50/75	>> 944291
117	4000	16200	105	symmetric		OPAL	LS2		grey	1177/50/75	>> 944307
117	4000	16200	105	symmetric		OPAL	LS2,5		grey	1177/50/75	>> 944314

INDUSTRY SLIM LED 120°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
23	4000	3200	120	symmetric		transparent			grey	621/50/75	>> 934001
23	4000	3200	120	symmetric	yes	transparent			grey	621/50/75	>> 934018
23	4000	3200	120	symmetric		transparent	LS2		grey	651/50/75	>> 934032
23	4000	3200	120	symmetric		transparent	LS2		grey	651/50/75	>> 934025
23	5000	3200	120	symmetric		transparent			grey	621/50/75	>> 934124
23	5000	3200	120	symmetric	yes	transparent			grey	621/50/75	>> 934131
23	5000	3200	120	symmetric		transparent	LS2		grey	651/50/75	>> 934155
23	5000	3200	120	symmetric		transparent	LS2		grey	651/50/75	>> 934148
28	4000	4550	120	symmetric		transparent			grey	621/50/75	>> 934285
28	4000	4550	120	symmetric	yes	transparent			grey	621/50/75	>> 934292
28	4000	4550	120	symmetric		transparent	LS2		grey	651/50/75	>> 934315
28	4000	4550	120	symmetric		transparent	LS2		grey	651/50/75	>> 934308
28	5000	4550	120	symmetric		transparent			grey	621/50/75	>> 935046
28	5000	4550	120	symmetric	yes	transparent			grey	621/50/75	>> 935053

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	5000	4550	120	symmetric		transparent	LS2		grey	651/50/75	>> 935077
28	5000	4550	120	symmetric		transparent	LS2		grey	651/50/75	>> 935060
33	4000	4800	120	symmetric		transparent			grey	621/50/75	>> 934049
33	4000	4800	120	symmetric	yes	transparent			grey	621/50/75	>> 934056
33	4000	4800	120	symmetric		transparent	LS2		grey	651/50/75	>> 934063
33	4000	4800	120	symmetric		transparent	LS2		grey	651/50/75	>> 934070
33	5000	4800	120	symmetric		transparent			grey	621/50/75	>> 934162
33	5000	4800	120	symmetric	yes	transparent			grey	621/50/75	>> 934179
33	5000	4800	120	symmetric		transparent	LS2		grey	651/50/75	>> 934186
33	5000	4800	120	symmetric		transparent	LS2		grey	651/50/75	>> 934193
47	4000	7550	120	symmetric		transparent			grey	621/50/75	>> 934483
47	4000	7550	120	symmetric	yes	transparent			grey	621/50/75	>> 934490
47	4000	7550	120	symmetric		transparent	LS2		grey	651/50/75	>> 934513
47	4000	7550	120	symmetric		transparent	LS2		grey	651/50/75	>> 934506
47	5000	7550	120	symmetric		transparent			grey	621/50/75	>> 935244
47	5000	7550	120	symmetric	yes	transparent			grey	621/50/75	>> 935251
47	5000	7550	120	symmetric		transparent	LS2		grey	651/50/75	>> 935275
47	5000	7550	120	symmetric		transparent	LS2		grey	651/50/75	>> 935268
55	4000	9000	120	symmetric		transparent			grey	1177/50/75	>> 945243
55	4000	9000	120	symmetric	yes	transparent			grey	1177/50/75	>> 945250
55	4000	9000	120	symmetric		transparent	LS2,5		grey	1177/50/75	>> 945274
55	4000	9000	120	symmetric		transparent	LS2		grey	1177/50/75	>> 945267
56	4000	8100	120	symmetric		transparent			grey	621/50/75	>> 934087
56	4000	8100	120	symmetric	yes	transparent			grey	621/50/75	>> 934094
56	4000	8100	120	symmetric		transparent	LS2		grey	651/50/75	>> 934100
56	4000	8100	120	symmetric		transparent	LS2		grey	651/50/75	>> 934117
56	5000	8100	120	symmetric		transparent			grey	621/50/75	>> 934209
56	5000	8100	120	symmetric	yes	transparent			grey	621/50/75	>> 934216
56	5000	8100	120	symmetric		transparent	LS2		grey	651/50/75	>> 934223
56	5000	8100	120	symmetric		transparent	LS2		grey	651/50/75	>> 934230
59	4000	9250	120	symmetric		transparent			grey	621/50/75	>> 934681
59	4000	9250	120	symmetric	yes	transparent			grey	621/50/75	>> 934698
59	4000	9250	120	symmetric		transparent	LS2		grey	651/50/75	>> 934711
59	4000	9250	120	symmetric		transparent	LS2		grey	651/50/75	>> 934704
59	5000	9250	120	symmetric		transparent			grey	621/50/75	>> 935442
59	5000	9250	120	symmetric	yes	transparent			grey	621/50/75	>> 935459
59	5000	9250	120	symmetric		transparent	LS2		grey	651/50/75	>> 935473
59	5000	9250	120	symmetric		transparent	LS2		grey	651/50/75	>> 935466

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
81	4000	13000	120	symmetric		transparent			grey	1177/50/75	>> 944727
81	4000	13000	120	symmetric	yes	transparent			grey	1177/50/75	>> 944734
81	4000	13000	120	symmetric		transparent	LS2,5		grey	1177/50/75	>> 944758
81	4000	13000	120	symmetric		transparent	LS2		grey	1177/50/75	>> 944741
84	4000	13300	120	symmetric		transparent			grey	1177/50/75	>> 944406
84	4000	13300	120	symmetric	yes	transparent			grey	1177/50/75	>> 944413
84	4000	13300	120	symmetric		transparent	LS2,5		grey	1177/50/75	>> 944437
84	4000	13300	120	symmetric		transparent	LS2		grey	1177/50/75	>> 944420
94	4000	15300	120	symmetric		transparent			grey	1177/50/75	>> 944567
94	4000	15300	120	symmetric	yes	transparent			grey	1177/50/75	>> 944574
94	4000	15300	120	symmetric		transparent	LS2,5		grey	1177/50/75	>> 944598
94	4000	15300	120	symmetric		transparent	LS2		grey	1177/50/75	>> 944581
103	4000	17000	120	symmetric		transparent		R2	grey	1177/50/75	>> 944994/2
117	4000	17500	120	symmetric		transparent			grey	1177/50/75	>> 944246
117	4000	17500	120	symmetric	yes	transparent			grey	1177/50/75	>> 944253
117	4000	17500	120	symmetric		transparent	LS2		grey	1177/50/75	>> 944260
117	4000	17500	120	symmetric		transparent	LS2,5		grey	1177/50/75	>> 944277

INDUSTRY SLIM LED 30°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
22	4000	3400	30	VN		matrix led			grey	590/50/75	>> 827495
22	4000	3400	30	VN	yes	matrix led			grey	590/50/75	>> 827501
27	4000	4050	30	VN		matrix led			grey	590/50/75	>> 827518
27	4000	4050	30	VN	yes	matrix led			grey	590/50/75	>> 827525
33	4000	4800	30	VN		matrix led			grey	590/50/75	>> 827532
33	4000	4800	30	VN	yes	matrix led			grey	590/50/75	>> 827549
37	4000	5400	30	VN		matrix led			grey	590/50/75	>> 827556
37	4000	5400	30	VN	yes	matrix led			grey	590/50/75	>> 827563

INDUSTRY SLIM LED 35/67°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
22	4000	3400	35/67	CN		matrix led			grey	590/50/75	>> 827013
22	4000	3400	35/67	CN	yes	matrix led			grey	590/50/75	>> 827020
27	4000	4050	35/67	CN		matrix led			grey	590/50/75	>> 827037
27	4000	4050	35/67	CN	yes	matrix led			grey	590/50/75	>> 827044
33	4000	4800	35/67	CN		matrix led			grey	590/50/75	>> 827051
33	4000	4800	35/67	CN	yes	matrix led			grey	590/50/75	>> 827068
37	4000	5400	35/67	CN		matrix led			grey	590/50/75	>> 827075
37	4000	5400	35/67	CN	yes	matrix led			grey	590/50/75	>> 827082

INDUSTRY SLIM LED 46/117°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
23	4000	2950	46/117	corridor		transparent			grey	621/50/75	>> 933042
23	4000	2950	46/117	corridor	yes	transparent			grey	621/50/75	>> 933059
23	4000	2950	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933073
23	4000	2950	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933066
23	5000	2950	46/117	corridor		transparent			grey	621/50/75	>> 933523
23	5000	2950	46/117	corridor	yes	transparent			grey	621/50/75	>> 933530
23	5000	2950	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933554
23	5000	2950	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933547
28	4000	4250	46/117	corridor		transparent			grey	621/50/75	>> 934322
28	4000	4250	46/117	corridor	yes	transparent			grey	621/50/75	>> 934339
28	4000	4250	46/117	corridor		transparent	LS2		grey	651/50/75	>> 934353
28	4000	4250	46/117	corridor		transparent	LS2		grey	651/50/75	>> 934346
28	5000	4250	46/117	corridor		transparent			grey	621/50/75	>> 935084
28	5000	4250	46/117	corridor	yes	transparent			grey	621/50/75	>> 935091
28	5000	4250	46/117	corridor		transparent	LS2		grey	651/50/75	>> 935114
28	5000	4250	46/117	corridor		transparent	LS2		grey	651/50/75	>> 935107
33	4000	4500	46/117	corridor		transparent			grey	621/50/75	>> 933202
33	4000	4500	46/117	corridor	yes	transparent			grey	621/50/75	>> 933219
33	4000	4500	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933233
33	4000	4500	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933226
33	5000	4500	46/117	corridor		transparent			grey	621/50/75	>> 933684
33	5000	4500	46/117	corridor	yes	transparent			grey	621/50/75	>> 933691

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
33	5000	4500	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933714
33	5000	4500	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933707
47	4000	7100	46/117	corridor		transparent			grey	621/50/75	>> 934520
47	4000	7100	46/117	corridor	yes	transparent			grey	621/50/75	>> 934537
47	4000	7100	46/117	corridor		transparent	LS2		grey	651/50/75	>> 934551
47	4000	7100	46/117	corridor		transparent	LS2		grey	651/50/75	>> 934544
47	5000	7100	46/117	corridor		transparent			grey	621/50/75	>> 935282
47	5000	7100	46/117	corridor	yes	transparent			grey	621/50/75	>> 935299
47	5000	7100	46/117	corridor		transparent	LS2		grey	651/50/75	>> 935312
47	5000	7100	46/117	corridor		transparent	LS2		grey	651/50/75	>> 935305
55	4000	8500	46/117	corridor		transparent			grey	1177/50/75	>> 945328
55	4000	8500	46/117	corridor	yes	transparent			grey	1177/50/75	>> 945335
55	4000	8500	46/117	corridor		transparent	LS2,5		grey	1177/50/75	>> 945359
55	4000	8500	46/117	corridor		transparent	LS2		grey	1177/50/75	>> 945342
56	4000	7600	46/117	corridor		transparent			grey	621/50/75	>> 933363
56	4000	7600	46/117	corridor	yes	transparent			grey	621/50/75	>> 933370
56	4000	7600	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933394
56	4000	7600	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933387
56	5000	7600	46/117	corridor		transparent			grey	621/50/75	>> 933844
56	5000	7600	46/117	corridor	yes	transparent			grey	621/50/75	>> 933851
56	5000	7600	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933875
56	5000	7600	46/117	corridor		transparent	LS2		grey	651/50/75	>> 933868
59	4000	8700	46/117	corridor		transparent			grey	621/50/75	>> 934728
59	4000	8700	46/117	corridor	yes	transparent			grey	621/50/75	>> 934735
59	4000	8700	46/117	corridor		transparent	LS2		grey	651/50/75	>> 934759
59	4000	8700	46/117	corridor		transparent	LS2		grey	651/50/75	>> 934742
59	5000	8700	46/117	corridor		transparent			grey	621/50/75	>> 935480
59	5000	8700	46/117	corridor	yes	transparent			grey	621/50/75	>> 935497
59	5000	8700	46/117	corridor		transparent	LS2		grey	651/50/75	>> 935510
59	5000	8700	46/117	corridor		transparent	LS2		grey	651/50/75	>> 935503
81	4000	12300	46/117	corridor		transparent			grey	1177/50/75	>> 944802
81	4000	12300	46/117	corridor	yes	transparent			grey	1177/50/75	>> 944819
81	4000	12300	46/117	corridor		transparent	LS2,5		grey	1177/50/75	>> 944833
81	4000	12300	46/117	corridor		transparent	LS2		grey	1177/50/75	>> 944826
84	4000	12450	46/117	corridor		transparent			grey	1177/50/75	>> 944482
84	4000	12450	46/117	corridor	yes	transparent			grey	1177/50/75	>> 944499
84	4000	12450	46/117	corridor		transparent	LS2,5		grey	1177/50/75	>> 944512
84	4000	12450	46/117	corridor		transparent	LS2		grey	1177/50/75	>> 944505

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
94	4000	14400	46/117	corridor		transparent			grey	1177/50/75	>> 944642
94	4000	14400	46/117	corridor	yes	transparent			grey	1177/50/75	>> 944659
94	4000	14400	46/117	corridor		transparent	LS2,5		grey	1177/50/75	>> 944673
94	4000	14400	46/117	corridor		transparent	LS2		grey	1177/50/75	>> 944666
117	4000	16350	46/117	corridor		transparent			grey	1177/50/75	>> 944321
117	4000	16350	46/117	corridor	yes	transparent			grey	1177/50/75	>> 944338
117	4000	16350	46/117	corridor		transparent	LS2		grey	1177/50/75	>> 944345
117	4000	16350	46/117	corridor		transparent	LS2,5		grey	1177/50/75	>> 944352

INDUSTRY SLIM LED 65°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
22	4000	3400	65	SN		matrix led			grey	590/50/75	>> 827334
22	4000	3400	65	SN	yes	matrix led			grey	590/50/75	>> 827341
27	4000	4050	65	SN		matrix led			grey	590/50/75	>> 827358
27	4000	4050	65	SN	yes	matrix led			grey	590/50/75	>> 827365
33	4000	4800	65	SN		matrix led			grey	590/50/75	>> 827372
33	4000	4800	65	SN	yes	matrix led			grey	590/50/75	>> 827389
37	4000	5400	65	SN		matrix led			grey	590/50/75	>> 827396
37	4000	5400	65	SN	yes	matrix led			grey	590/50/75	>> 827402

INDUSTRY SLIM LED 80°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
14	4000	2100	80	SW		transparent			silver	1177/50/75	>> 838033
14	4000	2100	80	SW	yes	transparent			silver	1177/50/75	>> 973703
14	4000	2100	80	SW		transparent		R2	silver	1177/50/75	>> 838033/2
14	4000	2100	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973703/2
18	4000	2700	80	SW		transparent			silver	1177/50/75	>> 672989
18	4000	2700	80	SW	yes	transparent			silver	1177/50/75	>> 973710
18	4000	2700	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973710/2
22	4000	3500	80	SW		matrix led			grey	590/50/75	>> 827419
22	4000	3500	80	SW	yes	matrix led			grey	590/50/75	>> 827426
22	4000	3500	80	SW		matrix led		R2	grey	590/50/75	>> 827419/2

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
22	4000	3500	80	SW	yes	matrix led		R2	grey	590/50/75	>> 827426/2
26	4000	4100	80	SW		transparent			silver	1177/50/75	>> 672996
26	4000	4100	80	SW	yes	transparent			silver	1177/50/75	>> 973727
26	4000	4100	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973727/2
27	4000	4150	80	SW		matrix led			grey	590/50/75	>> 827433
27	4000	4150	80	SW	yes	matrix led			grey	590/50/75	>> 827440
27	4000	4150	80	SW		matrix led		R2	grey	590/50/75	>> 827433/2
27	4000	4150	80	SW	yes	matrix led		R2	grey	590/50/75	>> 827440/2
31	4000	5000	80	SW		transparent			silver	1177/50/75	>> 838040
31	4000	5000	80	SW	yes	transparent			silver	1177/50/75	>> 973734
31	4000	5000	80	SW		transparent		R2	silver	1177/50/75	>> 838040/2
31	4000	5000	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973734/2
33	4000	4900	80	SW		matrix led			grey	590/50/75	>> 827457
33	4000	4900	80	SW	yes	matrix led			grey	590/50/75	>> 827464
33	4000	4900	80	SW		matrix led		R2	grey	590/50/75	>> 827457/2
33	4000	4900	80	SW	yes	matrix led		R2	grey	590/50/75	>> 827464/2
37	4000	5500	80	SW		matrix led			grey	590/50/75	>> 827471
37	4000	5500	80	SW	yes	matrix led			grey	590/50/75	>> 827488
37	4000	5500	80	SW		matrix led		R2	grey	590/50/75	>> 827471/2
37	4000	5500	80	SW	yes	matrix led		R2	grey	590/50/75	>> 827488/2
40	4000	6400	80	SW		transparent			silver	1177/50/75	>> 838057
40	4000	6400	80	SW	yes	transparent			silver	1177/50/75	>> 973741
40	4000	6400	80	SW		transparent		R2	silver	1177/50/75	>> 838057/2
40	4000	6400	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973741/2
47	4000	8000	80	SW		transparent			silver	1177/50/75	>> 838064
47	4000	8000	80	SW	yes	transparent			silver	1177/50/75	>> 973758
47	4000	8000	80	SW		transparent		R2	silver	1177/50/75	>> 838064/2
47	4000	8000	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973758/2
57	4000	9500	80	SW		transparent			silver	1177/50/75	>> 838071
57	4000	9500	80	SW	yes	transparent			silver	1177/50/75	>> 973765
57	4000	9500	80	SW		transparent		R2	silver	1177/50/75	>> 838071/2
57	4000	9500	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973765/2
61	4000	10300	80	SW		transparent			silver	1177/50/75	>> 838088
61	4000	10300	80	SW	yes	transparent			silver	1177/50/75	>> 973772
61	4000	10300	80	SW		transparent		R2	silver	1177/50/75	>> 838088/2
61	4000	10300	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973772/2
71	4000	11800	80	SW		transparent			silver	1177/50/75	>> 838095
71	4000	11800	80	SW	yes	transparent			silver	1177/50/75	>> 973789

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
71	4000	11800	80	SW		transparent		R2	silver	1177/50/75	>> 838095/2
71	4000	11800	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973789/2
80	4000	13300	80	SW		transparent			silver	1177/50/75	>> 838101
80	4000	13300	80	SW	yes	transparent			silver	1177/50/75	>> 944987
80	4000	13300	80	SW		transparent		R2	silver	1177/50/75	>> 838101/2
91	4000	14900	80	SW		transparent			silver	1177/50/75	>> 838118
91	4000	14900	80	SW	yes	transparent			silver	1177/50/75	>> 973796
91	4000	14900	80	SW		transparent		R2	silver	1177/50/75	>> 838118/2
91	4000	14900	80	SW	yes	transparent		R2	silver	1177/50/75	>> 973796/2

INDUSTRY SLIM LED 90°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
14	4000	2100	90	MW		transparent			silver	1177/50/75	>> 838231
14	4000	2100	90	MW	yes	transparent			silver	1177/50/75	>> 973918
14	4000	2021	90	MW MAT		transparent			silver	1177/50/75	>> 208874
14	4000	2021	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209055
14	4000	2000	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208874/2
14	4000	2000	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209055/2
14	4000	2043	90	SA MAT		transparent			silver	1177/50/75	>> 210501
14	4000	2043	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210679
14	4000	2000	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210501/2
14	4000	2000	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210679/2
14	4000	2043	90	SN MAT		transparent			silver	1177/50/75	>> 210075
14	4000	2043	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210280
14	4000	2021	90	SW MAT		transparent			silver	1177/50/75	>> 209277
14	4000	2021	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209444
14	4000	2000	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209277/2
14	4000	2000	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209444/2
14	4000	2021	90	VW MAT		transparent			silver	1177/50/75	>> 209666
14	4000	2021	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209833
14	4000	2000	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209666/2
14	4000	2000	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209833/2
14	4000	2089	90	DAN MAT		transparent			silver	1177/50/75	>> 210891
14	4000	2089	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211072
14	4000	2050	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210891/2
14	4000	2050	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211072/2
14	4000	2100	90	MW		transparent		R2	silver	1177/50/75	>> 838231/2

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
14	4000	2100	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973918/2
18	4000	2700	90	MW		transparent			silver	1177/50/75	>> 838248
18	4000	2700	90	MW	yes	transparent			silver	1177/50/75	>> 973925
18	4000	2599	90	MW MAT		transparent			silver	1177/50/75	>> 208881
18	4000	2599	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209062
18	4000	2550	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208881/2
18	4000	2550	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209062/2
18	4000	2599	90	SW MAT		transparent			silver	1177/50/75	>> 209284
18	4000	2599	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209451
18	4000	2550	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209284/2
18	4000	2550	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209451/2
18	4000	2599	90	VW MAT		transparent			silver	1177/50/75	>> 209673
18	4000	2599	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209840
18	4000	2550	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209673/2
18	4000	2550	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209840/2
18	4000	2626	90	SA MAT		transparent			silver	1177/50/75	>> 210518
18	4000	2626	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210686
18	4000	2600	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210518/2
18	4000	2600	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210686/2
18	4000	2626	90	SN MAT		transparent			silver	1177/50/75	>> 210082
18	4000	2626	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210297
18	4000	2686	90	DAN MAT		transparent			silver	1177/50/75	>> 210907
18	4000	2686	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211089
18	4000	2650	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210907/2
18	4000	2650	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211089/2
18	4000	2700	90	MW		transparent		R2	silver	1177/50/75	>> 838248/2
18	4000	2700	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973925/2
22	4000	3500	90	MW		matrix led			grey	590/50/75	>> 827174
22	4000	3500	90	MW	yes	matrix led			grey	590/50/75	>> 827181
22	4000	3321	90	MW MAT		matrix led			grey	590/50/75	>> 208751
22	4000	3321	90	MW MAT	yes	matrix led			grey	590/50/75	>> 208768
22	4000	3300	90	MW MAT		matrix led		R2	grey	590/50/75	>> 208751/2
22	4000	3300	90	MW MAT	yes	matrix led		R2	grey	590/50/75	>> 208768/2
22	4000	3356	90	SA MAT		matrix led			grey	590/50/75	>> 210389
22	4000	3356	90	SA MAT	yes	matrix led			grey	590/50/75	>> 210396
22	4000	3300	90	SA MAT		matrix led		R2	grey	590/50/75	>> 210389/2
22	4000	3300	90	SA MAT	yes	matrix led		R2	grey	590/50/75	>> 210396/2
22	4000	3356	90	SN MAT		matrix led			grey	590/50/75	>> 209932

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
22	4000	3356	90	SN MAT	yes	matrix led			grey	590/50/75	>> 209949
22	4000	3321	90	SW MAT		matrix led			grey	590/50/75	>> 209154
22	4000	3321	90	SW MAT	yes	matrix led			grey	590/50/75	>> 209161
22	4000	3300	90	SW MAT		matrix led		R2	grey	590/50/75	>> 209154/2
22	4000	3300	90	SW MAT	yes	matrix led		R2	grey	590/50/75	>> 209161/2
22	4000	3321	90	VW MAT		matrix led			grey	590/50/75	>> 209543
22	4000	3321	90	VW MAT	yes	matrix led			grey	590/50/75	>> 209550
22	4000	3300	90	VW MAT		matrix led		R2	grey	590/50/75	>> 209543/2
22	4000	3300	90	VW MAT	yes	matrix led		R2	grey	590/50/75	>> 209550/2
22	4000	3432	90	DAN MAT		matrix led			grey	590/50/75	>> 210778
22	4000	3432	90	DAN MAT	yes	matrix led			grey	590/50/75	>> 210785
22	4000	3400	90	DAN MAT		matrix led		R2	grey	590/50/75	>> 210778/2
22	4000	3400	90	DAN MAT	yes	matrix led		R2	grey	590/50/75	>> 210785/2
22	4000	3500	90	MW		matrix led		R2	grey	590/50/75	>> 827174/2
22	4000	3500	90	MW	yes	matrix led		R2	grey	590/50/75	>> 827181/2
26	4000	4100	90	MW		transparent			silver	1177/50/75	>> 838255
26	4000	4100	90	MW	yes	transparent			silver	1177/50/75	>> 973932
26	4000	3946	90	MW MAT	yes	transparent			silver	1177/50/75	>> 208836
26	4000	3900	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 208836/2
26	4000	3946	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209239
26	4000	3900	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209239/2
26	4000	3946	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209628
26	4000	3900	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209628/2
26	4000	3946	90	MW MAT		transparent			silver	1177/50/75	>> 208898
26	4000	3946	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209079
26	4000	3900	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208898/2
26	4000	3900	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209079/2
26	4000	3946	90	SW MAT		transparent			silver	1177/50/75	>> 209291
26	4000	3946	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209468
26	4000	3900	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209291/2
26	4000	3900	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209468/2
26	4000	3946	90	VW MAT		transparent			silver	1177/50/75	>> 209680
26	4000	3946	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209857
26	4000	3900	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209680/2
26	4000	3900	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209857/2
26	4000	3988	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210464
26	4000	3950	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210464/2
26	4000	3988	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210037

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
26	4000	3988	90	SA MAT		transparent			silver	1177/50/75	>> 210525
26	4000	3988	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210693
26	4000	3950	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210525/2
26	4000	3950	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210693/2
26	4000	3988	90	SN MAT		transparent			silver	1177/50/75	>> 210099
26	4000	3988	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210303
26	4000	4079	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 210853
26	4000	4050	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 210853/2
26	4000	4079	90	DAN MAT		transparent			silver	1177/50/75	>> 210914
26	4000	4079	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211096
26	4000	4050	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210914/2
26	4000	4050	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211096/2
26	4000	4100	90	MW		transparent		R2	silver	1177/50/75	>> 838255/2
26	4000	4100	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973932/2
27	4000	4150	90	MW		matrix led			grey	590/50/75	>> 827198
27	4000	4150	90	MW	yes	matrix led			grey	590/50/75	>> 827204
27	4000	3994	90	MW MAT		matrix led			grey	590/50/75	>> 208775
27	4000	3994	90	MW MAT	yes	matrix led			grey	590/50/75	>> 208782
27	4000	3950	90	MW MAT		matrix led		R2	grey	590/50/75	>> 208775/2
27	4000	3950	90	MW MAT	yes	matrix led		R2	grey	590/50/75	>> 208782/2
27	4000	3994	90	SW MAT		matrix led			grey	590/50/75	>> 209178
27	4000	3994	90	SW MAT	yes	matrix led			grey	590/50/75	>> 209185
27	4000	3950	90	SW MAT		matrix led		R2	grey	590/50/75	>> 209178/2
27	4000	3950	90	SW MAT	yes	matrix led		R2	grey	590/50/75	>> 209185/2
27	4000	3994	90	VW MAT		matrix led			grey	590/50/75	>> 209567
27	4000	3994	90	VW MAT	yes	matrix led			grey	590/50/75	>> 209574
27	4000	3950	90	VW MAT		matrix led		R2	grey	590/50/75	>> 209567/2
27	4000	3950	90	VW MAT	yes	matrix led		R2	grey	590/50/75	>> 209574/2
27	4000	4036	90	SA MAT		matrix led			grey	590/50/75	>> 210402
27	4000	4036	90	SA MAT	yes	matrix led			grey	590/50/75	>> 210419
27	4000	4000	90	SA MAT		matrix led		R2	grey	590/50/75	>> 210402/2
27	4000	4000	90	SA MAT	yes	matrix led		R2	grey	590/50/75	>> 210419/2
27	4000	4036	90	SN MAT		matrix led			grey	590/50/75	>> 209956
27	4000	4036	90	SN MAT	yes	matrix led			grey	590/50/75	>> 209963
27	4000	4129	90	DAN MAT		matrix led			grey	590/50/75	>> 210792
27	4000	4129	90	DAN MAT	yes	matrix led			grey	590/50/75	>> 210808
27	4000	4100	90	DAN MAT		matrix led		R2	grey	590/50/75	>> 210792/2
27	4000	4100	90	DAN MAT	yes	matrix led		R2	grey	590/50/75	>> 210808/2

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
27	4000	4150	90	MW		matrix led		R2	grey	590/50/75	>> 827198/2
27	4000	4150	90	MW	yes	matrix led		R2	grey	590/50/75	>> 827204/2
31	4000	5000	90	MW		transparent			silver	1177/50/75	>> 838262
31	4000	5000	90	MW	yes	transparent			silver	1177/50/75	>> 973949
31	4000	4813	90	MW MAT		transparent			silver	1177/50/75	>> 208904
31	4000	4813	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209086
31	4000	4750	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208904/2
31	4000	4750	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209086/2
31	4000	4813	90	SW MAT		transparent			silver	1177/50/75	>> 209307
31	4000	4813	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209475
31	4000	4750	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209307/2
31	4000	4750	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209475/2
31	4000	4813	90	VW MAT		transparent			silver	1177/50/75	>> 209697
31	4000	4813	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209864
31	4000	4750	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209697/2
31	4000	4750	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209864/2
31	4000	4863	90	SA MAT		transparent			silver	1177/50/75	>> 210532
31	4000	4863	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210709
31	4000	4800	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210532/2
31	4000	4800	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210709/2
31	4000	4863	90	SN MAT		transparent			silver	1177/50/75	>> 210105
31	4000	4863	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210310
31	4000	4974	90	DAN MAT		transparent			silver	1177/50/75	>> 210921
31	4000	4974	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211102
31	4000	4950	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210921/2
31	4000	4950	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211102/2
31	4000	5000	90	MW		transparent		R2	silver	1177/50/75	>> 838262/2
31	4000	5000	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973949/2
33	4000	4900	90	MW		matrix led			grey	590/50/75	>> 827211
33	4000	4900	90	MW	yes	matrix led			grey	590/50/75	>> 827228
33	4000	4716	90	MW MAT		matrix led			grey	590/50/75	>> 208799
33	4000	4716	90	MW MAT	yes	matrix led			grey	590/50/75	>> 208805
33	4000	4650	90	MW MAT		matrix led		R2	grey	590/50/75	>> 208799/2
33	4000	4650	90	MW MAT	yes	matrix led		R2	grey	590/50/75	>> 208805/2
33	4000	4716	90	SW MAT		matrix led			grey	590/50/75	>> 209192
33	4000	4716	90	SW MAT	yes	matrix led			grey	590/50/75	>> 209208
33	4000	4650	90	SW MAT		matrix led		R2	grey	590/50/75	>> 209192/2
33	4000	4650	90	SW MAT	yes	matrix led		R2	grey	590/50/75	>> 209208/2

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
33	4000	4716	90	VW MAT		matrix led			grey	590/50/75	>> 209581
33	4000	4716	90	VW MAT	yes	matrix led			grey	590/50/75	>> 209598
33	4000	4650	90	VW MAT		matrix led		R2	grey	590/50/75	>> 209581/2
33	4000	4650	90	VW MAT	yes	matrix led		R2	grey	590/50/75	>> 209598/2
33	4000	4766	90	SA MAT		matrix led			grey	590/50/75	>> 210426
33	4000	4766	90	SA MAT	yes	matrix led			grey	590/50/75	>> 210433
33	4000	4700	90	SA MAT		matrix led		R2	grey	590/50/75	>> 210426/2
33	4000	4700	90	SA MAT	yes	matrix led		R2	grey	590/50/75	>> 210433/2
33	4000	4766	90	SN MAT		matrix led			grey	590/50/75	>> 209970
33	4000	4766	90	SN MAT	yes	matrix led			grey	590/50/75	>> 209987
33	4000	4875	90	DAN MAT		matrix led			grey	590/50/75	>> 210815
33	4000	4875	90	DAN MAT	yes	matrix led			grey	590/50/75	>> 210822
33	4000	4850	90	DAN MAT		matrix led		R2	grey	590/50/75	>> 210815/2
33	4000	4850	90	DAN MAT	yes	matrix led		R2	grey	590/50/75	>> 210822/2
33	4000	4900	90	MW		matrix led		R2	grey	590/50/75	>> 827211/2
33	4000	4900	90	MW	yes	matrix led		R2	grey	590/50/75	>> 827228/2
37	4000	5500	90	MW		matrix led			grey	590/50/75	>> 827235
37	4000	5500	90	MW	yes	matrix led			grey	590/50/75	>> 827242
37	4000	5294	90	MW MAT		matrix led			grey	590/50/75	>> 208812
37	4000	5294	90	MW MAT	yes	matrix led			grey	590/50/75	>> 208829
37	4000	5250	90	MW MAT		matrix led		R2	grey	590/50/75	>> 208812/2
37	4000	5250	90	MW MAT	yes	matrix led		R2	grey	590/50/75	>> 208829/2
37	4000	5294	90	SW MAT		matrix led			grey	590/50/75	>> 209215
37	4000	5294	90	SW MAT	yes	matrix led			grey	590/50/75	>> 209222
37	4000	5250	90	SW MAT		matrix led		R2	grey	590/50/75	>> 209215/2
37	4000	5250	90	SW MAT	yes	matrix led		R2	grey	590/50/75	>> 209222/2
37	4000	5294	90	VW MAT		matrix led			grey	590/50/75	>> 209604
37	4000	5294	90	VW MAT	yes	matrix led			grey	590/50/75	>> 209611
37	4000	5250	90	VW MAT		matrix led		R2	grey	590/50/75	>> 209604/2
37	4000	5250	90	VW MAT	yes	matrix led		R2	grey	590/50/75	>> 209611/2
37	4000	5349	90	SA MAT		matrix led			grey	590/50/75	>> 210440
37	4000	5349	90	SA MAT	yes	matrix led			grey	590/50/75	>> 210457
37	4000	5300	90	SA MAT		matrix led		R2	grey	590/50/75	>> 210440/2
37	4000	5300	90	SA MAT	yes	matrix led		R2	grey	590/50/75	>> 210457/2
37	4000	5349	90	SN MAT		matrix led			grey	590/50/75	>> 209994
37	4000	5349	90	SN MAT	yes	matrix led			grey	590/50/75	>> 210020
37	4000	5472	90	DAN MAT		matrix led			grey	590/50/75	>> 210839
37	4000	5472	90	DAN MAT	yes	matrix led			grey	590/50/75	>> 210846

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
37	4000	5400	90	DAN MAT		matrix led		R2	grey	590/50/75	>> 210839/2
37	4000	5400	90	DAN MAT	yes	matrix led		R2	grey	590/50/75	>> 210846/2
37	4000	5500	90	MW		matrix led		R2	grey	590/50/75	>> 827235/2
37	4000	5500	90	MW	yes	matrix led		R2	grey	590/50/75	>> 827242/2
40	4000	6400	90	MW		transparent			silver	1177/50/75	>> 838279
40	4000	6400	90	MW	yes	transparent			silver	1177/50/75	>> 973956
40	4000	6160	90	MW MAT		transparent			silver	1177/50/75	>> 208911
40	4000	6160	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209093
40	4000	6100	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208911/2
40	4000	6100	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209093/2
40	4000	6160	90	SW MAT		transparent			silver	1177/50/75	>> 209314
40	4000	6160	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209482
40	4000	6100	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209314/2
40	4000	6100	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209482/2
40	4000	6160	90	VW MAT		transparent			silver	1177/50/75	>> 209703
40	4000	6160	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209871
40	4000	6100	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209703/2
40	4000	6100	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209871/2
40	4000	6225	90	SA MAT		transparent			silver	1177/50/75	>> 210549
40	4000	6225	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210716
40	4000	6150	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210549/2
40	4000	6150	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210716/2
40	4000	6225	90	SN MAT		transparent			silver	1177/50/75	>> 210112
40	4000	6225	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210327
40	4000	6367	90	DAN MAT		transparent			silver	1177/50/75	>> 210938
40	4000	6367	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211119
40	4000	6300	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210938/2
40	4000	6300	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211119/2
40	4000	6400	90	MW		transparent		R2	silver	1177/50/75	>> 838279/2
40	4000	6400	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973956/2
47	4000	8000	90	MW		transparent			silver	1177/50/75	>> 944925
47	4000	8000	90	MW	yes	transparent			silver	1177/50/75	>> 973963
47	4000	6882	90	MW MAT		transparent			silver	1177/50/75	>> 208997
47	4000	6800	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208997/2
47	4000	6882	90	SW MAT		transparent			silver	1177/50/75	>> 209390
47	4000	6800	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209390/2
47	4000	6882	90	VW MAT		transparent			silver	1177/50/75	>> 209789
47	4000	6800	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209789/2

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
47	4000	6954	90	SA MAT		transparent			silver	1177/50/75	>> 210624
47	4000	6900	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210624/2
47	4000	6954	90	SN MAT		transparent			silver	1177/50/75	>> 210235
47	4000	7113	90	DAN MAT		transparent			silver	1177/50/75	>> 211027
47	4000	7050	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 211027/2
47	4000	7700	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209109
47	4000	7600	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209109/2
47	4000	7700	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209499
47	4000	7600	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209499/2
47	4000	7700	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209888
47	4000	7600	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209888/2
47	4000	7781	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210723
47	4000	7700	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210723/2
47	4000	7781	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210334
47	4000	7959	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211126
47	4000	7900	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211126/2
47	4000	8000	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973963/2
57	4000	9500	90	MW		transparent			silver	1177/50/75	>> 838286
57	4000	9500	90	MW	yes	transparent			silver	1177/50/75	>> 973970
57	4000	9144	90	MW MAT	yes	transparent			silver	1177/50/75	>> 208843
57	4000	9050	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 208843/2
57	4000	9144	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209246
57	4000	9050	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209246/2
57	4000	9144	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209635
57	4000	9050	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209635/2
57	4000	9144	90	MW MAT		transparent			silver	1177/50/75	>> 208928
57	4000	9144	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209116
57	4000	9050	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208928/2
57	4000	9050	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209116/2
57	4000	9144	90	SW MAT		transparent			silver	1177/50/75	>> 209321
57	4000	9144	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209505
57	4000	9050	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209321/2
57	4000	9050	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209505/2
57	4000	9144	90	VW MAT		transparent			silver	1177/50/75	>> 209710
57	4000	9144	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209895
57	4000	9050	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209710/2
57	4000	9050	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209895/2
57	4000	9240	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210471

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
57	4000	9150	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210471/2
57	4000	9240	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210044
57	4000	9240	90	SA MAT		transparent			silver	1177/50/75	>> 210556
57	4000	9240	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210730
57	4000	9150	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210556/2
57	4000	9150	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210730/2
57	4000	9240	90	SN MAT		transparent			silver	1177/50/75	>> 210129
57	4000	9240	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210341
57	4000	9451	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 210860
57	4000	9350	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 210860/2
57	4000	9451	90	DAN MAT		transparent			silver	1177/50/75	>> 210945
57	4000	9451	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211133
57	4000	9350	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210945/2
57	4000	9350	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211133/2
57	4000	9500	90	MW		transparent		R2	silver	1177/50/75	>> 838286/2
57	4000	9500	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973970/2
67	4000	10300	90	MW		transparent			silver	1177/50/75	>> 838293
67	4000	10300	90	MW	yes	transparent			silver	1177/50/75	>> 973987
67	4000	10247	90	DAN MAT		transparent			silver	1177/50/75	>> 210952
67	4000	10247	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211140
67	4000	10150	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210952/2
67	4000	10150	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211140/2
67	4000	10300	90	MW		transparent		R2	silver	1177/50/75	>> 838293/2
67	4000	10300	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973987/2
67	4000	9914	90	MW MAT		transparent			silver	1177/50/75	>> 208935
67	4000	9914	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209123
67	4000	9800	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208935/2
67	4000	9800	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209123/2
67	4000	9914	90	SW MAT		transparent			silver	1177/50/75	>> 209338
67	4000	9914	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209512
67	4000	9800	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209338/2
67	4000	9800	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209512/2
67	4000	9914	90	VW MAT		transparent			silver	1177/50/75	>> 209727
67	4000	9914	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209901
67	4000	9800	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209727/2
67	4000	9800	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209901/2
67	4000	10018	90	SA MAT		transparent			silver	1177/50/75	>> 210563
67	4000	10018	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210747

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
67	4000	9900	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210563/2
67	4000	9900	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210747/2
67	4000	10018	90	SN MAT		transparent			silver	1177/50/75	>> 210174
67	4000	10018	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210358
71	4000	11800	90	MW		transparent			silver	1177/50/75	>> 838309
71	4000	11800	90	MW	yes	transparent			silver	1177/50/75	>> 973994
71	4000	11358	90	MW MAT		transparent			silver	1177/50/75	>> 208942
71	4000	11358	90	MW MAT	yes	transparent			silver	1177/50/75	>> 209130
71	4000	11250	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208942/2
71	4000	11250	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 209130/2
71	4000	11358	90	SW MAT		transparent			silver	1177/50/75	>> 209345
71	4000	11358	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209529
71	4000	11250	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209345/2
71	4000	11250	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209529/2
71	4000	11358	90	VW MAT		transparent			silver	1177/50/75	>> 209734
71	4000	11358	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209918
71	4000	11250	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209734/2
71	4000	11250	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209918/2
71	4000	11477	90	SA MAT		transparent			silver	1177/50/75	>> 210570
71	4000	11477	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210754
71	4000	11350	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210570/2
71	4000	11350	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210754/2
71	4000	11477	90	SN MAT		transparent			silver	1177/50/75	>> 210181
71	4000	11477	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210365
71	4000	11739	90	DAN MAT		transparent			silver	1177/50/75	>> 210969
71	4000	11739	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 211157
71	4000	11600	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210969/2
71	4000	11600	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 211157/2
71	4000	11800	90	MW		transparent		R2	silver	1177/50/75	>> 838309/2
71	4000	11800	90	MW	yes	transparent		R2	silver	1177/50/75	>> 973994/2
80	4000	13300	90	MW		transparent			silver	1177/50/75	>> 838316
80	4000	13300	90	MW	yes	transparent			silver	1177/50/75	>> 838019
80	4000	12802	90	MW MAT		transparent			silver	1177/50/75	>> 208959
80	4000	12802	90	MW MAT	yes	transparent			silver	1177/50/75	>> 208850
80	4000	12650	90	MW MAT		transparent		R2	silver	1177/50/75	>> 208959/2
80	4000	12650	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 208850/2
80	4000	12802	90	SW MAT		transparent			silver	1177/50/75	>> 209352
80	4000	12802	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209253

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
80	4000	12650	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209352/2
80	4000	12650	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209253/2
80	4000	12802	90	VW MAT		transparent			silver	1177/50/75	>> 209741
80	4000	12802	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209642
80	4000	12650	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209741/2
80	4000	12650	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209642/2
80	4000	12936	90	SA MAT		transparent			silver	1177/50/75	>> 210587
80	4000	12936	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210488
80	4000	12800	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210587/2
80	4000	12800	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210488/2
80	4000	12936	90	SN MAT		transparent			silver	1177/50/75	>> 210198
80	4000	12936	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210051
80	4000	13232	90	DAN MAT		transparent			silver	1177/50/75	>> 210976
80	4000	13232	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 210877
80	4000	13100	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 210976/2
80	4000	13100	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 210877/2
80	4000	13300	90	MW		transparent		R2	silver	1177/50/75	>> 838316/2
80	4000	13300	90	MW	yes	transparent		R2	silver	1177/50/75	>> 838019/2
91	4000	14900	90	MW		transparent			silver	1177/50/75	>> 944970
91	4000	14900	90	MW	yes	transparent			silver	1177/50/75	>> 838026
91	4000	14342	90	MW MAT		transparent			silver	1177/50/75	>> 209017
91	4000	14342	90	MW MAT	yes	transparent			silver	1177/50/75	>> 208867
91	4000	14200	90	MW MAT		transparent		R2	silver	1177/50/75	>> 209017/2
91	4000	14200	90	MW MAT	yes	transparent		R2	silver	1177/50/75	>> 208867/2
91	4000	14342	90	SW MAT		transparent			silver	1177/50/75	>> 209406
91	4000	14342	90	SW MAT	yes	transparent			silver	1177/50/75	>> 209260
91	4000	14200	90	SW MAT		transparent		R2	silver	1177/50/75	>> 209406/2
91	4000	14200	90	SW MAT	yes	transparent		R2	silver	1177/50/75	>> 209260/2
91	4000	14342	90	VW MAT		transparent			silver	1177/50/75	>> 209796
91	4000	14342	90	VW MAT	yes	transparent			silver	1177/50/75	>> 209659
91	4000	14200	90	VW MAT		transparent		R2	silver	1177/50/75	>> 209796/2
91	4000	14200	90	VW MAT	yes	transparent		R2	silver	1177/50/75	>> 209659/2
91	4000	14492	90	SA MAT		transparent			silver	1177/50/75	>> 210631
91	4000	14492	90	SA MAT	yes	transparent			silver	1177/50/75	>> 210495
91	4000	14350	90	SA MAT		transparent		R2	silver	1177/50/75	>> 210631/2
91	4000	14350	90	SA MAT	yes	transparent		R2	silver	1177/50/75	>> 210495/2
91	4000	14492	90	SN MAT		transparent			silver	1177/50/75	>> 210242
91	4000	14492	90	SN MAT	yes	transparent			silver	1177/50/75	>> 210068

INDUSTRY SLIM LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
91	4000	14823	90	DAN MAT		transparent			silver	1177/50/75	>> 211034
91	4000	14823	90	DAN MAT	yes	transparent			silver	1177/50/75	>> 210884
91	4000	14700	90	DAN MAT		transparent		R2	silver	1177/50/75	>> 211034/2
91	4000	14700	90	DAN MAT	yes	transparent		R2	silver	1177/50/75	>> 210884/2
91	4000	14900	90	MW	yes	transparent		R2	silver	1177/50/75	>> 838026/2

INDUSTRY SLIM LED asymmetric°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
22	4000	3350	asymmetric	SA		matrix led			grey	590/50/75	>> 827259
22	4000	3350	asymmetric	SA	yes	matrix led			grey	590/50/75	>> 827266
22	4000	3350	asymmetric	SA		matrix led		R2	grey	590/50/75	>> 827259/2
22	4000	3350	asymmetric	SA	yes	matrix led		R2	grey	590/50/75	>> 827266/2
27	4000	4000	asymmetric	SA		matrix led			grey	590/50/75	>> 827273
27	4000	4000	asymmetric	SA	yes	matrix led			grey	590/50/75	>> 827280
27	4000	4000	asymmetric	SA		matrix led		R2	grey	590/50/75	>> 827273/2
27	4000	4000	asymmetric	SA	yes	matrix led		R2	grey	590/50/75	>> 827280/2
33	4000	4700	asymmetric	SA		matrix led			grey	590/50/75	>> 827297
33	4000	4700	asymmetric	SA	yes	matrix led			grey	590/50/75	>> 827303
33	4000	4700	asymmetric	SA		matrix led		R2	grey	590/50/75	>> 827297/2
33	4000	4700	asymmetric	SA	yes	matrix led		R2	grey	590/50/75	>> 827303/2
37	4000	5300	asymmetric	SA		matrix led			grey	590/50/75	>> 827310
37	4000	5300	asymmetric	SA	yes	matrix led			grey	590/50/75	>> 827327
37	4000	5300	asymmetric	SA		matrix led		R2	grey	590/50/75	>> 827310/2
37	4000	5300	asymmetric	SA	yes	matrix led		R2	grey	590/50/75	>> 827327/2

INDUSTRY SLIM LED butterfly°

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index

INDUSTRY SLIM LED


GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Light distribution type	DIMM DALI	Diffuser type	Through wiring	Version	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
22	4000	3300	butterfly	DAN		matrix led			grey	590/50/75	>> 827099
22	4000	3300	butterfly	DAN	yes	matrix led			grey	590/50/75	>> 827105
22	4000	3300	butterfly	DAN		matrix led		R2	grey	590/50/75	>> 827099/2
22	4000	3300	butterfly	DAN	yes	matrix led		R2	grey	590/50/75	>> 827105/2
27	4000	3900	butterfly	DAN		matrix led			grey	590/50/75	>> 827112
27	4000	3900	butterfly	DAN	yes	matrix led			grey	590/50/75	>> 827129
27	4000	3900	butterfly	DAN		matrix led		R2	grey	590/50/75	>> 827112/2
27	4000	3900	butterfly	DAN	yes	matrix led		R2	grey	590/50/75	>> 827129/2
33	4000	4650	butterfly	DAN		matrix led			grey	590/50/75	>> 827136
33	4000	4650	butterfly	DAN	yes	matrix led			grey	590/50/75	>> 827143
33	4000	4650	butterfly	DAN		matrix led		R2	grey	590/50/75	>> 827136/2
33	4000	4650	butterfly	DAN	yes	matrix led		R2	grey	590/50/75	>> 827143/2
37	4000	5200	butterfly	DAN		matrix led			grey	590/50/75	>> 827150
37	4000	5200	butterfly	DAN	yes	matrix led			grey	590/50/75	>> 827167
37	4000	5200	butterfly	DAN		matrix led		R2	grey	590/50/75	>> 827150/2
37	4000	5200	butterfly	DAN	yes	matrix led		R2	grey	590/50/75	>> 827167/2


INDUSTRY SLIM LED

GENERAL CARD


LUMINOUS INTENSITY DISTRIB. CURVE




105°




105D




120°




46 x 117°



80 x 100°



MW




SW

INDUSTRY SLIM LED

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: max 45839

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

The luminaire has been fitted with new luminous distributions:

SW - a standard wide lens (80D conventional angle) with a wide range of applications in commercial buildings, industrial halls and even - due to its low glare index UGR

MW - medium wide lens (90D conventional angle) with a wide range of applications in commercial buildings, industrial halls and even - due to the low glare UGR

VW - very wide lens (105D conventional angle) with wide application in open spaces and low warehouses. It provides high luminous efficacy and helps meet the most stringent requirements of EN 12464-1 in terms of glare index (UGR<22, UGR<25), illuminance and high uniformity when the system is installed in low spaces. Particularly recommended for rooms where luminaires are mounted at a height of 2.5-5m.