

MAGNUM FUTURE LED XL

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|---|----------------------|
| Ingress protection: | IP44; IP54 |
| Impact resistance: | IK10 |
| Rated power of the luminaire [W]*: | 50.00; 78.00; 105.00 |
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 6500; 11000; 14055 |
| Supply voltage [V]: | 220-240; 24; 42-48 |
| Energy efficiency class: | C; D |
| Electrical protection class: | I; II; III |
| Colour of the body: | grey |
| Diffuser material: | PC |
| Diffuser type: | MAT; frozen |
| Dimensions (H/W/T/S) [mm]: | 300/480/75; |
| Material of the body: | PP |

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

A rubber cable H07RN-F 3x1,5 mm² (5 m) comes as standard.

APPLICATION

With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and maximum degree of impact resistance are especially important for lighting construction sites or for the work of services intervening in various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. The multi-position arm and numerous accessories provide a wide range of mounting options so as to precisely direct the light beam, leaving the worker's hands free. Its small size and light weight make it easy to use in workshops, car showrooms, to illuminate the workplace in industrial halls or finishing work.

MAGNUM FUTURE LED XL

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

MAGNUM FUTURE LED XL 220-240V 78W i 105W

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Plug type | Socket type | Index |
|-----------------------------------|------------------------|---------------------|---------------|------------|-------------|---------------------------------|
| 105 | 4000 | 14055 | MAT | UNI-SCHUKO | | >> 244544 |
| 105 | 4000 | 14055 | MAT | UNI-SCHUKO | DK | >> 244537 |
| 105 | 4000 | 14055 | MAT | UNI-SCHUKO | PL-FR | >> 244568 |
| 105 | 4000 | 14055 | MAT | UNI-SCHUKO | PL-FR | >> 244575 |
| 105 | 4000 | 14055 | MAT | UNI-SCHUKO | SCHUKO | >> 244551 |
| 105 | 4000 | 14055 | MAT | UNI-SCHUKO | SCHUKO | >> 244582 |
| 78 | 4000 | 11000 | frozen | UNI-SCHUKO | | >> 248863 |
| 78 | 4000 | 11000 | frozen | UNI-SCHUKO | SCHUKO | >> 248887 |
| 78 | 4000 | 11000 | frozen | DK | DK | >> 248917 |
| 78 | 4000 | 11000 | frozen | UNI-SCHUKO | PL-FR | >> 248894 |
| 78 | 4000 | 11000 | frozen | UNI-SCHUKO | PL-FR | >> 248955 |
| 78 | 4000 | 11000 | frozen | UNI-SCHUKO | SCHUKO | >> 248931 |

MAGNUM FUTURE LED XL 220-240V 50W

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Plug type | Socket type | Index |
|-----------------------------------|------------------------|---------------------|---------------|------------|-------------|---------------------------------|
| 50 | 4000 | 6500 | frozen | CH | | >> 247415 |
| 50 | 4000 | 6500 | frozen | DK | | >> 247422 |
| 50 | 4000 | 6500 | frozen | UK | | >> 247439 |
| 50 | 4000 | 6500 | frozen | CH | CH | >> 247385 |
| 50 | 4000 | 6500 | frozen | CH | CH | >> 247477 |
| 50 | 4000 | 6500 | frozen | DK | DK | >> 247330 |
| 50 | 4000 | 6500 | frozen | DK | DK | >> 247446 |
| 50 | 4000 | 6500 | frozen | UNI-SCHUKO | PL-FR | >> 247354 |
| 50 | 4000 | 6500 | frozen | UNI-SCHUKO | PL-FR | >> 247460 |
| 50 | 4000 | 6500 | frozen | UNI-SCHUKO | SCHUKO | >> 247347 |
| 50 | 4000 | 6500 | frozen | UNI-SCHUKO | SCHUKO | >> 247453 |
| 50 | 4000 | 6500 | frozen | UNI-SCHUKO | | >> 247408 |

MAGNUM FUTURE LED XL 50W 24V

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Plug type | Socket type | Index |
|-----------------------------------|------------------------|---------------------|---------------|-----------|-------------|---------------------------------|
| 50 | 4000 | 6500 | frozen | CEE | | >> 248207 |
| 50 | 4000 | 6500 | frozen | TRAFO | | >> 248214 |
| 50 | 4000 | 6500 | frozen | CEE | CEE (2-PIN) | >> 248221 |

MAGNUM FUTURE LED XL

GENERAL CARD

MAGNUM FUTURE LED XL 50W 42-48V

| Rated power of the luminaire [W]* | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Plug type | Socket type | Index |
|-----------------------------------|------------------------|---------------------|---------------|-----------|-------------|---------------------------------|
| 50 | 4000 | 6500 | frozen | CEE | | >> 248238 |
| 50 | 4000 | 6500 | frozen | CEE | CEE (2-PIN) | >> 248245 |

Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: max 179/2018



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl