


BARIS SQUARE 52 LED

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	32.00 - 145.00
Luminous flux [lm]*:	3850 - 18575
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000; 4000
Color rendering index (Ra) >:	80
Diffuser type:	OPAL; transparent
Diffuser colour:	milky; transparent
Colour of the body:	black; grey; white
Impact resistance:	IK06
Ingress protection:	IP40

CHARACTERISTICS

Baris Square 52 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in four sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. The unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings or where the requirement is IP40 protection.

BARIS SQUARE 52 LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

BARIS SQUARE 52 LED 1173/1173/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
65	7825	3000	transparent	black	1173/1173/69	>> 938818
65	7825	3000	transparent	black	1173/1173/69	>> 939013
65	7950	3000	milky	black	1173/1173/69	>> 939112
65	7950	3000	milky	black	1173/1173/69	>> 938917
65	8200	4000	transparent	black	1173/1173/69	>> 938023
65	8200	4000	transparent	black	1173/1173/69	>> 938610
65	8325	4000	milky	grey	1173/1173/69	>> 939310
65	8325	4000	milky	black	1173/1173/69	>> 938245
65	8325	4000	milky	white	1173/1173/69	>> 939303
65	8325	4000	milky	black	1173/1173/69	>> 938719
116	13950	3000	transparent	black	1173/1173/69	>> 938863
116	13950	3000	transparent	black	1173/1173/69	>> 939068
116	14200	3000	milky	black	1173/1173/69	>> 938993
116	14200	3000	milky	black	1173/1173/69	>> 939198
116	14600	4000	transparent	black	1173/1173/69	>> 938139
116	14600	4000	transparent	black	1173/1173/69	>> 938665
116	14850	4000	milky	grey	1173/1173/69	>> 939297
116	14850	4000	milky	black	1173/1173/69	>> 938597
116	14850	4000	transparent	white	1173/1173/69	>> 939280
116	14850	4000	milky	black	1173/1173/69	>> 938795

BARIS SQUARE 52 LED 1453/1453/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
80	9625	3000	transparent	black	1453/1453/69	>> 938825
80	9625	3000	transparent	black	1453/1453/69	>> 939020
80	9800	3000	milky	black	1453/1453/69	>> 938924
80	9800	3000	milky	black	1453/1453/69	>> 939129
80	10075	4000	transparent	black	1453/1453/69	>> 938030
80	10075	4000	transparent	black	1453/1453/69	>> 938627
80	10250	4000	milky	black	1453/1453/69	>> 938726
80	10250	4000	transparent	white	1453/1453/69	>> 939426
80	10250	4000	milky	black	1453/1453/69	>> 938252
80	10250	4000	milky	grey	1453/1453/69	>> 939433
145	17425	3000	transparent	black	1453/1453/69	>> 938870

BARIS SQUARE 52 LED

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
145	17425	3000	transparent	black	1453/1453/69	>> 939075
145	17750	3000	milky	black	1453/1453/69	>> 939174
145	17750	3000	milky	black	1453/1453/69	>> 938979
145	18250	4000	transparent	black	1453/1453/69	>> 938672
145	18250	4000	transparent	black	1453/1453/69	>> 938146
145	18575	4000	milky	grey	1453/1453/69	>> 939419
145	18575	4000	milky	black	1453/1453/69	>> 938573
145	18575	4000	milky	black	1453/1453/69	>> 938771
145	18575	4000	milky	white	1453/1453/69	>> 939402

BARIS SQUARE 52 LED 613/613/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
32	3850	3000	transparent	black	613/613/69	>> 938450
32	3850	3000	transparent	black	613/613/69	>> 938474
32	3925	3000	milky	black	613/613/69	>> 938481
32	3925	3000	milky	black	613/613/69	>> 938467
32	4050	4000	transparent	black	613/613/69	>> 938412
32	4050	4000	transparent	black	613/613/69	>> 938009
32	4100	4000	milky	black	613/613/69	>> 938429
32	4100	4000	milky	black	613/613/69	>> 938221
56	6750	3000	transparent	black	613/613/69	>> 938399
56	6750	3000	transparent	black	613/613/69	>> 938382
56	6850	3000	milky	black	613/613/69	>> 938375
56	6850	3000	milky	black	613/613/69	>> 938368
56	7050	4000	transparent	black	613/613/69	>> 938115
56	7050	4000	transparent	black	613/613/69	>> 938283
56	7175	4000	milky	black	613/613/69	>> 938290
56	7175	4000	milky	black	613/613/69	>> 938269
56	7175	4000	transparent	white	613/613/69	>> 939204
56	7175	4000	milky	grey	613/613/69	>> 939211

BARIS SQUARE 52 LED 893/893/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
48	5775	3000	transparent	black	893/893/69	>> 939006
48	5775	3000	transparent	black	893/893/69	>> 938801
48	5875	3000	milky	black	893/893/69	>> 939105
48	5875	3000	milky	black	893/893/69	>> 938900
48	6050	4000	transparent	black	893/893/69	>> 938603
48	6050	4000	transparent	black	893/893/69	>> 938016
48	6150	4000	milky	black	893/893/69	>> 938238

BARIS SQUARE 52 LED

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
48	6150	4000	milky	grey	893/893/69	>> 939396
48	6150	4000	transparent	white	893/893/69	>> 939389
48	6150	4000	milky	black	893/893/69	>> 938702
86	10350	3000	transparent	black	893/893/69	>> 939051
86	10350	3000	transparent	black	893/893/69	>> 938856
86	10525	3000	milky	black	893/893/69	>> 939181
86	10525	3000	milky	black	893/893/69	>> 938986
86	10825	4000	transparent	black	893/893/69	>> 938658
86	10825	4000	transparent	black	893/893/69	>> 938122
86	11025	4000	milky	black	893/893/69	>> 938788
86	11025	4000	milky	white	893/893/69	>> 939365
86	11025	4000	milky	black	893/893/69	>> 938580
86	11025	4000	milky	grey	893/893/69	>> 939372

Card creation date: 21 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 210/2023

