

# BARIS SQUARE 52 LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Rated power of the luminaire [W]*:</b>	32.00 - 145.00
<b>Luminous flux [lm]*:</b>	3100 - 15100
<b>Supply voltage [V]:</b>	220-240
<b>Frequency [Hz]:</b>	50-60
<b>Energy efficiency class:</b>	E; F
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>Diffuser type:</b>	OPAL; clear
<b>Diffuser colour:</b>	milky; prismatic
<b>Colour of the body:</b>	black; grey; white
<b>Impact resistance:</b>	IK06
<b>Ingress protection:</b>	IP40

## CHARACTERISTICS

Baris Square 52 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in four sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

## APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. The unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings or where the requirement is IP40 protection.

# BARIS SQUARE 52 LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### BARIS SQUARE 52 LED 1173/1173/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
65	6300	3000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 939112</a>
65	6300	3000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 938917</a>
65	6650	3000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 939013</a>
65	6650	3000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 938818</a>
65	6800	4000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 938719</a>
65	6800	4000	milky	white	1173/1173/69	<a href="#">&gt;&gt; 939303</a>
65	6800	4000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 938245</a>
65	6800	4000	milky	grey	1173/1173/69	<a href="#">&gt;&gt; 939310</a>
65	7150	4000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 938610</a>
65	7150	4000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 938023</a>
116	10800	3000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 939068</a>
116	10800	3000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 938863</a>
116	11250	3000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 939198</a>
116	11250	3000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 938993</a>
116	11600	4000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 938665</a>
116	11600	4000	prismatic	black	1173/1173/69	<a href="#">&gt;&gt; 938139</a>
116	12100	4000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 938795</a>
116	12100	4000	prismatic	white	1173/1173/69	<a href="#">&gt;&gt; 939280</a>
116	12100	4000	milky	black	1173/1173/69	<a href="#">&gt;&gt; 938597</a>
116	12100	4000	milky	grey	1173/1173/69	<a href="#">&gt;&gt; 939297</a>

### BARIS SQUARE 52 LED 1453/1453/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
80	7750	3000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 939129</a>
80	7750	3000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 938924</a>
80	8250	3000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 939020</a>
80	8250	3000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 938825</a>
80	8350	4000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 938726</a>
80	8350	4000	prismatic	white	1453/1453/69	<a href="#">&gt;&gt; 939426</a>
80	8350	4000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 938252</a>
80	8350	4000	milky	grey	1453/1453/69	<a href="#">&gt;&gt; 939433</a>
80	8850	4000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 938627</a>
80	8850	4000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 938030</a>
145	13500	3000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 939174</a>

# BARIS SQUARE 52 LED

## GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
145	13500	3000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 938979</a>
145	14050	3000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 939075</a>
145	14050	3000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 938870</a>
145	14500	4000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 938771</a>
145	14500	4000	milky	white	1453/1453/69	<a href="#">&gt;&gt; 939402</a>
145	14500	4000	milky	black	1453/1453/69	<a href="#">&gt;&gt; 938573</a>
145	14500	4000	milky	grey	1453/1453/69	<a href="#">&gt;&gt; 939419</a>
145	15100	4000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 938672</a>
145	15100	4000	prismatic	black	1453/1453/69	<a href="#">&gt;&gt; 938146</a>

## BARIS SQUARE 52 LED 613/613/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
32	3100	3000	milky	black	613/613/69	<a href="#">&gt;&gt; 938481</a>
32	3100	3000	milky	black	613/613/69	<a href="#">&gt;&gt; 938467</a>
32	3300	3000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938474</a>
32	3300	3000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938450</a>
32	3350	4000	milky	black	613/613/69	<a href="#">&gt;&gt; 938429</a>
32	3350	4000	milky	black	613/613/69	<a href="#">&gt;&gt; 938221</a>
32	3550	4000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938412</a>
32	3550	4000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938009</a>
56	5200	3000	milky	black	613/613/69	<a href="#">&gt;&gt; 938375</a>
56	5200	3000	milky	black	613/613/69	<a href="#">&gt;&gt; 938368</a>
56	5450	3000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938399</a>
56	5450	3000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938382</a>
56	5600	4000	milky	black	613/613/69	<a href="#">&gt;&gt; 938290</a>
56	5600	4000	prismatic	white	613/613/69	<a href="#">&gt;&gt; 939204</a>
56	5600	4000	milky	black	613/613/69	<a href="#">&gt;&gt; 938269</a>
56	5600	4000	milky	grey	613/613/69	<a href="#">&gt;&gt; 939211</a>
56	5850	4000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938283</a>
56	5850	4000	prismatic	black	613/613/69	<a href="#">&gt;&gt; 938115</a>

## BARIS SQUARE 52 LED 893/893/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
48	4650	3000	milky	black	893/893/69	<a href="#">&gt;&gt; 939105</a>
48	4650	3000	milky	black	893/893/69	<a href="#">&gt;&gt; 938900</a>
48	4950	3000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 939006</a>
48	4950	3000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 938801</a>
48	5000	4000	milky	black	893/893/69	<a href="#">&gt;&gt; 938702</a>
48	5000	4000	prismatic	white	893/893/69	<a href="#">&gt;&gt; 939389</a>
48	5000	4000	milky	black	893/893/69	<a href="#">&gt;&gt; 938238</a>

# BARIS SQUARE 52 LED

## GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
48	5000	4000	milky	grey	893/893/69	<a href="#">&gt;&gt; 939396</a>
48	5300	4000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 938603</a>
48	5300	4000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 938016</a>
86	8000	3000	milky	black	893/893/69	<a href="#">&gt;&gt; 939181</a>
86	8000	3000	milky	black	893/893/69	<a href="#">&gt;&gt; 938986</a>
86	8350	3000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 939051</a>
86	8350	3000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 938856</a>
86	8600	4000	milky	black	893/893/69	<a href="#">&gt;&gt; 938788</a>
86	8600	4000	milky	white	893/893/69	<a href="#">&gt;&gt; 939365</a>
86	8600	4000	milky	black	893/893/69	<a href="#">&gt;&gt; 938580</a>
86	8600	4000	milky	grey	893/893/69	<a href="#">&gt;&gt; 939372</a>
86	9000	4000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 938658</a>
86	9000	4000	prismatic	black	893/893/69	<a href="#">&gt;&gt; 938122</a>

Card creation date: 22 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 210/2023