


BARIS SQUARE 52 LED

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	32.00 - 145.00
Luminous flux [lm]*:	3100 - 15100
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Energy efficiency class:	E; F
Electrical protection class:	I
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
Diffuser type:	OPAL; clear
Diffuser colour:	milky; prismatic
Colour of the body:	black; grey; white
Impact resistance:	IK06
Ingress protection:	IP40

CHARACTERISTICS

Baris Square 52 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in four sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. The unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings or where the requirement is IP40 protection.

BARIS SQUARE 52 LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

BARIS SQUARE 52 LED 1173/1173/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
65	6300	3000	milky	black	1173/1173/69	>> 939112
65	6300	3000	milky	black	1173/1173/69	>> 938917
65	6650	3000	prismatic	black	1173/1173/69	>> 939013
65	6650	3000	prismatic	black	1173/1173/69	>> 938818
65	6800	4000	milky	black	1173/1173/69	>> 938719
65	6800	4000	milky	white	1173/1173/69	>> 939303
65	6800	4000	milky	black	1173/1173/69	>> 938245
65	6800	4000	milky	grey	1173/1173/69	>> 939310
65	7150	4000	prismatic	black	1173/1173/69	>> 938610
65	7150	4000	prismatic	black	1173/1173/69	>> 938023
116	10800	3000	prismatic	black	1173/1173/69	>> 939068
116	10800	3000	prismatic	black	1173/1173/69	>> 938863
116	11250	3000	milky	black	1173/1173/69	>> 939198
116	11250	3000	milky	black	1173/1173/69	>> 938993
116	11600	4000	prismatic	black	1173/1173/69	>> 938665
116	11600	4000	prismatic	black	1173/1173/69	>> 938139
116	12100	4000	milky	black	1173/1173/69	>> 938795
116	12100	4000	prismatic	white	1173/1173/69	>> 939280
116	12100	4000	milky	black	1173/1173/69	>> 938597
116	12100	4000	milky	grey	1173/1173/69	>> 939297

BARIS SQUARE 52 LED 1453/1453/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
80	7750	3000	milky	black	1453/1453/69	>> 939129
80	7750	3000	milky	black	1453/1453/69	>> 938924
80	8250	3000	prismatic	black	1453/1453/69	>> 939020
80	8250	3000	prismatic	black	1453/1453/69	>> 938825
80	8350	4000	milky	black	1453/1453/69	>> 938726
80	8350	4000	prismatic	white	1453/1453/69	>> 939426
80	8350	4000	milky	black	1453/1453/69	>> 938252
80	8350	4000	milky	grey	1453/1453/69	>> 939433
80	8850	4000	prismatic	black	1453/1453/69	>> 938627
80	8850	4000	prismatic	black	1453/1453/69	>> 938030
145	13500	3000	milky	black	1453/1453/69	>> 939174

BARIS SQUARE 52 LED

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
145	13500	3000	milky	black	1453/1453/69	>> 938979
145	14050	3000	prismatic	black	1453/1453/69	>> 939075
145	14050	3000	prismatic	black	1453/1453/69	>> 938870
145	14500	4000	milky	black	1453/1453/69	>> 938771
145	14500	4000	milky	white	1453/1453/69	>> 939402
145	14500	4000	milky	black	1453/1453/69	>> 938573
145	14500	4000	milky	grey	1453/1453/69	>> 939419
145	15100	4000	prismatic	black	1453/1453/69	>> 938672
145	15100	4000	prismatic	black	1453/1453/69	>> 938146

BARIS SQUARE 52 LED 613/613/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
32	3100	3000	milky	black	613/613/69	>> 938481
32	3100	3000	milky	black	613/613/69	>> 938467
32	3300	3000	prismatic	black	613/613/69	>> 938474
32	3300	3000	prismatic	black	613/613/69	>> 938450
32	3350	4000	milky	black	613/613/69	>> 938429
32	3350	4000	milky	black	613/613/69	>> 938221
32	3550	4000	prismatic	black	613/613/69	>> 938412
32	3550	4000	prismatic	black	613/613/69	>> 938009
56	5200	3000	milky	black	613/613/69	>> 938375
56	5200	3000	milky	black	613/613/69	>> 938368
56	5450	3000	prismatic	black	613/613/69	>> 938399
56	5450	3000	prismatic	black	613/613/69	>> 938382
56	5600	4000	milky	black	613/613/69	>> 938290
56	5600	4000	prismatic	white	613/613/69	>> 939204
56	5600	4000	milky	black	613/613/69	>> 938269
56	5600	4000	milky	grey	613/613/69	>> 939211
56	5850	4000	prismatic	black	613/613/69	>> 938283
56	5850	4000	prismatic	black	613/613/69	>> 938115

BARIS SQUARE 52 LED 893/893/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
48	4650	3000	milky	black	893/893/69	>> 939105
48	4650	3000	milky	black	893/893/69	>> 938900
48	4950	3000	prismatic	black	893/893/69	>> 939006
48	4950	3000	prismatic	black	893/893/69	>> 938801
48	5000	4000	milky	black	893/893/69	>> 938702
48	5000	4000	prismatic	white	893/893/69	>> 939389
48	5000	4000	milky	black	893/893/69	>> 938238

BARIS SQUARE 52 LED

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
48	5000	4000	milky	grey	893/893/69	>> 939396
48	5300	4000	prismatic	black	893/893/69	>> 938603
48	5300	4000	prismatic	black	893/893/69	>> 938016
86	8000	3000	milky	black	893/893/69	>> 939181
86	8000	3000	milky	black	893/893/69	>> 938986
86	8350	3000	prismatic	black	893/893/69	>> 939051
86	8350	3000	prismatic	black	893/893/69	>> 938856
86	8600	4000	milky	black	893/893/69	>> 938788
86	8600	4000	milky	white	893/893/69	>> 939365
86	8600	4000	milky	black	893/893/69	>> 938580
86	8600	4000	milky	grey	893/893/69	>> 939372
86	9000	4000	prismatic	black	893/893/69	>> 938658
86	9000	4000	prismatic	black	893/893/69	>> 938122

Card creation date: 13 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 210/2023

