

# BARIS SQUARE 40 LED

## GENERAL CARD



### TECHNICAL PARAMETERS

<b>Rated power of the luminaire [W]*:</b>	32.00 - 116.00
<b>Luminous flux [lm]*:</b>	4275 - 16450
<b>Supply voltage [V]:</b>	220-240
<b>Frequency [Hz]:</b>	50-60
<b>Energy efficiency class:</b>	C; D
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	3000; 4000
<b>Diffuser type:</b>	OPAL; transparent
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black; grey; white
<b>Impact resistance:</b>	IK06
<b>Ingress protection:</b>	IP20

### CHARACTERISTICS

Baris Square 40 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in three sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

### APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. Unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings.

# BARIS SQUARE 40 LED

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### Baris SQUARE 40 LED 1162/1162/52mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
65	8675	3000	milky	black		1162/1162/52	<a href="#">&gt;&gt; 938962</a>
65	8675	3000	milky	black	yes	1162/1162/52	<a href="#">&gt;&gt; 939167</a>
65	8850	3000	transparent	black		1162/1162/52	<a href="#">&gt;&gt; 938849</a>
65	8850	3000	transparent	black	yes	1162/1162/52	<a href="#">&gt;&gt; 939044</a>
65	9125	4000	milky	grey		1162/1162/52	<a href="#">&gt;&gt; 939273</a>
65	9125	4000	milky	black		1162/1162/52	<a href="#">&gt;&gt; 938566</a>
65	9125	4000	milky	white		1162/1162/52	<a href="#">&gt;&gt; 939266</a>
65	9125	4000	milky	black	yes	1162/1162/52	<a href="#">&gt;&gt; 938764</a>
65	9225	4000	transparent	black		1162/1162/52	<a href="#">&gt;&gt; 938108</a>
65	9225	4000	transparent	black	yes	1162/1162/52	<a href="#">&gt;&gt; 938641</a>
116	15475	3000	milky	black	yes	1162/1162/52	<a href="#">&gt;&gt; 939150</a>
116	15475	3000	milky	black		1162/1162/52	<a href="#">&gt;&gt; 938955</a>
116	15800	3000	transparent	black		1162/1162/52	<a href="#">&gt;&gt; 938894</a>
116	15800	3000	transparent	black	yes	1162/1162/52	<a href="#">&gt;&gt; 939099</a>
116	16275	4000	milky	grey		1162/1162/52	<a href="#">&gt;&gt; 939259</a>
116	16275	4000	milky	black		1162/1162/52	<a href="#">&gt;&gt; 938559</a>
116	16275	4000	milky	white		1162/1162/52	<a href="#">&gt;&gt; 939242</a>
116	16275	4000	milky	black	yes	1162/1162/52	<a href="#">&gt;&gt; 938757</a>
116	16450	4000	transparent	black	yes	1162/1162/52	<a href="#">&gt;&gt; 938696</a>
116	16450	4000	transparent	black		1162/1162/52	<a href="#">&gt;&gt; 938214</a>

### Baris SQUARE 40 LED 602/602/52mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
32	4275	3000	milky	black	yes	602/602/52	<a href="#">&gt;&gt; 938528</a>
32	4275	3000	milky	black		602/602/52	<a href="#">&gt;&gt; 938504</a>
32	4375	3000	transparent	black	yes	602/602/52	<a href="#">&gt;&gt; 938511</a>
32	4375	3000	transparent	black		602/602/52	<a href="#">&gt;&gt; 938498</a>
32	4500	4000	milky	black	yes	602/602/52	<a href="#">&gt;&gt; 938443</a>
32	4500	4000	milky	black		602/602/52	<a href="#">&gt;&gt; 938405</a>
32	4550	4000	transparent	black	yes	602/602/52	<a href="#">&gt;&gt; 938436</a>
32	4550	4000	transparent	black		602/602/52	<a href="#">&gt;&gt; 938085</a>
56	7475	4000	milky	black		602/602/52	<a href="#">&gt;&gt; 938337</a>
56	7475	3000	milky	black	yes	602/602/52	<a href="#">&gt;&gt; 938351</a>

# BARIS SQUARE 40 LED

## GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
56	7625	3000	transparent	black	yes	602/602/52	<a href="#">&gt;&gt; 938344</a>
56	7625	4000	transparent	black		602/602/52	<a href="#">&gt;&gt; 938320</a>
56	7875	4000	milky	black	yes	602/602/52	<a href="#">&gt;&gt; 938313</a>
56	7875	4000	milky	white		602/602/52	<a href="#">&gt;&gt; 939228</a>
56	7875	4000	milky	black		602/602/52	<a href="#">&gt;&gt; 938276</a>
56	7875	4000	milky	grey		602/602/52	<a href="#">&gt;&gt; 939235</a>
56	7950	4000	transparent	black	yes	602/602/52	<a href="#">&gt;&gt; 938306</a>
56	7950	4000	transparent	black		602/602/52	<a href="#">&gt;&gt; 938191</a>

## Baris SQUARE 40 LED 882/882/52mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser colour	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
48	6400	3000	milky	black	yes	882/882/52	<a href="#">&gt;&gt; 939143</a>
48	6400	3000	milky	black		882/882/52	<a href="#">&gt;&gt; 938948</a>
48	6550	3000	transparent	black	yes	882/882/52	<a href="#">&gt;&gt; 939037</a>
48	6550	3000	transparent	black		882/882/52	<a href="#">&gt;&gt; 938832</a>
48	6750	4000	milky	white		882/882/52	<a href="#">&gt;&gt; 939341</a>
48	6750	4000	milky	grey		882/882/52	<a href="#">&gt;&gt; 939358</a>
48	6750	4000	milky	black		882/882/52	<a href="#">&gt;&gt; 938542</a>
48	6750	4000	milky	black	yes	882/882/52	<a href="#">&gt;&gt; 938740</a>
48	6800	4000	transparent	black	yes	882/882/52	<a href="#">&gt;&gt; 938634</a>
48	6800	4000	transparent	black		882/882/52	<a href="#">&gt;&gt; 938092</a>
86	11475	3000	milky	black	yes	882/882/52	<a href="#">&gt;&gt; 939136</a>
86	11475	3000	milky	black		882/882/52	<a href="#">&gt;&gt; 938931</a>
86	11725	3000	transparent	black	yes	882/882/52	<a href="#">&gt;&gt; 939082</a>
86	11725	3000	transparent	black		882/882/52	<a href="#">&gt;&gt; 938887</a>
86	12075	4000	milky	black	yes	882/882/52	<a href="#">&gt;&gt; 938733</a>
86	12075	4000	milky	white		882/882/52	<a href="#">&gt;&gt; 939327</a>
86	12075	4000	milky	black		882/882/52	<a href="#">&gt;&gt; 938535</a>
86	12075	4000	milky	grey		882/882/52	<a href="#">&gt;&gt; 939334</a>
86	12200	4000	transparent	black	yes	882/882/52	<a href="#">&gt;&gt; 938689</a>
86	12200	4000	transparent	black		882/882/52	<a href="#">&gt;&gt; 938207</a>

Card creation date: 21 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 211/2023

