

BARIS SQUARE 40 LED

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|---|--------------------|
| Rated power of the luminaire [W]*: | 32.00 - 116.00 |
| Luminous flux [lm]*: | 4275 - 16450 |
| Supply voltage [V]: | 220-240 |
| Frequency [Hz]: | 50-60 |
| Energy efficiency class: | C; D |
| Electrical protection class: | I |
| Colour temperature [K]: | 3000; 4000 |
| Diffuser type: | OPAL; transparent |
| Material of the body: | aluminium |
| Colour of the body: | black; grey; white |
| Impact resistance: | IK06 |
| Ingress protection: | IP20 |

CHARACTERISTICS

Baris Square 40 Led is a striking pendant lamp. Its classic shape fits perfectly into modern design. The lamp body is made of anodized aluminum profile in gray or aluminum profile painted in white or black (other colors available on request). The lamp is offered with two types of lampshade - prismatic or milky. The availability of the lamp in three sizes allows you to design the distribution of lighting in an individually tailored way. Lamps of different sizes and hung at different lengths can create an unlimited number of lighting compositions in the room.

APPLICATION

The lamp is dedicated for indoor use. It is used as a source of main light in representative rooms, hotels, restaurants, conference rooms. Unique design and energy-saving LED modules also dedicate the lamp for use in modern office buildings.

BARIS SQUARE 40 LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Baris SQUARE 40 LED 1162/1162/52mm

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Colour temperature [K] | Diffuser colour | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|------------------------|-----------------|--------------------|-----------|---------------------------|---------------------------------|
| 65 | 8675 | 3000 | milky | black | | 1162/1162/52 | >> 938962 |
| 65 | 8675 | 3000 | milky | black | yes | 1162/1162/52 | >> 939167 |
| 65 | 8850 | 3000 | transparent | black | | 1162/1162/52 | >> 938849 |
| 65 | 8850 | 3000 | transparent | black | yes | 1162/1162/52 | >> 939044 |
| 65 | 9125 | 4000 | milky | grey | | 1162/1162/52 | >> 939273 |
| 65 | 9125 | 4000 | milky | black | | 1162/1162/52 | >> 938566 |
| 65 | 9125 | 4000 | milky | white | | 1162/1162/52 | >> 939266 |
| 65 | 9125 | 4000 | milky | black | yes | 1162/1162/52 | >> 938764 |
| 65 | 9225 | 4000 | transparent | black | | 1162/1162/52 | >> 938108 |
| 65 | 9225 | 4000 | transparent | black | yes | 1162/1162/52 | >> 938641 |
| 116 | 15475 | 3000 | milky | black | yes | 1162/1162/52 | >> 939150 |
| 116 | 15475 | 3000 | milky | black | | 1162/1162/52 | >> 938955 |
| 116 | 15800 | 3000 | transparent | black | | 1162/1162/52 | >> 938894 |
| 116 | 15800 | 3000 | transparent | black | yes | 1162/1162/52 | >> 939099 |
| 116 | 16275 | 4000 | milky | grey | | 1162/1162/52 | >> 939259 |
| 116 | 16275 | 4000 | milky | black | | 1162/1162/52 | >> 938559 |
| 116 | 16275 | 4000 | milky | white | | 1162/1162/52 | >> 939242 |
| 116 | 16275 | 4000 | milky | black | yes | 1162/1162/52 | >> 938757 |
| 116 | 16450 | 4000 | transparent | black | yes | 1162/1162/52 | >> 938696 |
| 116 | 16450 | 4000 | transparent | black | | 1162/1162/52 | >> 938214 |

Baris SQUARE 40 LED 602/602/52mm

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Colour temperature [K] | Diffuser colour | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|------------------------|-----------------|--------------------|-----------|---------------------------|---------------------------------|
| 32 | 4275 | 3000 | milky | black | yes | 602/602/52 | >> 938528 |
| 32 | 4275 | 3000 | milky | black | | 602/602/52 | >> 938504 |
| 32 | 4375 | 3000 | transparent | black | yes | 602/602/52 | >> 938511 |
| 32 | 4375 | 3000 | transparent | black | | 602/602/52 | >> 938498 |
| 32 | 4500 | 4000 | milky | black | yes | 602/602/52 | >> 938443 |
| 32 | 4500 | 4000 | milky | black | | 602/602/52 | >> 938405 |
| 32 | 4550 | 4000 | transparent | black | yes | 602/602/52 | >> 938436 |
| 32 | 4550 | 4000 | transparent | black | | 602/602/52 | >> 938085 |
| 56 | 7475 | 4000 | milky | black | | 602/602/52 | >> 938337 |
| 56 | 7475 | 3000 | milky | black | yes | 602/602/52 | >> 938351 |

BARIS SQUARE 40 LED

GENERAL CARD

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Colour temperature [K] | Diffuser colour | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|------------------------|-----------------|--------------------|-----------|---------------------------|---------------------------------|
| 56 | 7625 | 3000 | transparent | black | yes | 602/602/52 | >> 938344 |
| 56 | 7625 | 4000 | transparent | black | | 602/602/52 | >> 938320 |
| 56 | 7875 | 4000 | milky | black | yes | 602/602/52 | >> 938313 |
| 56 | 7875 | 4000 | milky | white | | 602/602/52 | >> 939228 |
| 56 | 7875 | 4000 | milky | black | | 602/602/52 | >> 938276 |
| 56 | 7875 | 4000 | milky | grey | | 602/602/52 | >> 939235 |
| 56 | 7950 | 4000 | transparent | black | yes | 602/602/52 | >> 938306 |
| 56 | 7950 | 4000 | transparent | black | | 602/602/52 | >> 938191 |

Baris SQUARE 40 LED 882/882/52mm

| Rated power of the luminaire [W]* | Luminous flux [lm]* | Colour temperature [K] | Diffuser colour | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-----------------------------------|---------------------|------------------------|-----------------|--------------------|-----------|---------------------------|---------------------------------|
| 48 | 6400 | 3000 | milky | black | yes | 882/882/52 | >> 939143 |
| 48 | 6400 | 3000 | milky | black | | 882/882/52 | >> 938948 |
| 48 | 6550 | 3000 | transparent | black | yes | 882/882/52 | >> 939037 |
| 48 | 6550 | 3000 | transparent | black | | 882/882/52 | >> 938832 |
| 48 | 6750 | 4000 | milky | white | | 882/882/52 | >> 939341 |
| 48 | 6750 | 4000 | milky | grey | | 882/882/52 | >> 939358 |
| 48 | 6750 | 4000 | milky | black | | 882/882/52 | >> 938542 |
| 48 | 6750 | 4000 | milky | black | yes | 882/882/52 | >> 938740 |
| 48 | 6800 | 4000 | transparent | black | yes | 882/882/52 | >> 938634 |
| 48 | 6800 | 4000 | transparent | black | | 882/882/52 | >> 938092 |
| 86 | 11475 | 3000 | milky | black | yes | 882/882/52 | >> 939136 |
| 86 | 11475 | 3000 | milky | black | | 882/882/52 | >> 938931 |
| 86 | 11725 | 3000 | transparent | black | yes | 882/882/52 | >> 939082 |
| 86 | 11725 | 3000 | transparent | black | | 882/882/52 | >> 938887 |
| 86 | 12075 | 4000 | milky | black | yes | 882/882/52 | >> 938733 |
| 86 | 12075 | 4000 | milky | white | | 882/882/52 | >> 939327 |
| 86 | 12075 | 4000 | milky | black | | 882/882/52 | >> 938535 |
| 86 | 12075 | 4000 | milky | grey | | 882/882/52 | >> 939334 |
| 86 | 12200 | 4000 | transparent | black | yes | 882/882/52 | >> 938689 |
| 86 | 12200 | 4000 | transparent | black | | 882/882/52 | >> 938207 |

Card creation date: 21 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 211/2023

