

# TERRA 2 LED IOT

GENERAL CARD



## TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	20.00 - 48.00
Luminous flux [lm]*:	2400 - 5400
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
Ingress protection:	IP20
Mounting version:	recessed
Dimensions (H/W/T/S) [mm]:	595/595/32;

## CHARACTERISTICS

Recessed square LED luminaire with high total luminous Flux. Made of powder-coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter), or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

### IoT characteristics

Variants available:

**IoT BT CAS DALI** a built-in **BT CAS** module that allows you to program functions in the CASAMBI app and control in real time, and a **DALI** driver that allows you to dim the light source.

**IoT BT HYT PWM BT HYT** module (built into the driver) allowing you to program functions in the Lena Lighting Clue app and control in real time, and a **PWM** driver for dimming the light source.

**IoT BT PIR HYT DALI** a built-in **BT HYT** module that allows you to program functions in the Lena Lighting Clue app and control in real time; **PIR** motion and daylight sensor and **DALI** driver for dimming the light source.

**IoT BT PIR HYT PWM BT HYT** module (built into the driver) allowing for programming functions in the Lena Lighting Clue application and real-time control; **PIR** motion and daylight sensor and **PWM** driver for dimming the light source.

**IoT DS HYT 1-10V** a built-in **DS** daylight sensor and a **1-10V** driver for dimming the light source.

## APPLICATION

General-purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

UGR <19

Unified Glare Rating is an indicator characterizing glare. The lower the Unified Lighting Rating Index (UGR), the lower the glare. In the case of luminaires designed for office spaces, UGR <19, among others improves the comfort of work, reduces errors and fatigue. The UGR value also depends on many factors characterizing the room and the location of the observer. Special computer programs should be used to precisely determine the degree of glare for specific conditions.

# TERRA 2 LED IOT

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### TERRA 2 LED IoT white mat

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	PIR	Version	Dimensions (H/W/T/S) [mm]	Index
20	2400	3000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224232</a>
20	2600	4000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224256</a>
27	3000	3000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224430</a>
27	3200	4000	white mat	yes	BT PIR HYT PWM	595/595/32	<a href="#">&gt;&gt; 242960</a>
31	3300	3000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224270</a>
31	3500	4000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224294</a>
36	3950	3000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224317</a>
36	4200	4000	white mat	yes	BT PIR HYT PWM	595/595/32	<a href="#">&gt;&gt; 224331</a>
41	4450	3000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224355</a>
41	4750	4000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224379</a>
48	5050	3000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224393</a>
48	5400	4000	white mat	yes		595/595/32	<a href="#">&gt;&gt; 224416</a>

### TERRA 2 LED IoT white gloss


Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	PIR	Version	Dimensions (H/W/T/S) [mm]	Index
20	2400	3000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224249</a>
20	2600	4000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224263</a>
27	3000	3000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224447</a>
27	3200	4000	white gloss	yes	BT PIR HYT PWM	595/595/32	<a href="#">&gt;&gt; 242953</a>
31	3300	3000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224287</a>
31	3500	4000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224300</a>
36	3950	3000	white gloss	yes	BT PIR HYT PWM	595/595/32	<a href="#">&gt;&gt; 224324</a>
36	4200	4000	white gloss	yes	BT PIR HYT PWM	595/595/32	<a href="#">&gt;&gt; 224348</a>
41	4450	3000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224362</a>
41	4750	4000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224386</a>
48	5050	3000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224409</a>
48	5400	4000	white gloss	yes		595/595/32	<a href="#">&gt;&gt; 224423</a>

# TERRA 2 LED IOT

GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
<a href="#">999543</a>	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard recessing kit 630x630  
white (steel version) (999543)

Card creation date: 06 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 354/2023; 445/2023

---

### **Terra 2 LED IoT - explanation of the different versions:**

The **IoT BT CAS DALI** version has: a built-in **BT CAS** module that allows you to program functions in the CASAMBI app and control in real time, and a **DALI** driver that allows you to dim the light source.

The **IoT BT HYT PWM** version has: **BT HYT** module (built into the driver) allowing you to program functions in the Lena Lighting Clue app and control in real time, and a **PWM** driver for dimming the light source.

The **IoT BT PIR HYT DALI** version has: a built-in **BT HYT** module that allows you to program functions in the Lena Lighting Clue app and control in real time; **PIR** motion and daylight sensor and **DALI** driver for dimming the light source.

The **IoT BT PIR HYT PWM** version has: **BT HYT** module (built into the driver) allowing for programming functions in the Lena Lighting Clue application and real-time control; **PIR** motion and daylight sensor and **PWM** driver for dimming the light source.

The **IoT DS HYT 1-10V** version has: a built-in **DS** daylight sensor and a **1-10V** driver for dimming the light source.