

TORES LED PC

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Luminous flux [lm]*:	5000 - 10100
Rated power of the luminaire [W]*:	36.00; 50.00; 70.00
Colour temperature [K]:	4000
Material of the body:	PC
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	frozen
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	1200/85/80; 1500/85/80;
Impact resistance:	IK06

CHARACTERISTICS

Tores LED PC is a lamp dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance. Its very good technical parameters guarantee the achievement of the required level of illumination and energy savings. The lamp has a number of improvements to make installation easier and faster, such as adjustable brackets that provide an installation tolerance of +/-50 mm. As standard, it is equipped with durable stainless steel (INOX) clips. The lamp has a high IP65 rating, and the lamp body and shade are UV resistant.

APPLICATION

Multifunctional surface-mounted LED lamp is designed for use in areas with high requirements for dust- and waterproofing. Particularly recommended for illuminating industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underpasses. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions.

TORES LED PC

GENERAL CARD

AVAILABLE VERSIONS

 Click index >>, to see details

TORES LED PC 36W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
36	4000	5000	frozen			1200/85/80	>> 374166
36	4000	5000	frozen	yes		1200/85/80	>> 374319
36	4000	5000	frozen		LS2	1200/85/80	>> 374326



TORES LED PC 50W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
50	4000	7100	frozen			1200/85/80	>> 374173
50	4000	7200	frozen			1500/85/80	>> 374227
50	4000	7100	frozen	yes		1200/85/80	>> 374333
50	4000	7100	frozen		LS2	1200/85/80	>> 374340
50	4000	7200	frozen	yes		1500/85/80	>> 374357
50	4000	7200	frozen		LS2	1500/85/80	>> 374364

TORES LED PC 70W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
70	4000	10100	frozen			1500/85/80	>> 374180
70	4000	10100	frozen	yes		1500/85/80	>> 374371
70	4000	10100	frozen		LS2	1500/85/80	>> 374388

Card creation date: 29 May 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).  Certificate CE - Nr: 171/2023