

# TORES LED PC

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP65
<b>Luminous flux [lm]*:</b>	5000 - 10100
<b>Rated power of the luminaire [W]*:</b>	36.00; 50.00; 70.00
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	frozen
<b>Mounting version:</b>	surface, suspended
<b>Dimensions (H/W/T/S) [mm]:</b>	1200/85/80; 1500/85/80;
<b>Impact resistance:</b>	IK06

## CHARACTERISTICS

Tores LED PC is a lamp dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance. Its very good technical parameters guarantee the achievement of the required level of illumination and energy savings. The lamp has a number of improvements to make installation easier and faster, such as adjustable brackets that provide an installation tolerance of +/-50 mm. As standard, it is equipped with durable stainless steel (INOX) clips. The lamp has a high IP65 rating, and the lamp body and shade are UV resistant.

## APPLICATION

Multifunctional surface-mounted LED lamp is designed for use in areas with high requirements for dust- and waterproofing. Particularly recommended for illuminating industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underpasses. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions.

# TORES LED PC

## GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### TORES LED PC 36W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
36	4000	5000	frozen			1200/85/80	<a href="#">&gt;&gt; 374166</a>
36	4000	5000	frozen	yes		1200/85/80	<a href="#">&gt;&gt; 374319</a>
36	4000	5000	frozen		LS2	1200/85/80	<a href="#">&gt;&gt; 374326</a>

### TORES LED PC 50W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
50	4000	7100	frozen			1200/85/80	<a href="#">&gt;&gt; 374173</a>
50	4000	7200	frozen			1500/85/80	<a href="#">&gt;&gt; 374227</a>
50	4000	7100	frozen	yes		1200/85/80	<a href="#">&gt;&gt; 374333</a>
50	4000	7100	frozen		LS2	1200/85/80	<a href="#">&gt;&gt; 374340</a>
50	4000	7200	frozen	yes		1500/85/80	<a href="#">&gt;&gt; 374357</a>
50	4000	7200	frozen		LS2	1500/85/80	<a href="#">&gt;&gt; 374364</a>

### TORES LED PC 70W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Through wiring	Dimensions (H/W/T/S) [mm]	Index
70	4000	10100	frozen			1500/85/80	<a href="#">&gt;&gt; 374180</a>
70	4000	10100	frozen	yes		1500/85/80	<a href="#">&gt;&gt; 374371</a>
70	4000	10100	frozen		LS2	1500/85/80	<a href="#">&gt;&gt; 374388</a>

Card creation date: 07 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 171/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl