


TERRANO S

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	9.00; 16.00; 22.00; 28.00; 35.00
Luminous flux [lm]*:	1050; 1150; 1750; 2300; 2700
Energy efficiency class:	D; E
Electrical protection class:	I
Colour temperature [K]:	3000; 4000
Diffuser type:	matrix led
Material of the body:	powder coated steel
Colour of the body:	black; white
Dimensions (H/W/T/S) [mm]:	48/566/69; 48/1117/69;
Ingress protection:	IP20

CHARACTERISTICS

The new Terrano S linear luminaire, thanks to the use of the latest generation of LED modules, is characterized by energy efficiency and excellent technical parameters. Equipped with focusing lenses, Terrano S lamps are sight-friendly and effectively reduce glare (UGR of 12-19). Mounted in a busbar system, they are available in two color temperatures of 3000 K and 4000 K and two color versions: white and black. DALI version available on request.

APPLICATION

Mounting on a rail system, increases the range of applications of this lamp and allows the user to make rearrangements, even after installation. The lamp has an adapter equipped with mechanical catches that make it easy to plug in, unplug and move the lamps, while ensuring that the fixture is securely held in the rail. The lamps, together with appropriately selected rails and components, allow for ceiling or wall mounting. The Terrano S lamp is perfect as a source of light in offices, stores, dressing rooms, in passageways.

TERRANO S

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

TERRANO S 48/1117/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	3000	3000	black	48/1117/69	>> 577161
28	3200	4000	black	48/1117/69	>> 577246
28	3300	3000	white	48/1117/69	>> 577208
28	3500	4000	white	48/1117/69	>> 577284
35	3700	3000	black	48/1117/69	>> 577178
35	3900	4000	black	48/1117/69	>> 577253
35	4100	3000	white	48/1117/69	>> 577215
35	4300	4000	white	48/1117/69	>> 577291
40	4100	3000	black	48/1117/69	>> 577185
40	4400	4000	black	48/1117/69	>> 577260
40	4600	3000	white	48/1117/69	>> 577222
40	4800	4000	white	48/1117/69	>> 577307
56	5400	3000	black	48/1117/69	>> 577192
56	5700	4000	black	48/1117/69	>> 577277
56	5900	3000	white	48/1117/69	>> 577239
56	6300	4000	white	48/1117/69	>> 577314

TERRANO S 48/566/69mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
9	1050	3000	black	48/566/69	>> 577000
9	1100	4000	black	48/566/69	>> 577086
9	1150	3000	white	48/566/69	>> 577048
9	1200	4000	white	48/566/69	>> 577123
16	1750	3000	black	48/566/69	>> 577017
16	1850	4000	black	48/566/69	>> 577093
16	1950	3000	white	48/566/69	>> 577055
16	2050	4000	white	48/566/69	>> 577130
22	2300	3000	black	48/566/69	>> 577024
22	2400	4000	black	48/566/69	>> 577109
22	2500	3000	white	48/566/69	>> 577062
22	2650	4000	white	48/566/69	>> 577147
28	2700	3000	black	48/566/69	>> 577031
28	2850	4000	black	48/566/69	>> 577116
28	2950	3000	white	48/566/69	>> 577079

TERRANO S

GENERAL CARD

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
28	3150	4000	white	48/566/69	>> 577154

Card creation date: 10 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 06/2023; 303/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

