


# RQ 220 LED N PLUS

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Rated power of the luminaire [W]*:</b>	17.00
<b>Luminous flux [lm]*:</b>	2050 - 2450
<b>Energy efficiency class:</b>	C; D
<b>Electrical protection class:</b>	I; II
<b>Colour temperature [K]:</b>	3000; 4000
<b>Beam angle [°]:</b>	110; 115
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PRM; matt
<b>Material of the body:</b>	ABS
<b>Colour of the body:</b>	white
<b>Dimensions (H/W/T/S) [mm]:</b>	227/227/86; 232/232/100;

## CHARACTERISTICS

RQ 220 LED N PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# RQ 220 LED N PLUS

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser type	Ingress protection	DIMM DALI	Emergency lighting [h]	Autotest	Dimensions (H/W/T/S) [mm]	Index
17	2050	3000	matt	IP20				227/227/86	<a href="#">&gt;&gt; 947414</a>
17	2050	3000	matt	IP20		3	yes	227/227/86	<a href="#">&gt;&gt; 947421</a>
17	2050	3000	matt	IP20	yes			227/227/86	<a href="#">&gt;&gt; 947438</a>
17	2050	3000	matt	IP44	yes			232/232/100	<a href="#">&gt;&gt; 947537</a>
17	2050	3000	matt	IP44				232/232/100	<a href="#">&gt;&gt; 947520</a>
17	2050	3000	matt	IP44		3	yes	232/232/100	<a href="#">&gt;&gt; 947513</a>
17	2200	4000	matt	IP20		3	yes	227/227/86	<a href="#">&gt;&gt; 947391</a>
17	2200	4000	matt	IP44	yes			232/232/100	<a href="#">&gt;&gt; 947568</a>
17	2200	4000	matt	IP44				232/232/100	<a href="#">&gt;&gt; 947551</a>
17	2200	4000	matt	IP44		3	yes	232/232/100	<a href="#">&gt;&gt; 947544</a>
17	2200	4000	matt	IP20	yes			227/227/86	<a href="#">&gt;&gt; 947407</a>
17	2200	4000	matt	IP20				227/227/86	<a href="#">&gt;&gt; 947384</a>
17	2300	3000	PRM	IP20		3	yes	227/227/86	<a href="#">&gt;&gt; 947483</a>
17	2300	3000	PRM	IP20	yes			227/227/86	<a href="#">&gt;&gt; 947490</a>
17	2300	3000	PRM	IP20				227/227/86	<a href="#">&gt;&gt; 947476</a>
17	2300	3000	PRM	IP44				232/232/100	<a href="#">&gt;&gt; 947575</a>
17	2300	3000	PRM	IP44		3	yes	232/232/100	<a href="#">&gt;&gt; 947582</a>
17	2300	3000	PRM	IP44	yes			232/232/100	<a href="#">&gt;&gt; 947605</a>
17	2450	4000	PRM	IP20	yes			227/227/86	<a href="#">&gt;&gt; 947469</a>
17	2450	4000	PRM	IP20		3	yes	227/227/86	<a href="#">&gt;&gt; 947452</a>
17	2450	4000	PRM	IP20				227/227/86	<a href="#">&gt;&gt; 947445</a>
17	2450	4000	PRM	IP44		3	yes	232/232/100	<a href="#">&gt;&gt; 947612</a>
17	2450	4000	PRM	IP44				232/232/100	<a href="#">&gt;&gt; 947896</a>
17	2450	4000	PRM	IP44	yes			232/232/100	<a href="#">&gt;&gt; 947902</a>

# RQ 220 LED N PLUS

GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
947353	Suspension RQ220 f100 white ON/OFF. DALI

Card creation date: 05 November 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 297/2023; 30/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl