

RQ 220 LED N PLUS

GENERAL CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	17.00
Luminous flux [lm]*:	2050 - 2450
Energy efficiency class:	C; D
Electrical protection class:	I; II
Colour temperature [K]:	3000; 4000
Beam angle [°]:	110; 115
Diffuser material:	PC
Diffuser type:	PRM; matt
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	227/227/86; 232/232/100;

CHARACTERISTICS

RQ 220 LED N PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

RQ 220 LED N PLUS

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Diffuser type	Ingress protection	DIMM DALI	Emergency lighting [h]	Autotest	Dimensions (H/W/T/S) [mm]	Index
17	2050	3000	matt	IP20				227/227/86	>> 947414
17	2050	3000	matt	IP20		3	yes	227/227/86	>> 947421
17	2050	3000	matt	IP20	yes			227/227/86	>> 947438
17	2050	3000	matt	IP44	yes			232/232/100	>> 947537
17	2050	3000	matt	IP44				232/232/100	>> 947520
17	2050	3000	matt	IP44		3	yes	232/232/100	>> 947513
17	2200	4000	matt	IP20		3	yes	227/227/86	>> 947391
17	2200	4000	matt	IP44	yes			232/232/100	>> 947568
17	2200	4000	matt	IP44				232/232/100	>> 947551
17	2200	4000	matt	IP44		3	yes	232/232/100	>> 947544
17	2200	4000	matt	IP20	yes			227/227/86	>> 947407
17	2200	4000	matt	IP20				227/227/86	>> 947384
17	2300	3000	PRM	IP20		3	yes	227/227/86	>> 947483
17	2300	3000	PRM	IP20	yes			227/227/86	>> 947490
17	2300	3000	PRM	IP20				227/227/86	>> 947476
17	2300	3000	PRM	IP44				232/232/100	>> 947575
17	2300	3000	PRM	IP44		3	yes	232/232/100	>> 947582
17	2300	3000	PRM	IP44	yes			232/232/100	>> 947605
17	2450	4000	PRM	IP20	yes			227/227/86	>> 947469
17	2450	4000	PRM	IP20		3	yes	227/227/86	>> 947452
17	2450	4000	PRM	IP20				227/227/86	>> 947445
17	2450	4000	PRM	IP44		3	yes	232/232/100	>> 947612
17	2450	4000	PRM	IP44				232/232/100	>> 947896
17	2450	4000	PRM	IP44	yes			232/232/100	>> 947902

RQ 220 LED N PLUS

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
947353	Suspension RQ220 f100 white ON/OFF. DALI

Card creation date: 05 November 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 297/2023; 30/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl