

# ALTEZZO L 100 K

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Rated power of the luminaire [W]*:</b>	5.00
<b>Luminous flux [lm]*:</b>	600 - 650
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK08
<b>Colour temperature [K]:</b>	3000; 4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	RAL7016
<b>Diffuser material:</b>	PC
<b>Beam angle [°]:</b>	110
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	40/100/250;
<b>CE certificate:</b>	183/2023

## CHARACTERISTICS

The Altezzo L 100 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with two light color temperatures of 3000 K and 4000 K.

## APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

# ALTEZZO L 100 K

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Beam angle [°]	Dimensions (H/W/T/S) [mm]	Index
5	650	4000	110	40/100/250	<a href="#">&gt;&gt; 984341</a>
5	600	3000	110	40/100/250	<a href="#">&gt;&gt; 984358</a>

Card creation date: 22 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 17/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl