ALTEZZO L 150 K

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	40.00
Luminous flux [lm]*:	4600 - 5200
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	2700; 3000; 4000
Color rendering index (Ra) >:	70
Beam angle [°]:	110

CHARACTERISTICS

The Altezzo L 150 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with three light color temperatures2700 K 3000 K and 4000 K.

APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

ALTEZZO L 150 K

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Beam angle [°]	Dimensions (H/W/T/S) [mm]	Index
40	5200	4000	110	150/150/500	>> 984365
40	4900	3000	110	150/150/500	>> 984372
40	4600	2700	110	150/150/500	>> 984389

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 181/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl