

# ALTEZZO L 150 K

## GENERAL CARD



### TECHNICAL PARAMETERS

<b>Rated power of the luminaire [W]*:</b>	40.00
<b>Luminous flux [lm]*:</b>	4600 - 5200
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK08
<b>Colour temperature [K]:</b>	2700; 3000; 4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	RAL7016
<b>Diffuser material:</b>	PC
<b>Beam angle [°]:</b>	110
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	150/150/500;

### CHARACTERISTICS

The Altezzo L 150 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with three light color temperatures 2700 K 3000 K and 4000 K.

### APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

# ALTEZZO L 150 K

## GENERAL CARD

## AVAILABLE VERSIONS

 Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	Beam angle [°]	Dimensions (H/W/T/S) [mm]	Index
40	5200	4000	110	150/150/500	<a href="#">&gt;&gt; 984365</a>
40	4900	3000	110	150/150/500	<a href="#">&gt;&gt; 984372</a>
40	4600	2700	110	150/150/500	<a href="#">&gt;&gt; 984389</a>