

# MESSAGGIO

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Rated power [W] - range:</b>	18 - 64
<b>Luminous flux of the luminaire [lm] - range:</b>	1900 - 3300 - 5700
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	2700; 3000; 4000
<b>Diffuser material:</b>	PC
<b>Material of the body:</b>	Steel
<b>Colour of the body:</b>	RAL2004/4003; RAL5025/4011; RAL8029/1035; black; white
<b>Ingress protection:</b>	IP20
<b>Dimensions (H/W/T/S) [mm]:</b>	1230/701/80; 1230/1261/80; 1230/1541/80;
<b>Rated power of the luminaire [W]*:</b>	18.00; 35.00; 57.00; 64.00
<b>Luminous flux [lm]*:</b>	1000; 2950; 3950; 4300

## CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

## APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

## AVAILABLE VERSIONS



Click index >>, to see details

### Messaggio 1230/1261/80mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
33 - 57	1900 - 3300	4000	RAL8029/1035		1230/1261/80	<a href="#">&gt;&gt; 579332</a>
33 - 57	2000 - 3300	2700	black		1230/1261/80	<a href="#">&gt;&gt; 578045</a>
33 - 57	2000 - 3300	3000	black		1230/1261/80	<a href="#">&gt;&gt; 575587</a>
33 - 57	2000 - 3300	4000	black		1230/1261/80	<a href="#">&gt;&gt; 575082</a>
33 - 57	2000 - 3500	4000	RAL5025/4011		1230/1261/80	<a href="#">&gt;&gt; 579196</a>
33 - 57	2300 - 3950	4000	RAL2004/4003		1230/1261/80	<a href="#">&gt;&gt; 579059</a>
33 - 57	3300 - 5400	2700	white		1230/1261/80	<a href="#">&gt;&gt; 578021</a>
33 - 57	3300 - 5400	3000	white		1230/1261/80	<a href="#">&gt;&gt; 575563</a>
33 - 57	3300 - 5400	4000	white		1230/1261/80	<a href="#">&gt;&gt; 575068</a>
57	2700	4000	RAL5025/4011	yes	1230/1261/80	<a href="#">&gt;&gt; 579189</a>
57	3300	2700	black	yes	1230/1261/80	<a href="#">&gt;&gt; 578052</a>
57	3300	3000	black	yes	1230/1261/80	<a href="#">&gt;&gt; 575594</a>
57	3300	4000	black	yes	1230/1261/80	<a href="#">&gt;&gt; 575099</a>
57	3300	4000	RAL8029/1035	yes	1230/1261/80	<a href="#">&gt;&gt; 579325</a>
57	3650	4000	RAL9016/2004	yes	1230/1261/80	<a href="#">&gt;&gt; 579448</a>
57	3950	4000	RAL2004/4003	yes	1230/1261/80	<a href="#">&gt;&gt; 579042</a>
57	5400	2700	white	yes	1230/1261/80	<a href="#">&gt;&gt; 578038</a>
57	5400	3000	white	yes	1230/1261/80	<a href="#">&gt;&gt; 575570</a>
57	5400	4000	white	yes	1230/1261/80	<a href="#">&gt;&gt; 575075</a>

### Messaggio 1230/1541/80mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
35 - 64	1700 - 2950	4000	RAL5025/4011		1230/1541/80	<a href="#">&gt;&gt; 579172</a>
35 - 64	2000 - 3400	2700	black		1230/1541/80	<a href="#">&gt;&gt; 578083</a>
35 - 64	2000 - 3400	3000	black		1230/1541/80	<a href="#">&gt;&gt; 575624</a>
35 - 64	2000 - 3400	4000	black		1230/1541/80	<a href="#">&gt;&gt; 575143</a>
35 - 64	2050 - 3600	4000	RAL8029/1035		1230/1541/80	<a href="#">&gt;&gt; 579318</a>
35 - 64	2500 - 4300	4000	RAL2004/4003		1230/1541/80	<a href="#">&gt;&gt; 579035</a>
35 - 64	2500-4450	4000	RAL3018/2004		1230/1541/80	<a href="#">&gt;&gt; 579479</a>
35 - 64	2500-4450	4000	RAL9005/2004		1230/1541/80	<a href="#">&gt;&gt; 579462</a>
35 - 64	3200 - 5700	2700	white		1230/1541/80	<a href="#">&gt;&gt; 578069</a>
35 - 64	3200 - 5700	3000	white		1230/1541/80	<a href="#">&gt;&gt; 575600</a>
35 - 64	3200 - 5700	4000	white		1230/1541/80	<a href="#">&gt;&gt; 575129</a>
64	2950	4000	RAL5025/4011	yes	1230/1541/80	<a href="#">&gt;&gt; 579165</a>

# MESSAGGIO

## GENERAL CARD

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
64	3400	2700	black	yes	1230/1541/80	<a href="#">&gt;&gt; 578090</a>
64	3400	3000	black	yes	1230/1541/80	<a href="#">&gt;&gt; 575631</a>
64	3400	4000	black	yes	1230/1541/80	<a href="#">&gt;&gt; 575150</a>
64	3600	4000	RAL8029/1035	yes	1230/1541/80	<a href="#">&gt;&gt; 579301</a>
64	4300	4000	RAL2004/4003	yes	1230/1541/80	<a href="#">&gt;&gt; 579028</a>
64	4450	4000	RAL9016/4003	yes	1230/1541/80	<a href="#">&gt;&gt; 579455</a>
64	5700	2700	white	yes	1230/1541/80	<a href="#">&gt;&gt; 578076</a>
64	5700	3000	white	yes	1230/1541/80	<a href="#">&gt;&gt; 575617</a>
64	5700	4000	white	yes	1230/1541/80	<a href="#">&gt;&gt; 575136</a>

## Messaggio 1230/701/80mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
18	1000	4000	RAL2004/4003		1230/701/80	<a href="#">&gt;&gt; 579066</a>
18	1100	2700	black		1230/701/80	<a href="#">&gt;&gt; 578014</a>
18	1100	3000	black		1230/701/80	<a href="#">&gt;&gt; 575556</a>
18	1100	4000	black		1230/701/80	<a href="#">&gt;&gt; 575020</a>
18	1900	2700	white		1230/701/80	<a href="#">&gt;&gt; 578007</a>
18	1900	3000	white		1230/701/80	<a href="#">&gt;&gt; 575549</a>
18	1900	4000	white		1230/701/80	<a href="#">&gt;&gt; 575006</a>
18	670	4000	RAL5025/4011		1230/701/80	<a href="#">&gt;&gt; 579202</a>
18	830	4000	RAL8029/1035		1230/701/80	<a href="#">&gt;&gt; 579349</a>

Card creation date: 19 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 207/2023