

MESSAGGIO KINKIET

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|---|---|
| Rated power [W] - range: | 18; 33 - 57; 35 - 64; 57; 64 |
| Luminous flux of the luminaire [lm] - range: | 670 - 5700 |
| Electrical protection class: | I |
| Colour temperature [K]: | 2700; 3000; 4000 |
| Diffuser material: | PC |
| Diffuser type: | OPAL |
| Diffuser colour: | milky |
| Material of the body: | Steel |
| Colour of the body: | RAL2004/4003; RAL5025/4011; RAL8029/1035; black; white |
| Ingress protection: | IP20 |
| Mounting dimensions [mm]: | 340 |
| Dimensions (H/W/T/S) [mm]: | 128/701/106; 128/1261/106; 128/1541/70; |

CHARACTERISTICS

Wall lamps from the Messaggio collection, available in a variety of colors and sizes, can create spectacular light and decorative compositions, designed according to the architect's individual concepts. The LED modules used in the lamps ensure a high level of energy efficiency. The steel, solid, yet visually delicate housing can be painted in the interior and exterior parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO KINKIET

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Messaggio Kinkiet 128/1261/106mm

| Rated power [W] - range | Luminous flux of the luminaire [lm] - range | Colour temperature [K] | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-------------------------|---|------------------------|--------------------|-----------|---------------------------|---------------------------------|
| 33 - 57 | 3300 - 5400 | 2700 | white | | 128/1261/106 | >> 578120 |
| 33 - 57 | 2000 - 3300 | 2700 | black | | 128/1261/106 | >> 578144 |
| 33 - 57 | 3300 - 5400 | 3000 | white | | 128/1261/106 | >> 575662 |
| 33 - 57 | 2000 - 3300 | 3000 | black | | 128/1261/106 | >> 575686 |
| 33 - 57 | 3300 - 5400 | 4000 | white | | 128/1261/106 | >> 575242 |
| 33 - 57 | 2000 - 3300 | 4000 | black | | 128/1261/106 | >> 575266 |
| 33 - 57 | 1550 - 2700 | 4000 | RAL5025/4011 | | 128/1261/106 | >> 579264 |
| 33 - 57 | 1900 - 3300 | 4000 | RAL8029/1035 | | 128/1261/106 | >> 579400 |
| 33 - 57 | 2300 - 3950 | 4000 | RAL2004/4003 | | 128/1261/106 | >> 579127 |
| 57 | 5400 | 2700 | white | yes | 128/1261/106 | >> 578137 |
| 57 | 3300 | 2700 | black | yes | 128/1261/106 | >> 578151 |
| 57 | 5400 | 3000 | white | yes | 128/1261/106 | >> 575679 |
| 57 | 3300 | 3000 | black | yes | 128/1261/106 | >> 575693 |
| 57 | 5400 | 4000 | white | yes | 128/1261/106 | >> 575259 |
| 57 | 3300 | 4000 | black | yes | 128/1261/106 | >> 575273 |
| 57 | 2700 | 4000 | RAL5025/4011 | yes | 128/1261/106 | >> 579257 |
| 57 | 3300 | 4000 | RAL8029/1035 | yes | 128/1261/106 | >> 579394 |
| 57 | 3950 | 4000 | RAL2004/4003 | yes | 128/1261/106 | >> 579110 |

Messaggio Kinkiet 128/1541/70mm

| Rated power [W] - range | Luminous flux of the luminaire [lm] - range | Colour temperature [K] | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-------------------------|---|------------------------|--------------------|-----------|---------------------------|---------------------------------|
| 35 - 64 | 3200 - 5700 | 2700 | white | | 128/1541/70 | >> 578168 |
| 35 - 64 | 2000 - 3400 | 2700 | black | | 128/1541/70 | >> 578182 |
| 35 - 64 | 3200 - 5700 | 3000 | white | | 128/1541/70 | >> 575709 |
| 35 - 64 | 2000 - 3400 | 3000 | black | | 128/1541/70 | >> 575723 |
| 35 - 64 | 3200 - 5700 | 4000 | white | | 128/1541/70 | >> 575303 |
| 35 - 64 | 2000 - 3400 | 4000 | black | | 128/1541/70 | >> 575327 |
| 35 - 64 | 1700 - 2950 | 4000 | RAL5025/4011 | | 128/1541/70 | >> 579240 |
| 35 - 64 | 2050 - 3600 | 4000 | RAL8029/1035 | | 128/1541/70 | >> 579387 |
| 35 - 64 | 2500 - 4300 | 4000 | RAL2004/4003 | | 128/1541/70 | >> 579103 |
| 64 | 5700 | 2700 | white | yes | 128/1541/70 | >> 578175 |
| 64 | 3400 | 2700 | black | yes | 128/1541/70 | >> 578199 |
| 64 | 5700 | 3000 | white | yes | 128/1541/70 | >> 575716 |
| 64 | 3400 | 3000 | black | yes | 128/1541/70 | >> 575730 |

MESSAGGIO KINKIET

GENERAL CARD

| Rated power [W] - range | Luminous flux of the luminaire [lm] - range | Colour temperature [K] | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-------------------------|---|------------------------|--------------------|-----------|---------------------------|---------------------------------|
| 64 | 5700 | 4000 | white | yes | 128/1541/70 | >> 575310 |
| 64 | 2950 | 4000 | RAL5025/4011 | yes | 128/1541/70 | >> 579233 |
| 64 | 3600 | 4000 | RAL8029/1035 | yes | 128/1541/70 | >> 579370 |
| 64 | 4300 | 4000 | RAL2004/4003 | yes | 128/1541/70 | >> 579097 |

Messaggio Kinkiet 128/701/106mm

| Rated power [W] - range | Luminous flux of the luminaire [lm] - range | Colour temperature [K] | Colour of the body | DIMM DALI | Dimensions (H/W/T/S) [mm] | Index |
|-------------------------|---|------------------------|--------------------|-----------|---------------------------|---------------------------------|
| 18 | 1900 | 2700 | white | | 128/701/106 | >> 578106 |
| 18 | 1100 | 2700 | black | | 128/701/106 | >> 578113 |
| 18 | 1900 | 3000 | white | | 128/701/106 | >> 575648 |
| 18 | 1100 | 3000 | black | | 128/701/106 | >> 575655 |
| 18 | 1900 | 4000 | white | | 128/701/106 | >> 575181 |
| 18 | 1100 | 4000 | black | | 128/701/106 | >> 575204 |
| 18 | 1000 | 4000 | RAL2004/4003 | | 128/701/106 | >> 579134 |
| 18 | 670 | 4000 | RAL5025/4011 | | 128/701/106 | >> 579271 |
| 18 | 830 | 4000 | RAL8029/1035 | | 128/701/106 | >> 579417 |

Card creation date: 05 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 208/2023