

# MESSAGGIO KINKIET

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Rated power [W] - range:</b>	18; 33 - 57; 35 - 64; 57; 64
<b>Luminous flux of the luminaire [lm] - range:</b>	670 - 5700
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	2700; 3000; 4000
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL
<b>Diffuser colour:</b>	milky
<b>Material of the body:</b>	Steel
<b>Colour of the body:</b>	RAL2004/4003; RAL5025/4011; RAL8029/1035; black; white
<b>Ingress protection:</b>	IP20
<b>Mounting dimensions [mm]:</b>	340
<b>Dimensions (H/W/T/S) [mm]:</b>	128/701/106; 128/1261/106; 128/1541/70;

## CHARACTERISTICS

Wall lamps from the Messaggio collection, available in a variety of colors and sizes, can create spectacular light and decorative compositions, designed according to the architect's individual concepts. The LED modules used in the lamps ensure a high level of energy efficiency. The steel, solid, yet visually delicate housing can be painted in the interior and exterior parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the luminous flux.

## APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

# MESSAGGIO KINKIET

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### Messaggio Kinkiet 128/1261/106mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
33 - 57	3300 - 5400	2700	white		128/1261/106	<a href="#">&gt;&gt; 578120</a>
33 - 57	2000 - 3300	2700	black		128/1261/106	<a href="#">&gt;&gt; 578144</a>
33 - 57	3300 - 5400	3000	white		128/1261/106	<a href="#">&gt;&gt; 575662</a>
33 - 57	2000 - 3300	3000	black		128/1261/106	<a href="#">&gt;&gt; 575686</a>
33 - 57	3300 - 5400	4000	white		128/1261/106	<a href="#">&gt;&gt; 575242</a>
33 - 57	2000 - 3300	4000	black		128/1261/106	<a href="#">&gt;&gt; 575266</a>
33 - 57	1550 - 2700	4000	RAL5025/4011		128/1261/106	<a href="#">&gt;&gt; 579264</a>
33 - 57	1900 - 3300	4000	RAL8029/1035		128/1261/106	<a href="#">&gt;&gt; 579400</a>
33 - 57	2300 - 3950	4000	RAL2004/4003		128/1261/106	<a href="#">&gt;&gt; 579127</a>
57	5400	2700	white	yes	128/1261/106	<a href="#">&gt;&gt; 578137</a>
57	3300	2700	black	yes	128/1261/106	<a href="#">&gt;&gt; 578151</a>
57	5400	3000	white	yes	128/1261/106	<a href="#">&gt;&gt; 575679</a>
57	3300	3000	black	yes	128/1261/106	<a href="#">&gt;&gt; 575693</a>
57	5400	4000	white	yes	128/1261/106	<a href="#">&gt;&gt; 575259</a>
57	3300	4000	black	yes	128/1261/106	<a href="#">&gt;&gt; 575273</a>
57	2700	4000	RAL5025/4011	yes	128/1261/106	<a href="#">&gt;&gt; 579257</a>
57	3300	4000	RAL8029/1035	yes	128/1261/106	<a href="#">&gt;&gt; 579394</a>
57	3950	4000	RAL2004/4003	yes	128/1261/106	<a href="#">&gt;&gt; 579110</a>

### Messaggio Kinkiet 128/1541/70mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
35 - 64	3200 - 5700	2700	white		128/1541/70	<a href="#">&gt;&gt; 578168</a>
35 - 64	2000 - 3400	2700	black		128/1541/70	<a href="#">&gt;&gt; 578182</a>
35 - 64	3200 - 5700	3000	white		128/1541/70	<a href="#">&gt;&gt; 575709</a>
35 - 64	2000 - 3400	3000	black		128/1541/70	<a href="#">&gt;&gt; 575723</a>
35 - 64	3200 - 5700	4000	white		128/1541/70	<a href="#">&gt;&gt; 575303</a>
35 - 64	2000 - 3400	4000	black		128/1541/70	<a href="#">&gt;&gt; 575327</a>
35 - 64	1700 - 2950	4000	RAL5025/4011		128/1541/70	<a href="#">&gt;&gt; 579240</a>
35 - 64	2050 - 3600	4000	RAL8029/1035		128/1541/70	<a href="#">&gt;&gt; 579387</a>
35 - 64	2500 - 4300	4000	RAL2004/4003		128/1541/70	<a href="#">&gt;&gt; 579103</a>
64	5700	2700	white	yes	128/1541/70	<a href="#">&gt;&gt; 578175</a>
64	3400	2700	black	yes	128/1541/70	<a href="#">&gt;&gt; 578199</a>
64	5700	3000	white	yes	128/1541/70	<a href="#">&gt;&gt; 575716</a>
64	3400	3000	black	yes	128/1541/70	<a href="#">&gt;&gt; 575730</a>

# MESSAGGIO KINKIET

## GENERAL CARD

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
64	5700	4000	white	yes	128/1541/70	<a href="#">&gt;&gt; 575310</a>
64	2950	4000	RAL5025/4011	yes	128/1541/70	<a href="#">&gt;&gt; 579233</a>
64	3600	4000	RAL8029/1035	yes	128/1541/70	<a href="#">&gt;&gt; 579370</a>
64	4300	4000	RAL2004/4003	yes	128/1541/70	<a href="#">&gt;&gt; 579097</a>

## Messaggio Kinkiet 128/701/106mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
18	1900	2700	white		128/701/106	<a href="#">&gt;&gt; 578106</a>
18	1100	2700	black		128/701/106	<a href="#">&gt;&gt; 578113</a>
18	1900	3000	white		128/701/106	<a href="#">&gt;&gt; 575648</a>
18	1100	3000	black		128/701/106	<a href="#">&gt;&gt; 575655</a>
18	1900	4000	white		128/701/106	<a href="#">&gt;&gt; 575181</a>
18	1100	4000	black		128/701/106	<a href="#">&gt;&gt; 575204</a>
18	1000	4000	RAL2004/4003		128/701/106	<a href="#">&gt;&gt; 579134</a>
18	670	4000	RAL5025/4011		128/701/106	<a href="#">&gt;&gt; 579271</a>
18	830	4000	RAL8029/1035		128/701/106	<a href="#">&gt;&gt; 579417</a>

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 208/2023