

MESSAGGIO KINKIET

GENERAL CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	18; 33 - 57; 35 - 64; 57; 64
Luminous flux of the luminaire [lm] - range:	670 - 5700
Electrical protection class:	I
Colour temperature [K]:	2700; 3000; 4000
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	RAL2004/4003; RAL5025/4011; RAL8029/1035; black; white
Ingress protection:	IP20
Mounting dimensions [mm]:	340
Dimensions (H/W/T/S) [mm]:	128/701/106; 128/1261/106; 128/1541/70;

CHARACTERISTICS

Wall lamps from the Messaggio collection, available in a variety of colors and sizes, can create spectacular light and decorative compositions, designed according to the architect's individual concepts. The LED modules used in the lamps ensure a high level of energy efficiency. The steel, solid, yet visually delicate housing can be painted in the interior and exterior parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO KINKIET

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Messaggio Kinkiet 128/1261/106mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
33 - 57	3300 - 5400	2700	white		128/1261/106	>> 578120
33 - 57	2000 - 3300	2700	black		128/1261/106	>> 578144
33 - 57	3300 - 5400	3000	white		128/1261/106	>> 575662
33 - 57	2000 - 3300	3000	black		128/1261/106	>> 575686
33 - 57	3300 - 5400	4000	white		128/1261/106	>> 575242
33 - 57	2000 - 3300	4000	black		128/1261/106	>> 575266
33 - 57	1550 - 2700	4000	RAL5025/4011		128/1261/106	>> 579264
33 - 57	1900 - 3300	4000	RAL8029/1035		128/1261/106	>> 579400
33 - 57	2300 - 3950	4000	RAL2004/4003		128/1261/106	>> 579127
57	5400	2700	white	yes	128/1261/106	>> 578137
57	3300	2700	black	yes	128/1261/106	>> 578151
57	5400	3000	white	yes	128/1261/106	>> 575679
57	3300	3000	black	yes	128/1261/106	>> 575693
57	5400	4000	white	yes	128/1261/106	>> 575259
57	3300	4000	black	yes	128/1261/106	>> 575273
57	2700	4000	RAL5025/4011	yes	128/1261/106	>> 579257
57	3300	4000	RAL8029/1035	yes	128/1261/106	>> 579394
57	3950	4000	RAL2004/4003	yes	128/1261/106	>> 579110

Messaggio Kinkiet 128/1541/70mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
35 - 64	3200 - 5700	2700	white		128/1541/70	>> 578168
35 - 64	2000 - 3400	2700	black		128/1541/70	>> 578182
35 - 64	3200 - 5700	3000	white		128/1541/70	>> 575709
35 - 64	2000 - 3400	3000	black		128/1541/70	>> 575723
35 - 64	3200 - 5700	4000	white		128/1541/70	>> 575303
35 - 64	2000 - 3400	4000	black		128/1541/70	>> 575327
35 - 64	1700 - 2950	4000	RAL5025/4011		128/1541/70	>> 579240
35 - 64	2050 - 3600	4000	RAL8029/1035		128/1541/70	>> 579387
35 - 64	2500 - 4300	4000	RAL2004/4003		128/1541/70	>> 579103
64	5700	2700	white	yes	128/1541/70	>> 578175
64	3400	2700	black	yes	128/1541/70	>> 578199
64	5700	3000	white	yes	128/1541/70	>> 575716
64	3400	3000	black	yes	128/1541/70	>> 575730

MESSAGGIO KINKIET

GENERAL CARD

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
64	5700	4000	white	yes	128/1541/70	>> 575310
64	2950	4000	RAL5025/4011	yes	128/1541/70	>> 579233
64	3600	4000	RAL8029/1035	yes	128/1541/70	>> 579370
64	4300	4000	RAL2004/4003	yes	128/1541/70	>> 579097

Messaggio Kinkiet 128/701/106mm

Rated power [W] - range	Luminous flux of the luminaire [lm] - range	Colour temperature [K]	Colour of the body	DIMM DALI	Dimensions (H/W/T/S) [mm]	Index
18	1900	2700	white		128/701/106	>> 578106
18	1100	2700	black		128/701/106	>> 578113
18	1900	3000	white		128/701/106	>> 575648
18	1100	3000	black		128/701/106	>> 575655
18	1900	4000	white		128/701/106	>> 575181
18	1100	4000	black		128/701/106	>> 575204
18	1000	4000	RAL2004/4003		128/701/106	>> 579134
18	670	4000	RAL5025/4011		128/701/106	>> 579271
18	830	4000	RAL8029/1035		128/701/106	>> 579417

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 208/2023