

MESSAGGIO BRACKET XS

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	2.00
Luminous flux [lm]*:	59; 100
Colour temperature [K]:	2700; 3000; 4000
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	RAL2004/4003; RAL5025/4011; RAL8029/1035; black; white
Ingress protection:	IP20
Dimensions (H/W/T/S) [mm]:	200/130/140;

CHARACTERISTICS

Messaggio small wall sconces surprise with their minimalist form and color personalization option. The lamps can be painted in any shade from the RAL palette and create phenomenal light decorations, designed according to the architect's individual concepts. The lamp housing is made of sturdy but visually delicate steel, while the lampshade is made of milky PC.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the light output.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET XS

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	DIMM DALI	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
2	59	2700		black	200/130/140	>> 578267
2	59	2700	yes	black	200/130/140	>> 578274
2	59	3000		black	200/130/140	>> 575808
2	59	3000	yes	black	200/130/140	>> 575815
2	59	4000		black	200/130/140	>> 575501
2	59	4000	yes	black	200/130/140	>> 575518
2	59	4000		RAL2004/4003	200/130/140	>> 579080
2	59	4000	yes	RAL2004/4003	200/130/140	>> 579073
2	59	4000		RAL5025/4011	200/130/140	>> 579226
2	59	4000	yes	RAL5025/4011	200/130/140	>> 579219
2	59	4000		RAL8029/1035	200/130/140	>> 579363
2	59	4000	yes	RAL8029/1035	200/130/140	>> 579356
2	100	2700		white	200/130/140	>> 578243
2	100	2700	yes	white	200/130/140	>> 578250
2	100	3000		white	200/130/140	>> 575785
2	100	3000	yes	white	200/130/140	>> 575792
2	100	4000		white	200/130/140	>> 575488
2	100	4000	yes	white	200/130/140	>> 575495

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 209/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl