MESSAGGIO STANDING

GENERAL CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	23.00; 44.00
Luminous flux [lm]*:	1400; 1850; 2400; 2700; 4500
Electrical protection class:	I
Colour temperature [K]:	2700; 3000; 4000
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Ingress protection:	IP20

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes standing lamps - the first of their kind in the brand's portfolio. Their minimalist form and the option of color personalization provide a wide range of arrangement possibilities. Lamps based on LED module technology, provide a high level of energy efficiency. The steel, solid yet visually delicate housing can be painted in the inner and outer parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio standing lamps are available with DALI control, which allows to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions that will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO STANDING

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

Messaggio standing 280/1241mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	DIMM DALI	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
23	1400	2700	yes	black	280/1241	>> 578212
23	1900	4000	yes	RAL2004/4003	280/1241	>> 579011
23	1400	4000	yes	RAL5025/4011	280/1241	>> 579158
23	1300	4000	yes	RAL8029/1035	280/1241	>> 579295
23	1400	4000	yes	black	280/1241	>> 575396
23	2400	4000	yes	white	280/1241	>> 575372
23	1400	3000	yes	black	280/1241	>> 575754
23	2400	3000	yes	white	280/1241	>> 575747
23	2400	2700	yes	white	280/1241	>> 578205

Messaggio standing 300/1802mm

Rated power of the luminaire [W]*	Luminous flux [lm]*	Colour temperature [K]	DIMM DALI	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
44	4500	3000	yes	white	300/1802	>> 575761
44	2700	3000	yes	black	300/1802	>> 575778
44	4500	4000	yes	white	300/1802	>> 575433
44	2700	4000	yes	black	300/1802	>> 575457
44	2700	2700	yes	black	300/1802	>> 578236
44	4500	2700	yes	white	300/1802	>> 578229
44	1850	4000	yes	RAL8029/1035	300/1802	>> 579288
44	2650	4000	yes	RAL5025/4011	300/1802	>> 579141
44	1850	4000	yes	RAL2004/4003	300/1802	>> 579004

Card creation date: 21 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 175/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl